THE MOKELUMNE RIVER CHINOOK SALMON AND STEELHEAD MONITORING PROGRAM 1993-1994

Administered by:

East Bay Municipal Utility District Watershed and Recreation Division 500 San Pablo Dam Road Orinda, California 94563

EVALUATION OF THE DOWNSTREAM MIGRATION OF JUVENILE CHINOOK SALMON AND STEELHEAD IN THE LOWER MOKELUMNE RIVER AND THE SACRAMENTO-SAN JOAQUIN DELTA (JANUARY THROUGH JULY 1994)

June 1996

Conducted and Prepared by:

David A. Vogel, Project Manager
Keith R. Marine, Assistant Project Manager
Vogel Environmental Services
21600 Wilcox Road
Red Bluff, California 96080
(916) 527-9587

TABLE OF CONTENTS

TASK OBJECTIVES
METHODS
Downstream Migrant Trapping at Woodbridge Dam
Rotary Screw Fish Traps
Fishway-Installed Downstream Migrant Traps
Fish Handling and Measurements
Trap Maintenance and Debris Management
Trap Calibrations for Abundance Estimates
Abundance and Timing of Emigration
Fish Size and Condition
Physical Environmental Data
Diel Migration Pottern Surveys
Diel Migration Pattern Surveys
Physical Injury Tests at Woodbridge Dam
Coded-Wire Tagging of Wild Smolts at Woodbridge Dam Trap Site
Coded-Wire Tagging of Hatchery Smolts and Delta Survival Experiments
Coded-Wire Tag Summaries and Assessment
Passive Integrated Transponder (PIT) Tags: Assessment of Individual Fish Migration
17
Radio-Telemetry: Assessment of Yearling Steelhead Migration Behavior 17
Physiological Monitoring of Smoltification of Fall Chinook Salmon
RESULTS AND DISCUSSION
Abundance of Downstream Migrant Juvenile Salmonids
Timing of the Downstream Migration of Juvenile Salmonids
Size and Condition of Downstream Migrant Salmon
Effects of Physical Environmental Conditions on Downstream Migrants
Diel Periodicity of Fish Migration Past Woodbridge Dam
Water Temperature, River Flow, Rainfall, Turbidity, and Lunar Phase 40
Comparison of Invenile Solmanid Deventages Migratica Design 1000 1004
Comparison of Juvenile Salmonid Downstream Migration During 1990-1994
Assessment of Physical Injury of Juvenile Chinook Salmon Passing Woodbridge Dam
48
Assessment of Survival of Juvenile Chinook Salmon Migrating Through the Sacramento-
San Joaquin Delta During the Spring of 1994
MRFI Chinook Salmon
Wild Chinook Salmon Smolts Coded-Wire Tagged at Woodbridge Dam 52
Releases of PIT-Tagged Chinook Salmon in Lake Lodi
Radio-Telemetry Assessment of the Migratory Behavior of Juvenile Salmonids Through
Lake Lodi
Lake Lodi Water Quality Monitoring
Physiological Assessment of Smolt Development of Fall Chinook Salmon 60
ACKNOWLEDGMENTS
REFERENCES 66
APPENDICES 67

LIST OF FIGURES

Number	Description	Page
Figure 1.	Map of the Mokelumne River from Camanche Dam to the confluence of the San Joaquin River.	2
Figure 2.	Plan view of Woodbridge Dam showing locations of box trap, inclined plane trap and downstream migrant rotary screw traps.	4
Figure 3.	Schematic diagrams of the incline screen fish trap installed at pool 15 of the high-stage fishway for capturing downstream migrant juvenile salmonids at Woodbridge Dam on the Mokelumne River.	5
Figure 4.	Illustrated implantation of a PIT tag in an anesthetized juvenile chinoook salmon, showing point of insertion through the body was musculature (cutaway view), needle injection angle to implantation site, and position of the implanted PIT tag within body cavity.	18
Figure 5.	Topographical view of the Mokelumne River and Lake Lodi depicting locations of Hydrolab sampling sites, release sites of PIT- and radio tagged- chinook salmon.	19
Figure 6.	Estimated total daily abundance of young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.	28
Figure 7.	Estimated total weekly abundance of young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.	29
Figure 8.	Timing and size of downstream migrant young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.	31
Figure 9.	Timing of total estimated weekly abundance and size of downstream migrant young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.	32
Figure 10.	Weekly counts of juvenile chinook salmon and steelhead trapped at the Woodbridge Dam on the Mokelumne River during January through July 1994.	33
Figure 11.	Daily average, maximum and minimum total lengths of young- of-year chinook salmon captured at Woodbridge Dam during January through July 1994.	35

LIST OF FIGURES (continued)

Number	Description	Page
Figure 12.	Weekly average total length and range in size of yearling chinook salmon captured in rotary crew fish traps and downstream migrant traps installed in the fishways at Woodbridge Dam during the period October 1993 through July 1994.	36
Figure 13.	Hourly abundance estimates and corresponding water temperatures for diel surveys of young-of-year fall chinook salmon migration by Woodbridge Dam during May 1994.	39
Figure 14.	River flow passing Woodbridge Dam, WID canal diversions, daily average turbidity (as measured by Secchi visibility), and rainfall at Woodbridge Dam trap site (RM 39) during January through July 1994.	41
Figure 15.	Hourly water temperatures recorded at Woodbridge Dam during January through July 1994.	42
Figure 16.	Average daily water temperature of the Mokelumne River at Woodbridge Dam during January through July 1994.	43
Figure 17.	Comparison of estimated total daily abundance of young-of-year chinook salmon passing Woodbridge Dam with average daily river flows passing Woodbridge Dam and water clarity (measured as Secchi depth) during January through July 1994.	44
Figure 18.	Comparison of estimated daily total abundance of young-of-year chinook salmon passing Woodbridge Dam with daily water temperatures, lunar cycle, and daily rainfall measured during January through July 1994.	45
Figure 19.	Comparison of weekly counts of downstream migrant chinook salmon at Woodbridge Dam for 1990, 1991, 1992 and 1993 with weekly abundance of young chinook salmon at Woodbridge Dam for 1994.	47
Figure 20.	Water temperature measurements (in Fahrenheit) for Lake Lodi and the Mokelumne River (May 26 to July 25, 1994).	57
Figure 21.	Temporal profile of mean gill Na/K ATPase specific activity from samples of young-of-year fall chinook salmon collected in the rearing reaches and as emigrants passing Woodbridge Dam on the Mokelumne River during March through July 1994.	62

LIST OF TABLES

Number	Description	Page
Table 1.	Trapping Efficiency Test Results for Tandem Rotary Screw Trap System at Woodbridge Dam During January through June 1994.	9
Table 2.	Total numbers of Juvenile Anadromous Salmonids Trapped at the Woodbridge Dam Trap Site During October 1993 through July 1994.	23
Table 3.	Monthly Capture of Incidental Species at the Woodbridge Dam Trap Site During October 1993 through July 1994.	24
Table 4.	Weekly Average Total Length, Range in Lengths, Weight, and Condition Factor for Young-of-Year Chinook Salmon Captured at Woodbridge Dam During January through July 1994.	37
Table 5.	Results of Physical Injury Tests Conducted on Juvenile Chinook Salmon at Woodbridge Dam During the Spring of 1994.	49
Table 6.	Release and Recovery Information for Four Groups of Mokelumne River Fish Installation Coded-Wire Tagged Juvenile Fall-Run Chinook Salmon Captured at the Chipps Island USFWS Trawling Station, Spring 1994.	50
Table 7.	Coded-Wire Tag Release Information for Mokelumne River Fall-Run Chinook Salmon, Spring 1994.	51
Table 8.	Recovery Data for PIT-Tagged Chinook Salmon Released at Various Locations in Lake Lodi and Recovered in Two Fish Traps at Woodbridge Dam.	54
Table 9.	Summary of Results for Releases of Radio-Tagged Juvenile Salmonids in Lake Lodi During the Period of April - July 1994.	55
Table 10.	Comparison of Size, Condition Factor, Gill Na/K ATPase Specific Activity in Samples of Young-of-Year Chinook Salmon Collected in Downstream Migrant Traps at Woodbridge Dam and By Beach Seining in the Rearing Reaches of the Mokelumne river During March through July 1994.	60

LIST OF APPENDICES

Number	Description
Appendix 1.	1993-94 Downstream Migrant Database - October 1993-July 1994
Appendix 2.	1993-94 Downstream Migrant Database - October 1993-July 1994 (Age 0 Fall Chinook Salmon)
Appendix 2. (continued)	June-July 1994 Downstream Migrant Fishway Traps (Age 0 Fall Chinook Salmon)
Appendix 3.	Estimated Daily Abundance of Downstream Migrant Salmon - January- July 1994
Appendix 4.	Size and Condition Database - January-July 1994 (Young-of-Year Salmon)
Appendix 5.	Size and Condition Database - January-July 1994 (Yearling Chinook Salmon)
Appendix 6.	Daily Environmental Conditions - October 1993-July 1994
Appendix 7.	Delta Outflow (in CFS), January 1994 - July 1994
Appendix 8.	Passive-Integrated Transponder Data for Juvenile Chinook Salmon
Appendix 9,	Water Quality Parameters Measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994
Appendix 10.	Fall Chinook Smolt Physiology Data - 1994

TASK OBJECTIVES

This report addresses three tasks of the 1993-94 Mokelumne River Chinook Salmon (Oncorhynchus tshawytscha) and Steelhead (Oncorhynchus mykiss) Monitoring Program:

- Monitoring of downstream-migrant salmonids within the Mokelumne River
- Evaluation of potential physical injury to downstream migrant salmonids passing over spill bays at Woodbridge Dam
- Mark-recapture experiments to determine survival of hatchery-reared chinook salmon smolts migrating through the Sacramento-San Joaquin Delta (Delta).

The purpose of these three tasks was to continue the ongoing development of information on the ecology and management of juvenile anadromous salmonids in the lower Mokelumne River (Figure 1). Task objectives and approaches of the 1993-94 investigation were modified and refined from those of previous years' to address differences in hydrological conditions, as well as investigate some specific aspects of the behavior of downstream migrant juvenile salmonids. Specific objectives of this year's program were as follows:

- To monitor the daily abundance and downstream migratory movement of naturally produced juvenile anadromous salmonids passing Woodbridge Irrigation District's (WID) dam (Woodbridge Dam).
- To monitor size and condition of emigrating juvenile anadromous salmonids and determine the proportions of juvenile salmon emigrating as fry and as smolt-sized salmon.
- 3) To evaluate juvenile anadromous salmonid emigration patterns related to environmental factors (stream flow, water temperature, lunar phase, precipitation, water turbidity, and time of day).
- 4) To assess the effects of juvenile chinook salmon passage over Woodbridge Dam.
- 5) To evaluate some aspects of specific migratory behavior, as measured by radio-telemetry and passive integrated transponder tagged fish, for monitoring juvenile salmonid responses to environmental conditions in the lower Mokelumne River.
- 6) To evaluate the use of a physiological indicator of salmonid smoltification, gill sodium-potassium activated adenosine triphosphatase (gill Na⁺/K⁺ ATPase), for monitoring juvenile salmonid responses to environmental conditions in the lower Mokelumne River.
- To coded-wire tag naturally produced chinook salmon smolts for later assessments of survival and fishery recruitment.
- 8) To assess the relative survival of coded-wire tagged Mokelumne River Fish Installation (MRFI)-reared salmon smolts migrating through the Delta under two water diversion scenarios.
- 9) To evaluate the results of the preceding tasks as related to resource monitoring activities and management recommendations/actions for the lower Mokelumne River.




Figure 1. Map of the Mokelumne River from Camanche Dam to the confluence of the San Joaquin River.

METHODS

Downstream Migrant Trapping at Woodbridge Dam

Rotary Screw Fish Traps

Woodbridge Dam has been used as a trapping site for downstream migrant salmonids since inception of the Mokelumne River Fishery Monitoring Program in 1990. During the 1990 to 1992 study seasons, river flows were low enough that nearly the entire river flow passed through the fishways and fish bypass system at Woodbridge Dam where traps were installed to capture most downstream migrant fishes (Bianchi et al. 1992). During 1993, rotary screw fish traps¹ were first employed to capture downstream migrant salmonids at two locations in the lower Mokelumne River, upstream near the spawning grounds and at Woodbridge Dam. During the downstream migrant monitoring season from October 21, 1993 to June 20, 1994, two 2.4 m diameter rotary screw fish traps in tandem were fished immediately downstream from Woodbridge Dam (Figure 2). The two traps were rigidly connected side-by-side by inserting 1.2 m long pieces of 3 cm square Unistrut through the ends of the tubular fore and aft cross members of both screw traps. These Unistrut "connectors" were bolted into place with the cross members to the traps' pontoons. The trap suspension and operation system at Woodbridge Dam was similar to that described by Vogel and Marine (1994).


Fishway-Installed Downstream Migrant Traps

From June 20 through July 31, 1994, river flows past Woodbridge Dam were reduced and the majority of the flow passed the dam through the high-stage fishway and WID canal diversion fish screen bypass system. During this time period, the California Department of Fish and Game (CDFG) installed a large box trap at the outfall terminus of the fish screen bypass in the low-stage fishway pool #9a to capture 100% of the fish passing through the bypass (see Bianchi et al. 1992 for description of CDFG trap). East Bay Municipal Utility District (EBMUD) staff and Vogel Environmental Services (VES) biologists designed, constructed, and installed an inclined plane fish trap in the high-stage fishway pool #15 to capture 100% of the fish moving through that route of passage (Figure 3).

Fish Handling and Measurements

Rotary screw fish traps, and the Woodbridge Dam fishway-installed traps when in service, were regularly tended twice each day. This was generally done early in the morning and late in the afternoon. During periods of high riverine debris loads and/or large catches of fish, the traps were attended two to three additional times each day, near mid-day and/or mid-evening. Fishes captured were transferred from the trap live boxes with dip nets to 20-liter buckets filled with

E.G. Solutions, Inc., Corvallis, Oregon



Plan view of Woodbridge Dam showing locations of box trap, inclined plane trap and downstream migrant rotary screw traps. Figure 2.




Figure 3. Schematic diagrams of the incline screen fish trap installed in pool 15 of the high-stage fishway for capturing downstream migrant juvenile salmonids at Woodbridge Dam on the Mokelumne River.

fresh river water to which tricaine methane sulfonate² was added at ca. 30-50 milligrams/liter for rapid and short-term induction of moderate sedation for most of the species captured (Summerfelt and Smith 1990). All fishes were identified in the field to species (when possible) and enumerated.

Up to 30 of each salmonid species captured in each trap during each trapping period were randomly sampled for measurements of total length (TL) and fork length (FL) (in mm) and weighed (in grams) on an Ohaus CT1200 portable balance. Weighing was done in tared beakers of fresh water set on the balance pan. Individual sedated fish netted in a small dip net were gently blotted on a moist sponge to remove excess water prior to weighing to ensure measurement of true wet weight. These measurements were recorded along with observations of disease and injury. All adipose fin-clipped salmon (indicating coded-wire tag implants) and salmon otherwise marked that were observed among the fish counted or measured were recorded. Upon completion of counting and measuring fish, fish were gently placed in another 20-liter bucket of fresh river water to recover from sedation prior to being released downstream from the traps (except during June 20 to July 31, 1994 when all fish were transported to Rio Vista, California and released in the Sacramento River). Total processing time for individual fish from sedation and measurement to recovery and release was generally 5 to 15 minutes. Fish were distributed among several buckets to avoid overcrowding and depletion of dissolved oxygen during the processing procedures. To insure dissolved oxygen remained at sufficient levels, water was exchanged in the holding buckets at regular intervals when necessary (about every 5-10 minutes).

Surface water temperature was measured with a mercury-filled thermometer and water clarity was measured with a secchi disk at the trapping site or in Lake Lodi immediately upstream from spill bay #1 each time the traps were attended. Any other relevant biological or environmental conditions potentially affecting trap performance or fish behavior (e.g., incidence of predators, incidence of poaching, debris loads in traps, changes in river flow or spill configurations at Woodbridge Dam) were recorded when observed.

Trap Maintenance and Debris Management

Riverine and urban-generated debris was periodically problematic in the operation of the rotary screw traps downstream from Woodbridge Dam. Of particular importance were large tree limbs and floating lumber. Tree limbs and floating lumber larger than about 40 cm long and 10 cm in diameter entrained into a screw trap usually lodged to stop the rotation of the trap. These occurrences required increased trap inspection frequencies and were most common during the stormy winter season and during increases in discharges from Camanche Dam. Discarded and tangled monofilament fishing line was also a periodic problem especially during episodes of illegal fishing in the vicinity of the dam and traps during the spring and summer months.

²"Finquel" formulation, sold by Argent Chemical Laboratories, Redmond, WA.

Fishing line wrapped around the main shaft of the rotating cone and the central axle of the livebox drum screen resulted in wear and tear on moving parts and nylon bushing components.

Algal growth on the perforated rotating cone of the traps was removed by brushing all surfaces when growth occurred, which could be as often as twice daily. This algal growth occurred predominately during the late spring and summer months.

Trap Calibrations for Abundance Estimates

Fish capture efficiency of the rotary screw trap system was measured at nine intervals during the monitoring season. All juvenile salmon used for these mark-recapture tests were obtained from MRFI and were of Mokelumne River or American River origin. Fish were anesthetized (ca. 70 to 100 milligrams/liter tricaine methane sulfonate solution) and marked by excision of either the right or left pelvic fin or by excision of a small, but distinct, portion of the upper or lower lobe of the caudal fin. These fish were allowed to recover in cylindrical 25-liter PVC live cars (30 cm diameter, 40 cm long with soft nylon 2 mm Delta mesh covered ends) placed in a protected refuge in the low-stage fishway for 8 to 24 hours prior to their release for the tests. A sample of fifty fish from each release group was measured for FL and examined for mark quality prior to release.

Paired test releases, one during daylight and one during night time, were made on each test date. Fish releases were made approximately 20 m to 30 m upstream from the traps where most of the dam discharges confluenced, which primarily consisted of spill from spill bays #2-#5 and the fishway discharge. The release groups were divided into two or three groups of approximately equal sublots and released across the width of the dam's discharge. Fish were released from 20-liter buckets by gently dipping the lip of the bucket underwater and lifting the bottom in one motion. We assumed that the release distance from the trap and the flow configuration of the dam's discharge issuing toward the traps allowed fish to seek a preferred portion, or natural migration route, in the discharge flow or to mix to a homogeneous distribution within the discharge flow prior to encountering the traps.

Live box retention efficiency of the traps, primarily for larger sized smolts, was measured several times during the monitoring period from May 21 to June 4, 1994. Fish marked by excising a pelvic fin or fish that were coded-wire tagged (CWT) and received an adipose fin clip were used for these evaluations. Numbers of marked fish used for these evaluations ranged from 20 to 122. Use of the combinations of fin-clip marks was coordinated with all other mark-recapture experiments (e.g., trap efficiency releases) to avoid conflicting purposes between tests. Fish were placed in the live boxes of the traps after 2 to 24 hours recovery from the fin removal procedure. Fish were left in the live box until the following trap check (a range of about 6-16 hours) when they were counted, measured for FL and TL, and released downstream from the trap.

Live box fish retention was examined after the unusually low recoveries of test release fish on

May 18-19 test. On two successive nights, May 21 and May 22, retention of marked fish placed in the live boxes were 51 of 107 and 65 of 88, respectively. One day test resulted in 122 of 123 fish retained in live box over a six-hour period. Several potential escape routes were eliminated between rear drum screen and seals; however, subsequent retention tests revealed that fish were still escaping in small numbers from the live box both during day and night. The only possible escape route was for fish to swim back upstream through the rotating auger cone of the screw traps. Rotation of the traps was generally between 2 and 3.5 revolutions per minute during the period of concern. This was apparently not sufficient to prevent larger, strong-swimming smolts from swimming against the current back out of the live boxes, through the auger cone, and away from the trap. We believe this behavior occurred for both wild trapped fish as well as for marked fish used in trap calibration tests during the period from about May 15 through June 20, 1994. So, trap calibration results should still be representative of overall trap and live box retention efficiencies during this period. However, to ensure sufficient recoveries for improved abundance estimation and sampling for size distributions, we recommend that the trap be located and operated where at least 4 rpm may be maintained.

Abundance and Timing of Emigration

The numbers of each species and each age class of salmonids captured were compiled on a daily basis. The age 1+ size criteria for chinook salmon were based on previous years' juvenile salmonid monitoring results and substantiated by the sizes of adipose-fin-clipped salmon released at age 1+ during the fall of 1993 and captured during each of the following time periods:

Time Period	Age 1+ Size Criterion
January 1 through February 28, 1994	> 75 mm TL
March 1 through May 31, 1994	>125 mm TL
June 1 through July 31, 1994	>150 mm TL

Morning and afternoon trap capture numbers were combined to provide daily totals for each trap site. Daily counts were compiled into weekly totals for several analyses.

Outmigrant abundance estimates were generated from trapping efficiency results. Trap efficiency recovery rates for each test date were computed for the day and night releases (Table 1). Based on chi-square analyses, distinctly different results were obtained for the day and night releases, except for the May 18-19 test. And, except for two periods represented by tests conducted on March 10 and March 16, night-time release recoveries were significantly higher than those conducted during daylight.

The average trapping efficiency for each test date was applied to each respective period for which it was representative in terms of river flow, fish size, numbers of traps in service, and observed incidence of predators as follows:

TIME M AVG FL (mm) R(24th) R(24th) AVG FL (mm) R(24th) AVG FL (mm) R(24th) R(35th)		RELEASE GROUP INFO. RECAPTURE GROUP INFO.	RELEASE GROUP INFO	ON INFO			RECAPTURE GROUP INFO	GROUP	NFO.				OIM	NOAT-CORC &
935 363 50 (s=8) 65 54 0.179 28 9*** 83 55.0 150 150 1926 388 60 (s=8) 108 53 0.278 25.1*** 75 55.0 146 1920 347 43 (s=3) 156 42 0.043 75 56.6 112 1920 347 41 (s=3) 22 47 0.083 13.3* 160 60.4 59 1934 300 47 (s=3) 22 47 0.083 13.3* 160 60.4 59 1934 300 47 (s=4) 18 46 0.027 138 60.4 59 114 2026 366 44 (s=4) 108 48 0.236 143 60.4 59 114 60.4 59 114 60.4 50 114 105 114 114 114 114 114 114 114 114 114 114 114 114 </th <th>DATE</th> <th>TIME</th> <th>Σ</th> <th>AVG FL (</th> <th></th> <th>R(24h)</th> <th>AVG FL (mm)</th> <th></th> <th>Chi-Sq.(day-night)</th> <th></th> <th></th> <th>_</th> <th></th> <th>TRAPS FISHING</th>	DATE	TIME	Σ	AVG FL (R(24h)	AVG FL (mm)		Chi-Sq.(day-night)			_		TRAPS FISHING
1925 388 60 (s=8) 108 63 0.278 95 55.0 146 970 398 43 (s=3) 56 42 0.141 25.1** 75 58.6 112 1920 347 47 (s=3) 56 42 0.141 25.1** 75 58.6 106 910 251 47 (s=3) 22 47 0.043 133* 186 58.6 106 1934 300 47 (s=4) 57 46 0.027 138 64.0 114 2026 350 44 (s=4) 57 46 0.027 138 64.0 114 2026 366 44 (s=4) 57 48 0.226 158 64.0 114 2010 366 82 (s=7) 22 49 0.063 245.7*** 140 63.6 95 2040 358 82 (s=7) 25 80 0.071 99.2*** 143 64.0 162	2/23/94	935	363	=8) 09	8)	65	54	0.179	28.9**	83	55.0	ν-		2
920 398 43 (s=3) 56 42 0.141 25.1** 75 58.6 112 1920 347 43 (s=3) 16 42 0.043 35 58.6 106 1920 347 43 (s=3) 15 48 0.043 133* 195 58.6 106 1934 30 47 (s=3) 22 47 0.038 133* 64.0 104 99 2025 350 44 (s=4) 57 46 0.163 39.2** 178 64.0 114 2026 356 44 (s=4) 108 48 0.236 39.2** 178 64.0 114 2026 356 347 50 (s=7) 22 49 0.063 245.7** 140 63.6 95 1162 2040 358 82 (s=7) 37 83 0.271 39.2** 143 64.0 102 2040 358 82 (s=6) 18 0.071	02/23/94	1925	389	50 (s=	8)	108	63	0.278		98	65.0	146	0	2
1920 347 43 (s=3) 15 48 0.043 93 58.6 106 1910 251 47 (s=3) 22 47 0.036 13.3* 196 58.5 99 1934 300 47 (s=3) 22 47 0.035 13.3* 196 58.5 99 850 350 44 (s=4) 57 46 0.027 178 60.4 99 2026 366 44 (s=4) 108 48 0.236 178 63.5 114 2010 336 60 (s=7) 22 49 0.063 245.7*** 140 63.6 95 2010 336 82 (s=7) 25 80 0.063 245.7*** 143 64.8 162 2040 356 82 (s=6) 18 89 0.071 99.2*** 148 64.8 154 2050 252 95 (s=6) 18 0.071 90.2*** 160 62.2 153 </td <td>03/10/94</td> <td>920</td> <td>398</td> <td>43 (s=</td> <td>3)</td> <td>26</td> <td>42</td> <td>0.141</td> <td>25.1**</td> <td>75</td> <td>58.6</td> <td>112</td> <td>0</td> <td></td>	03/10/94	920	398	43 (s=	3)	26	42	0.141	25.1**	75	58.6	112	0	
910 251 47 (s=3) 22 47 0.088 13.3° 196 58.5 99 1934 300 47 (s=3) 22 47 0.027 39.2°° 196 60.4 99 850 300 47 (s=4) 57 46 0.027 39.2°° 160 60.4 59 2026 366 44 (s=4) 108 48 0.236 178 64.0 114 2010 336 80 (s=7) 22 49 0.063 245.7°° 140 63.6 96 2010 336 82 (s=7) 25 80 0.063 245.7°° 118 64.0 102 2040 356 82 (s=7) 37 83 0.071 99.2°° 143 64.8 162 2040 256 95 (s=6) 18 89 0.071 99.2°° 148 64.8 154 200 256 86 (s=6) 56 93 0.074 2.92 (NS	03/10/94	1920	347	43 (5=	3)	15	48	0.043		93	58.6	106	0	
1834 300 47 (s=3) 8 46 0.027 160 60.4 99 850 350 44 (s=4) 57 46 0.163 39.2** 138 64.0 114 2026 366 44 (s=4) 108 48 0.296 178 63.5 115 2026 386 44 (s=4) 108 48 0.236 178 63.5 115 2040 386 60 (s=7) 22 49 0.083 245.7*** 140 62.9 162 941 396 82 (s=7) 25 80 0.083 245.7*** 118 62.9 162 2040 358 82 (s=7) 97 83 0.271 99.2*** 148 62.9 162 2040 255 96 (s=6) 18 0.071 99.2*** 148 64.8 154 210 250 96 (s=6) 1 62 0.004 2.92 (NS) 148 59.9 <td< td=""><td>03/16/94</td><td>910</td><td>251</td><td>47 (s=</td><td>3)</td><td>22</td><td>47</td><td>0.088</td><td>13.3*</td><td>195</td><td>58.5</td><td>66</td><td>0</td><td></td></td<>	03/16/94	910	251	47 (s=	3)	22	47	0.088	13.3*	195	58.5	66	0	
850 350 44 (s=4) 57 46 0.163 39.2*** 138 64.0 114 2025 3.66 44 (s=4) 108 48 0.265 178 64.0 115 2010 3.36 50 (s=7) 72 49 0.063 158.8*** 140 63.6 95 2010 3.36 82 (s=7) 25 80 0.033 245.7*** 143 62.9 162 2040 3.56 82 (s=7) 97 83 0.271 99.2*** 148 62.9 162 2040 2.56 95 (s=6) 16 89 0.071 99.2*** 148 64.8 154 2200 2.39 96 (s=6) 16 89 0.071 99.2*** 148 64.8 162 2130 2.95 81 (s=6) 6 89 0.074 2.92 (NS) 148 59.9 162 2100 2.55 81 (s=6) 6 80 0.024	03/16/94	1934	300	47 (5=	3)	80	46	0.027	THOUSE THE	160	60.4	8	0	
2025 366 44 (s=4) 108 48 0.295 178 63.5 115 2010 336 50 (s=7) 22 49 0.063 158.8*** 140 63.6 95 2010 336 80 (s=7) 25 80 0.036 143 64.0 102 941 396 82 (s=7) 25 80 0.071 99.2*** 143 64.0 102 2040 358 82 (s=7) 25 80 0.071 99.2*** 148 64.8 154 2200 252 95 (s=6) 18 89 0.071 99.2*** 148 64.8 153 2130 273 75 (s=6) 1 62 90 0.074 2.92 (NS) 148 59.9 162 2130 255 81 (s=6) 6 80 0.024 2.92 (NS) 148 59.9 162 2200 255 81 (s=6) 6 80 0.024	03/25/94	850	350	44 (5=	4	22	46	0.163	39.2**	138	64.0	114	0	
8.55 347 50 (s=7) 22 49 0.063 158.8*** 140 63.6 95 2010 336 60 (s=7) 79 61 0.236 143 64.0 102 2040 356 82 (s=7) 25 80 0.063 245.7*** 118 62.9 162 2040 356 82 (s=7) 87 83 0.071 99.2*** 148 64.8 154 2200 239 96 (s=6) 56 83 0.071 99.2*** 148 64.8 154 2130 273 75 (s=8) 1 62 0.074 2.92 (NS) 148 59.9 162 2130 255 81 (s=6) 6 80 0.010 2.92 (NS) 148 59.9 162 2200 255 81 (s=6) 6 80 0.024 391.3*** 150 66.9 121 2200 230 81 (s=6) 62 79 0.226	03/25/94	2025	366	44 (5=	4)	108	48	0.295	Commonweal Common Commo	178	63.5	115	30	
2010 335 60 (s=7) 79 61 0.236 143 64.0 102 2040 396 82 (s=7) 25 80 0.063 245.7*** 118 62.9 162 2040 396 (s=6) 87 83 0.071 99.2*** 135 62.9 162 975 252 95 (s=6) 18 89 0.071 99.2*** 148 64.8 154 915 273 75 (s=8) 1 62 93 0.074 2.92 (NS) 148 62.2 153 2130 250 75 (s=8) 1 62 0.004 2.92 (NS) 148 59.9 162 940 250 75 (s=8) 5 79 0.010 2.91 (NS) 148 59.9 162 940 250 81 (s=6) 6 80 0.010 2.91 (NS) 162 66.9 121 2200 230 81 (s=6) 62 79 0.024	04/01/94	855	347	=8) 09	7	22	49	0.063	158.8***	140	63.6	95	42	
941 396 82 (s=7) 25 80 0.063 245.7*** 118 62.9 162 2040 358 82 (s=7) 97 83 0.271 395.** 135 63.3 160 2200 235 95 (s=6) 18 89 0.071 99.2** 148 64.8 154 2200 239 256 80 0.004 2.92 (NS) 148 59.9 162 2130 256 81 (s=6) 6 80 0.024 391.3*** 150 65.9 121 2200 230 81 (s=6) 62 79 0.024 391.3*** 150 66.9 121	04/01/94	2010	335	=E) 09	- 6	79	51	0.236		143	64.0	102	25	
2040 358 82 (s=7) 97 83 0.271 135 63.3 160 925 252 95 (s=6) 18 89 0.071 99.2*** 148 64.8 154 2200 239 96 (s=6) 16 83 0.234 2.92 (NS) 148 62.2 153 2130 230 75 (s=8) 1 62 0.004 2.92 (NS) 148 59.9 162 940 256 81 (s=6) 6 80 0.024 391.3*** 150 66.9 121 2200 230 81 (s=6) 62 79 0.226 150 66.9 121	4/20/94	941	396	82 (s=	2	25	80	0.063	245.7***	118	62.9	162	000	
925 252 95 (s=6) 18 89 0.071 992*** 148 64.8 154 2200 239 96 (s=6) 93 0.234 29.7 150 62.2 153 2130 273 75 (s=8) 1 62 0.004 2.92 (NS) 148 59.9 162 2130 250 81 (s=6) 6 80 0.024 391.3*** 150 66.9 121 2200 230 81 (s=6) 62 79 0.226 150 66.9 121	04/20/94	2040	358	82 (s=	2	97	æ	0.271		135	63.3	160	06	
2200 239 96 (s=6) 66 93 0.234 150 62.2 153 916 273 75 (s=8) 1 62 0.004 2.92 (NS) 148 59.9 162 2130 259 75 (s=8) 3 79 0.010 148 59.9 162 940 256 81 (s=6) 6 80 0.010 391.3*** 150 66.9 121 2200 230 81 (s=6) 62 79 0.226 150 66.9 121	05/04/94	925	252	95 (s=	(9	18	88	0.071	99.2***	148	64.8	154	106	
915 273 75 (s=8) 1 62 0.004 2.92 (NS) 148 59.9 162 162 2130 290 76 (s=8) 3 79 0.010 148 59.9 162 162 940 255 81 (s=6) 6 80 0.024 391.3*** 150 66.9 121 2200 230 81 (s=6) 62 79 0.226 150 66.9 126	05/04/94	2200	239	95 (s=	(9	99	93	0.234	4444	150	62.2	53	135	
2130 290 75 (s=8) 3 79 0.010 148 59.9 162 121 2200 230 81 (s=6) 6 79 0.226 391.3*** 150 66.9 121 126	05/19/94	915	273	75 (s=	8)	-	62	0.004	2.92 (NS)	148	59.9	162	86	
1 940 255 81 (s=6) 6 80 0.024 391.3*** 150 66.9 121 1 2200 230 81 (s=6) 62 79 0.226 150 66.9 126	5/18/94	2130	290	75 (s=	(8)	63	79	0.010	200000000000000000000000000000000000000	148	59.9	162	94	
1 2200 230 81(s=6) 62 79 0.226 150 66.9 126	05/29/94	940	255	81 (s=	(9)	9	80	0.024	391.3***	150	66.99	121	106	
	05/29/94	2200	230	81 (5=	6)	52	79	0.226		150	6.99	126	106	

Applicable Period	Test Date Applied	River Flow (cfs)	Trap Type (#)
1/15/94 - 3/08/94	2/23/94	114-174	Rotary Screw (2)
3/09/94 - 3/13/94	3/10/94	106-112	Rotary Screw (2)
3/14/94 - 3/23/94	3/16/94	91-108	Rotary Screw (1)
3/24/94 - 3/30/94	3/25/94	103-116	Rotary Screw (1)
3/31/94 - 4/18/94	4/01/94	95-129	Rotary Screw (1)
4/19/94 - 4/27/94	4/20/94	155-202	Rotary Screw (1)
4/28/94 - 5/16/94	5/04/94	146-180	Rotary Screw (1)
5/17/94 - 5/25/94	5/19/94	134-177	Rotary Screw (1)
5/26/94 - 6/20/94	5/29/94	71-155	Rotary Screw (1)
6/21/94 - 7/31/94	100% of downstre	am migrants recovere	d in fishway traps.

Daily diurnal and nocturnal trap capture numbers were divided by the appropriate day or night trap efficiency rate applicable to the period in which it occurred to calculate an estimated abundance index. Diurnal and nocturnal abundance estimates for individual days were summed to produce daily abundance estimates. The individual daily abundance estimates were summed to produce abundance estimates for various time periods. The estimates of abundance based on these trap efficiency results should be considered as an index of relative temporal abundance at the release location for trap calibration fish (versus recapture location) and not as a population estimate. It is important to recognize that these estimates do not quantify potential fish losses between the release and recapture locations. For example, if there were no fish loss (as compared to some unquantified loss) between the release and recapture locations, the abundance indices would be the same in either case because the indices are reflective of the release location, not the recapture location. Actual fish losses between the release and recapture locations (e.g., attributable to predation) are unknown and cannot be quantified with these indices.

Fish Size and Condition

The size parameters of FL, TL, and weight measured on subsamples of young-of-year (Y-O-Y) and yearling salmon catches for samples of up to 60 fish per trap each day were compiled on a daily basis. Fulton's Condition Factor, given as (100 x weight/TL³) by Bagenal and Tesch (1978), where weight is in grams and TL is in mm, were computed for each fish for which TL and weight measurements were obtained. Daily and weekly averages for FL, TL, weight, and condition factor of Y-O-Y and yearling salmon were computed and compiled for analysis.

Observations of injuries on trapped fish were described, recorded, and compiled on a daily basis, as well as the numbers of dead fish found in the traps during each day. These incidents of injury and mortality were examined with regard to effects of predators, debris fouling of the traps, and other conditions which may have contributed to their occurrence.

Physical Environmental Data

Daily environmental data for January - July 1994 were obtained from the following sources:

- River Flow passing Woodbridge Dam: U.S. Geological Survey (USGS) gauging station (#11325500) located on the Mokelumne River downstream of Woodbridge Dam near River Mile 37.
- WID's Canal Diversions: USGS gauging station (#11325000) located in the canal near the point of diversion at Woodbridge, California.
- Local Watershed Precipitation: National Weather Service field data collection station at Camanche Dam, San Joaquin County, California.
- River Temperature at Woodbridge Dam: Ryan Model RTM 2000 thermograph³ installed in pool #6a (and pool #5a after June 20, 1994) of the low-stage fishway and surface temperatures generally measured twice daily during morning and afternoon with a mercury-filled thermometer.
- Water Turbidity Index (Secchi Depth): Generally measured twice daily in the river channel off downstream end of screw traps, or in Lake Lodi immediately upstream from spill bay #1 at Woodbridge Dam.
- Lunar Age and Regional Sunrise/Sunset Timing: 1994 Old Farmer's Almanac, Yankee Publishing Inc., Dublin, New Hampshire.
- Sacramento-San Joaquin Delta Water Conditions: U.S. Bureau of Reclamation, Central Valley Operations Coordinating Office, Sacramento, California and California Department of Water Resources, Sacramento, California.

Diel Migration Pattern Surveys

Diel patterns of the migration behavior of chinook salmon smolts were assessed on two dates during the height of the emigration period. These diel surveys were conducted at the Woodbridge Dam trap site on May 11-12 and May 24-25, 1994. On these dates, traps were tended hourly for a full 24-hour cycle using the same previously described fish handling and trap tending protocols, except that the trap was tended by boating over to its fishing position in the channel rather than pulling it to shore. This trap tending procedure allowed the trap to operate continuously during the entire diel survey period. Numbers of juvenile salmon captured during each of the three diel surveys were compiled on an hourly basis over the course of the 24 hours of survey for each date. Trap efficiencies for applicable diurnal and nocturnal time periods were applied to hourly trap captures to compute and compare hourly estimated abundance of downstream migrant fall chinook salmon smolts during these two survey periods.

³Ryan Instruments Inc., Redmond, Washington

Physical Injury Tests at Woodbridge Dam

Tests were conducted at Woodbridge Dam to assess the potential for fish mortality attributable to young chinook salmon passing over the top of Woodbridge Dam and into the dam spill bays. Experimental groups of approximately 500 juvenile chinook salmon (obtained from MRFI) were released directly into spill bays on top of Woodbridge Dam. Immediately prior to release, these fish were transferred from an oxygenated holding tank positioned adjacent to the left abutment of the dam into five 5-gallon buckets for each release group, hand carried to the release location, then poured into a 12-inch diameter PVC pipe (7 feet long) with its end positioned directly over the lip of the spill passing over the Woodbridge Dam flashboards. Positioning of the end of the PVC pipe was critical to ensure released fish did not escape upstream into Lake Lodi but instead passed over the spill on the dam and into the spill bays.

Experimental fish were recaptured downstream of the dam by positioning the rotary fish trap (previously described) into the flow emanated from spill bays where experimental fish were released. After approximately 15 minutes following the experimental fish release, all salmon captured within the rotary trap were removed. It was assumed that the capture of any wild fish during the 15-minute sampling period was minimal and would not significantly influence study results. Recaptured experimental fish were transferred to shore in a live car (12-inch diameter, 16-inch long PVC pipe with both ends covered with 1/8-inch knotless, nylon Delta mesh). All fish remained in water continuously following removal from the rotary trap. Each live car was placed in a protected area of the fishway (pool #5a) where fish were monitored daily for mortalities over a seven-day period.

For each experimental group of fish released into a spill bay, a control group of approximately 60 or 100 fish was released into the rotary trap for comparative purposes. After each experimental group of fish was released, recaptured, and placed into the fishway, a control group of fish was removed from the oxygenated holding tank positioned adjacent to the left abutment of the dam and placed into a 5-gallon bucket. These fish were then transferred out to the rotary trap where they were released directly into the rotary trap entrance. The estimated time the fish remained in the transfer bucket was approximately the same as for the comparable experimental fish group. The control group of fish remained in the rotary trap for approximately 15 minutes and were removed and transferred in a live car to the fishway as previously described for experimental groups of fish.

All attempts were made to treat experimental and control groups of fish the same, except for the experimental fish group's passage over the spill bays prior to recapture in the rotary trap. The numbers of fish within each group were purposefully not individually enumerated prior to release to minimize handling stress and potential physical injury attributable to handling. The numbers within each group were estimated by weighing in buckets of water to attempt relative similarities in fish densities between experimental and control groups after recapture. The intent was to minimize any differences in mortality that could be attributed to differences in densities of fish held in the same sized live cars during subsequent monitoring after recapture. Fish were

not fed during the seven-day monitoring period, but they had some limited ability to feed on water-borne natural feed because riverine water could freely pass through their live car. Any observed differential mortality between the experimental and control groups over the seven-day monitoring period was assumed to be primarily attributable to factors affecting fish after release into the dam spill and recapture in the rotary trap.

Coded-Wire Tagging of Wild Smolts at Woodbridge Dam Trap Site

Tagging of naturally produced juvenile salmon with coded-wire tags was initiated upon a dramatic increase in the number and size of juvenile salmon (≥75 mm TL) being captured at the Woodbridge Dam traps. Beginning on April 8, 1994 and continuing through the monitoring season until July 31, 1994, all juvenile chinook salmon captured at the Woodbridge Dam site were tagged by injecting 0.5 mm binary coded-wire tags into their head cartilage using a NMT4 Mark IV tagging machine and marked by excision of the adipose fin with Mitex fine surgical scissors. Fish were handled as previously described for fish handling and measurement with the additional procedures of injecting tag wire, passing fish through a quality control device (QCD) to insure tag implantation, and excising adipose fins prior to their placement into a recovery tank of fresh flowing river water. A single tagging machine with QCD provided by EBMUD was set up daily on the grate covering pool #15 of the high-stage fishway. Water was pumped from the fishway to operate the hydraulic controls of the QCD and to provide cool flowing water to a 120-liter plastic tank used as a recovery bath for the fish. A shade fabric (approximately 60% light reduction) was installed over the entire work area to control sun heating of equipment and fish. Upon recovery, fish were placed in 20-liter buckets at densities of no more than about 60 fish per bucket and hauled approximately 100 m downstream from the trap where they were released. Total time in transit was one to three minutes. Alternatively, during June 20 to July 31, 1994, all tagged fish were placed in live cars (previously described) after recovery and held for 1 - 2 days before being transported to the Sacramento River at Rio Vista for release.

Two tag codes assigned to EBMUD were used for tagging naturally produced chinook salmon smolts captured at Woodbridge Dam during 1994:

Tag Code	Time Period	Release Location
6-1-13-1-4	April 8 - June 20, 1994	Mokelumne R. at Woodbridge Dam
6-1-13-1-5	June 21 - July 30, 1994	Sacramento R. at Rio Vista, CA.

The use of two codes allocated to these two periods will allow some inferences to be made regarding the survival and fishery contributions of early and late emigrating naturally produced smolts when analyzing later tag returns. These two time periods also correspond to fish

⁴Northwest Marine Technologies, Shaw Island, Washington.

captured, tagged, and released at Woodbridge Dam (early period) and to fish captured, tagged, transported, and released in the Sacramento River at Rio Vista, California (later period).

The quality of tagging and latent mortality associated with handling during tagging were assessed at two different times for the early period tag code. Samples of 37 and 49 tagged fish were placed in 25-liter PVC live cars (previously described) at densities of about 15 fish per live car and held in a protected area of low-stage fishway (pool #5a) for 5 to 7 days⁵. The live cars were checked daily for mortalities. At the end of the holding period, all fish were mildly sedated with tricaine methane sulfonate (ca. 30 to 50 milligrams per liter), examined for quality of the adipose fin clip, and passed through the QCD to detect tag retention. After this procedure, all fish were released as previously described. During the later tagging period, due to adverse fish holding conditions because of high water temperatures, no tag retention assessments could be performed for the second tag code applied.

During the period of June 21 to July 31, 1994, when water temperatures were elevated in the reach of the Mokelumne River downstream from Woodbridge Dam, all fish captured and codedwire tagged at Woodbridge Dam were transported and released in the Sacramento River at Rio Vista, California (municipal boat launch). Fish were allowed to recover for 24 to 48 hours in live cars placed in a protected area of the low-stage fishway (pool #5a) prior to transport. A pick-up truck-mounted 500-liter, insulated, fiberglass fish hauling tank with bottled oxygen aeration (1.5-3.0 liters/minute) was used to transport fish. River water with approximately 0.7-0.9% salt (NaCl added) was used as the transportation medium to minimize osmotic stress during handling and transport (Carmichael and Tomasso 1988, Long et al. 1977, Wedemeyer 1992). Water temperature was carefully monitored and recorded when loading fish, occasionally during transport, and upon arrival at the release site. Transport time was generally about 1 hour and water temperature generally did not change by more than 1°F during transport. Temperature of the receiving water was measured and recorded prior to release of the fish. If water temperatures between the haul tank and river differed by more than 4°F then tempering of the hauling water was performed prior to release. Tempering consisted of exchanging water in the haul tank with receiving water to gradually acclimatize the fish to the receiving water temperature at a rate of about 2°F per 15 minutes. Fish mortality and any other biologically relevant observations at release were noted and recorded.

Coded-Wire Tagging of Hatchery Smolts and Delta Survival Experiments

As in 1993, CDFG provided a trailer outfitted with coded-wire tagging equipment for our use in tagging chinook salmon smolts reared at the MRFI for mark and recapture experiments of smolt survival in the Sacramento-San Joaquin Delta. The trailer was equipped with six marking stations each with a NMT Mark IV tagging machine, a QCD, and a stainless steel anesthetic bath

⁵Note: CDFG holds tagged hatchery fish for a minimum of 21 days for quality control assessment; however, this was not practicable under field conditions at the Woodbridge Dam site.

pan. A stainless steel trough running along the length of an interior wall of the trailer was supplied with continuously flowing water pumped from a hatchery water supply for loading and holding fish in the trailer prior to being tagged. A PVC return pipe manifold system that ran the length of the trailer's floor passing beneath each station served to collect and carry tagged fish back outside to a receiving raceway. Each station was plumbed to receive water pumped from the hatchery water supply. This plumbing system provided water to operate the QCD's hydraulic sorting switches, which separated correctly tagged from untagged fish, and to carry tagged fish through the return pipe system. The trailer was also equipped with a recirculating anesthetic system consisting of a 120-liter plastic barrel head tank, copper chilling coil, acrator, and submersible pump for pumping anesthetic solution through a PVC distribution manifold to each station. Anesthetic solution returned to the head tank by gravity through a return manifold pipe for reconditioning.

The tagging procedure was as follows. Fish were loaded directly from the hatchery raceway into the trailer's holding trough from which fish tagging technicians netted groups of fish to be tagged. In netted groups of about 50 to 60, the fish were mildly anesthetized in aerated, salted (0.7-0.9%), buffered tricaine methane sulfonate solutions (ca. 70 to 90 milligrams per liter, with 1:1 sodium bicarbonate as buffer). The temperature of the anesthetic solution at each station was monitored regularly by each worker or a supervisor. The anesthetic solution was changed regularly at 2 to 3 hour intervals or more frequently if the time for induction of anesthesia increased to more than about 1.5 to 2 minutes. Once the fish were anesthetized, a 1 mm binary coded-wire tag was injected into the head cartilage of each fish using the tagging machine, the adipose fin was excised with a pair of fine-pointed surgical scissors, and the fish was passed through the QCD. Those fish which the QCD detected as untagged were automatically directed to a recovery bucket and the QCD issued a warning tone to the operator. These fish were passed back through the QCD to double check the rejection and re-tagged if necessary. The efficiency of tagging, proper operation of QCD's, and tag placement for each operator and tagging machine was checked two to three times daily during tagging operations. Samples of 25 to 100 fish were collected from each station's QCD outflow and passed back through another QCD for confirmation of tagging efficiency and QCD operation. A subsample of 3 to 10 of these fish were dissected to confirm proper placement of the tags and the tagging machines were adjusted if necessary. Machine cleaning and major repair or adjustments were conducted at the end of each tagging day.

A total of approximately 207,000 smolts at a size of 90 fish per pound were tagged for the 1994 Delta survival study. These fish were of Mokelumne River origin incubated, hatched, and reared at MRFI. Four tag codes assigned to EBMUD were used during April 11 to April 25, 1994 to tag these fish. The tag codes were allocated to four groups of about 52,000 fish each. The initial experimental design was a fully duplicated release design with two groups paired as replicates in each of two experimental releases. The two replicated experimental releases were scheduled to occur during different Delta water export conditions, one in early May 1994 and one in late May 1994. Because of space and manpower constraints, CDFG was unable to release the fish as planned; each of the paired replicate coded-wire tag groups were loaded and

transported together to the release site by CDFG. This violated the original experimental design requirement for independent replication groups and resulted in a pseudo-replicated release consisting of two sublots for each experimental release (see Hurlbert 1984 for a discussion of pseudo-replication). The resulting coded-wire tagged release groups were as follows:

Experimental Group

Tag Codes

Early Season Release

6-48-03 & 6-48-04 mixed

Late Season Release

6-48-01 & 6-48-02 mixed

The main impact to the original experimental design of the mixed sublot release was the limitation of the resulting release design's capability to generate a statistical estimate of sampling variance for refined survival estimates.

During the pre-release holding period, CDFG maintained records of all mortalities in each of the tag code groups. Each of the tag groups were checked for tag retention 18 to 31 days after being tagged. Samples of about 300 to 500 fish for each of the tag groups were mildly sedated in a 50 milligrams per liter solution of tricaine methane sulfonate and singly passed through a QCD set up alongside the raceway. Then following the procedure outlined by CDFG, the proportion of fish detected without tags for each sample was used to adjust for total numbers of fish retaining tags after subtracting mortalities from the number originally tagged (F. Fisher, CDFG, Red Bluff, CA, personal communication). Two days prior to release of each of the composite groups, a sample of 40 to 80 fish were measured for FL and TL and weighed and their condition factors were calculated.

CDFG transported and released each of the composite tagged groups of fish, 6-48-03/04 on May 10, 1994 and 6-48-01/02 on May 23, 1994. Fish were released at New Hope Landing at the confluence of the Mokelumne River and the central Delta. A sample of 70 to 90 tagged fish were netted from the transport tank after transport to the release site, placed in a 25 liter live car, and subsequently held at the release site for 24 hours to assess post-transport stocking mortality. Live cars were attached to a boat dock adjacent to the release site at a depth of about 0.75 m to 1 m of water. Fish mortalities among those held were recorded after 24 hours and the surviving fish were then released. Subsequent recapture of the marked experimental release groups was conducted through June 1994 by the U.S. Fish and Wildlife Service's (USFWS) Sacramento-San Joaquin Estuary Fishery Resource Office using a standardized, routine trawl sampling program at the western outflow of the Delta near Chipps Island (P.L. Brandes, USFWS, Stockton, CA, pers. comm.). USFWS processed recaptured fish and identified coded-wire tag samples.

Coded-Wire Tag Summaries and Assessment

Coded-wire tagging data for both wild and hatchery reared groups were compiled to indicate initial numbers of fish tagged, tag retention, post-tagging mortality, size of fish at time of

release, and dates of release and release objectives. These data were previously submitted to CDFG in their reporting format during July and August 1994. Tagging data for both wild and hatchery release groups are also presented in this report. Tag recovery data for the Delta survival experimental releases were compiled by USFWS. USFWS provided preliminary computed survival indices (S_T) for each of the tag codes recovered during their surveys.

Passive Integrated Transponder (PIT) Tags: Assessment of Individual Fish Migration

Implantation of PIT tags in juvenile salmon for investigations of individual fish migration behavior was conducted at a marking station at the hatchery. Because of the surgical nature of this procedure, fish were tagged at the hatchery where water temperature was cooler than at Woodbridge Dam and transport stresses could be avoided prior to tagging. The procedure of Prentice et al. (1990) was followed for PIT tag implantation. A spring-loaded injector with a 12-gauge veterinary vaccinating needle loaded with a PIT tag, both disinfected with a 0.5% povidone-iodine solution (Veterinary grade Betadine solution) for at least 3 minutes and rinsed with sterile physiological saline (0.9% NaCl), was used to implant the tag in the peritoneal cavity of the fish. Fish were anesthetized before PIT implantation in groups of 25 to 30 in aerated solutions containing 100 mg/liter 2,2,2 tricaine methanesulfonate buffered with an equal weight of sodium bicarbonate, 2 ml of PolyAqua6, and about 5 to 7 g/liter NaCl. Water temperature of the anesthetic solution was monitored during PIT implant sessions and maintained within 2°F. Upon sedation, fish were placed with their ventral surface facing up in a foam tagging cradle which supported the entire body of the fish and was saturated with a recovery solution containing PolyAqua and 0.5 to 0.9% NaCl. The injector needle tip was gently inserted posteriorly into the abdomen of the salmon at a point just posterior to the pectoral girdle to create an incision. The PIT tag was pushed from the barrel of the injector needle through the incision simultaneously as the needle was retracted from the incision leaving the PIT tag in the peritoneal cavity (Figure 4). The PIT identifier code number, read with an AVID multi-tag reader, along with a tagging quality code ranging from 1 for good to 5 for poor were recorded for each fish tagged. Fish were immediately placed in a 20-liter recovery bucket containing an aerated solution of 3 ml PolyAqua and about 5 to 7 g/liter NaCl. Upon regaining equilibrium and stable ventilation, fish were placed in a raceway at MRFI and held there for more than one week prior to release to ensure full recovery from the surgical procedure. Test fish were transported in an aerated tank and released at a variety of locations in Lake Lodi (Figure 5). Upon recapture in the fish traps at Woodbridge Dam, the PIT tag codes were recorded with the AVID reader.

Radio-Telemetry: Assessment of Yearling Steelhead Migration Behavior

To complement the PIT tagging assessment of individual fish migration, radio-telemetry was employed utilizing juvenile steelhead. All steelhead used for this assessment were age 1+ fish

⁶Kordon/Novalek, Hayward, CA




Figure 4. Illustrated implantation of a PIT tag in an anesthetized juvenile chinook salmon, showing point of insertion through the body wall musculature (cutaway view), needle injection angle to implantation site, and position of the implanted PIT tag within body cavity. (Adapted from Prentice et al. 1990)




Figure 5. Topographical view of the Mokelumne River and Lake Lodi depicting release sites of PIT- and radio-tagged chinook salmon, and locations of Hydrolab sampling sites.

obtained from MRFI. A 1.8 g "smolt-sized" radio transmitter tag⁷ was used for either external attachment or internal implantations.

External attachment utilized a tag harness constructed of a small plastic plate (2 cm x 0.4 cm) with a piece of 2/0 surgical stainless steel suture wire bent in a U-shape with the ends of the wire passed through small holes in either end of the plastic plate. The plastic plate and suture wire assembly was firmly attached to the transmitter so that the ends of the wire protruded about 10 cm perpendicularly from the harness and tag. Heat-shrink tubing cut to fit the length of the plate and transmitter and cyanoacrylate adhesive were used to secure harness assembly to the transmitter. A second plastic plate identical in dimensions and in location of the holes to that previously described was used as a back plate to externally secure the transmitter harness assembly to the fish. Internal implantation required no modification of the transmitter tag.

Because of the surgical nature of the radio tagging procedure, fish were tagged at the hatchery where water temperature was cooler than at Woodbridge Dam and transport stresses could be avoided prior to tagging. Fish were anesthetized individually in aerated solutions containing 100 mg/liter 2,2,2 tricaine methanesulfonate buffered with an equal weight of sodium bicarbonate, 2 ml of PolyAqua, and about 7 g/liter NaCl. Water temperature of the anesthetic solution was monitored and maintained within 2°F.

For external attachment of the transmitter, upon sedation fish were placed dorsum up in a foam tagging cradle which supported the entire body of the fish and was saturated with a recovery solution containing river water, PolyAqua, and 0.9% NaCl. All surgical equipment and the tagharness suture wire were disinfected with a Betadine solution and rinsed with physiological saline before radio-tagging each fish. Two 18-gauge hypodermic needles (spaced 1.7 cm apart) were pushed through the dorsal musculature approximately 1.5 cm ventral to the dorsal fin. The ends of the suture wire protruding from the tag-harness assembly were threaded through the hypodermic needles and the needles were then withdrawn leaving the suture wire-harnesstransmitter assembly in place (antenna pointing toward the posterior of the fish). A neoprene pad, followed by the plastic back plate, were threaded on the ends of the wires, snugged gently against the body of the fish, and the ends of the wires were twisted (8-10x) to secure and complete the external attachment of the transmitter to the fish. The fish's buccal cavity (mouth and gills) was irrigated with the anaesthetic solution at 10 to 15 second intervals with a common meat basting bulb throughout the attachment procedure. After tagging, the fish was placed in a 20 liter recovery bucket containing an aerated solution of river water, 3 ml PolyAqua and about 5 to 7 g/liter NaCl. The entire tagging procedure from removal of the fish from the anesthetic solution to placing the fish in the recovery solution took from 30 to 60 seconds.

For internal implantation, the same fish handling procedure was followed except that fish were placed ventral surface up in the tagging cradle and a small 0.5 to 0.8 cm incision was made 2

⁷Advanced Telemetry Systems, Inc., Isanti, MN

mm lateral to the mid-ventral line just anterior to the pelvic girdle. The unharnessed transmitter was disinfected with Betadine and rinsed with physiological saline prior to inserting it gently through the incision into the peritoneal cavity of the fish. The antenna was left protruding from the incision. The incision was immediately closed with 3 or 4 cuticular monofilament nylon sutures (5/0 Ethilon). After closure, the incision area was rinsed with physiological saline and the fish was placed in a recovery bucket as previously described. The fish's buccal cavity was irrigated with anaesthetic solution as previously described during the surgery. The internal implantation procedure took between 1.5 to 2 minutes.

Fish were transported to Woodbridge Dam 1 to 2 hours after recovery in a 125 liter insulated plastic fish hauling box⁸ with bottled oxygen aeration (1-2 liters/minute). River water obtained at the hatchery with approximately 0.7-0.9% salt (NaCl added), 15ml PolyAqua, and ice to control temperature was used as the transportation medium to minimize osmotic and handling stress during transport. Upon arrival at the dam fish were acclimatized to the river water temperature by tempering at a rate of 2°F per 15 minutes. Fish were placed in pairs in 25 liter cylindrical PVC live cars and held overnight in the refuge area located in low-stage fishway pool #5a. After overnight acclimation to the water quality at Woodbridge Dam, fish were transported in the 125 liter fish hauling box (as previously described) and released at various locations within Lake Lodi (Figure 5).

Radio-tagged juvenile steelhead movements were monitored using mobile reconnaissance and a fixed-station located at Woodbridge Dam. Both techniques utilized Advanced Telemetry Systems, Inc. scan receivers (model ATS R2100). Mobile reconnaissance was conducted from a boat and from shore using a directional loop antenna to locate radio tagged fish. Radio reconnaissance surveys were conducted one to four times daily when radio tagged fish were at large after release. Each time a radio tagged fish was located during a reconnaissance survey, radio frequency identification number, location, time, and any relevant biological and behavioral observations were recorded on aerial photographic representations of the Lake Lodi reach of the river.

Fixed station monitoring was conducted using a scan receiver connected to an ATS DCC II datalogger (Advanced Telemetry Systems, Inc.). The receiver-datalogger system scanned radio tag frequencies programmed into the datalogger and recorded their reception/occurrence when tagged fish entered a specified and limited area within about 100 m upstream of Woodbridge Dam. To control the size of the desired radio reception area, a directional Yagi antenna was used in combination with a tuning/test transmitter (located in 2 m of water at the farthest radius of the desired reception region) and the gain/range controls of the scanning receiver.

⁸Coleman Ice Chest, Witchita, KS

Water Quality Monitoring in Lake Lodi and the Mokelumne River

Water quality monitoring occurred at various locations in Lake Lodi and the Mokelumne River (Figure 5) on one day in the afternoon during each week from May 26, to July 25, 1994. Nine monitoring sites were established from river mile 43.25 to river mile 38.5. Each site was located one river mile or less from adjacent sites. Measurements were taken at the same locations each week using a Hydrolab H20 Multiparameter Water Quality Data Transmitter and Surveyor 3 Display Logger. Water quality parameters monitored included: dissolved oxygen, percent saturation, temperature, specific conductance (conductivity), redox, and pH. At each location where sufficient water depth occurred, measurements were taken at the surface and every three feet in depth to the river bottom to obtain water column profile data. Standard methods for calibration, post calibration, maintenance, and data recovery from the instruments were employed as described in the Hydrolab instrument operating manual.

Physiological Monitoring of Smoltification of Fall Chinook Salmon

This task element was conducted at a pilot level of effort to assess the usefulness of gill Na+/K+ ATPase measurements from field-collected naturally produced chinook salmon to characterize an aspect of the smoltification process and for detecting fish responses to environmental conditions. At two-week intervals from March through July 1994, young-of-year fall chinook salmon were collected from rearing habitat between river miles 53 and 70 (Elliott Road Bridge to the Public Day Use Area at MRFI, respectively) and Woodbridge Dam. Collections from both reaches were made within one day of the other to minimize any temporal variations in measured parameters between groups collected in the different river reaches. Fish collected from the rearing habitat were assumed to be primarily in the rearing life stage; while fish collected at Woodbridge Dam were assumed to be actively migrating smolts. Collections in the rearing reach were made by beach seining with a 20 m x 1.5m x 2mm Delta mesh nylon seine. Collections at Woodbridge Dam were sampled from fish captured in the downstream migrant traps deployed there. Six to ten fish were sampled from each location on each collection date. Fish were euthanized individually as processed using a 200 - 250 mg/liter solution of 2,2,2 tricaine methanesulfonate buffered with bicarbonate. Fish were measured for TL, FL, and weighed as previously described. Gill filaments were carefully excised from all individual gill arches and placed in a 2ml vial of a fixative solution of sucrose, EDTA, and imidazole and frozen on dry ice. Samples were kept frozen at -18 to -25°F until shipped to a laboratory for processing10. The samples were homogenized and analyzed using the whole homogenate method for determining Na*/K+ ATPase activity (Johnson et al. 1977). The resulting data were subjected to analysis of variance (Neter and Wasserman 1974) to assess spatial and temporal differences and changes in gill Na*/K+ ATPase profiles among the groups of fish sampled.

⁹Hydrolab Corporation, Austin Texas

¹⁰ Bio Tech Research and Consulting, Inc., Corvallis, OR

RESULTS AND DISCUSSION

Abundance of Downstream Migrant Juvenile Salmonids

Trapping was conducted for a total of 71 days between October 21 and December 31, 1993 (primarily for yearling fall chinook salmon released at MFRI) and for a total of 212 days between January 1 and July 31, 1994 at Woodbridge Dam. Trapping was essentially continuous during the course of the entire season at Woodbridge Dam. Appendices 1 and 2 provide complete daily records of trapping effort and the capture numbers of young-of-year and yearling fall chinook salmon. The overall trapping numbers of juvenile salmonids during the 1993-94 monitoring season are presented in Table 2. As in previous years, juvenile chinook salmon were by far the most abundant species captured throughout the monitored period. The most abundant non-salmonid species were comprised of several introduced centrarchid fishes (sunfish family) and introduced cyprinids (minnow family). Seven adult smelt of the genus *Hypomesus* were captured during January through March. No differentiation of these smelt between wakasagi and Delta smelt could be performed in the field and they were carefully released alive when captured in the rotary traps. The monthly numbers of these species and others captured at the Woodbridge Dam downstream migrant trapping station are shown in Table 3. In general, most of those species captured (e.g., centrarchids, striped bass, shad, splittail) were sub-adults.

	October - De	ecember 1993	
Fall-Run Ch	nook Salmon	Steell	head
YOY	1+	YOY	1+
0	5628	0	20
	January -	July 1994	
Fall-Run Ch	nook Salmon	Steell	head
YOY	1+	YOY	1+
9014	1229	34	84

Species Oct Nov Dec Jan Pacific Lamprey 1 0 1 0 (Lampetra tridentata) 0 10 1 0 Sacramento Sucker (Catostomus occidentalis) 1 0 1 0 Bluegill (Catostomus occidentalis) 27 702 275 89 Largemouth Bass (Micropterus salmoides) 1 20 14 5 Smallmouth Bass (Micropterus dolomieut) 5 6 0 0 Skriped Bass 0 0 0 0 0 0	0 02 0		Feb 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Mar 12 1 34	Apr 2	May 0	June	July
1 0 1 0 10 1 27 702 275 1 20 14 5 6 0	0 02		e - =	1 1 34		0		20
5) 0 10 1 27 702 275 1 20 14 5 6 0 0 0 0	0 02		_ =	34			-	0
27 702 275 1 20 14 5 6 0 0 0 0	0 02		=	34	-	9	7	6
1 20 14 5 6 0 0 0 0					591	623	47	59
0 0 0 0		0 0	-	0	en:	627	548	0
0 0 0		0		0	-	0	0	0
			0	0	0	0	-	0
Spotted Bass 0 0 0 0 0 0 0 0 0	- 5	0	0	0	0	0	730	0
Redear Sunfish 1 7 10 12 (Lepomis microlophus) 10 12 10 12		12	1	3	15	6	5	0
Green Sunfish 0 0 1 0 0 1 0 0 Lepomis cyanellus)		0	-	3	7	0	0	0
Unidentifiable Centrarchid Species (e.g., hybrids, too small 0 40 0 10. in field)		0	0	4	_	0	66	2422
Prickly Sculpin 0 13 0 29 (Cottus asper)		29	173	06	28	19	12	36
White Crappie (Pomoxis annularis) 40			5	5	19	8	-	0
Black Crappie 0 62 12 1 (Pomoxis nigromaculatus)		-	-	0	-	0	0	0

Species	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	June	July
Channel Catfish (Ictahurus punctatus)	0	2	3	0	_	0	0	0	0	0
White Catfish (Ameiurus catus)	0	0	0	0	0	0	0	0	0	3
Brown Bullhead (Ameiurus nebulosus)	0	0	0	0	0	0	0	0	0	-
Carp (Cyprimis carpio)	0	24	80	4	1	0	0	12	10	6
Hardhead (<i>Mylopharodon conocephalus</i>)	0	0	0	0	0	0	0	0	1	0
Golden Shiner (Notemigonus crysoleucas)	2	09	44	48	16	17	1	1	0	2
Hitch (Lavinia exilicauda)	0	1	-	21	∞	6	0	0	0	0
Sacramento Squawfish (Prychocheilus grandis)	0	0	-	-	0	0	0	0	00	0
Unidentifiable Cyprinid Species (e.g., too small to accurately I.D. in field)	0	0	0	0	0	0	0	0	4	-
Inland Silverside (Menidia beryllina)	\$	54	0	0	0	2	6	-	0	0
Rainbow Trout/Steelhead (Oncorhynchus mykiss)	5	13	2	2	35	4	S	12	24	33
American Shad	0	-	6	0	0	0	0	0	0	0

Table 3. Monthly Capture of Incidental Species at the Woodbridge Dam Trap Site During October 1993 through July 1994 (Continued).	al Species at the	Woodbri	dge Dan	Trap Si	te Durin	g Octobe	er 1993 t	hrough.	fuly 1992	
Species	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	June	July
Threadfin Shad (Dorosoma Petenense)	0	0	0	0	-	0	-	0	0	0
Bigscale Logperch (Percina macrolepida)	0	8	0	0	-	0	0	0	0	-
Tule Perch (Hysterocarpus traskt)	0	-	0	0	2	2	0	0	3	∞
Smelt (Hypomesus spp.)	0	0	0	-	50	-	0	0	0	0
Splittail (Pogonichthys macrolepidotus)	0	0	0	0	4	0	0	0	0	0
Pumpkinseed (Leponis gibbosus)	0	0	0	0	0	0	0	-	0	0
Mosquitofish (Gambusia affinis)	0	0	0	0	0	0	0	0	500	0
Unidentifiable Larval Fish	0	0	0	0	0	0	c	0	c	c

A relative temporal abundance index for young-of-year fall chinook salmon passing Woodbridge Dam was generated based on the results of trap efficiency tests conducted at nine intervals throughout the season (see Table 1). From January 15 through July 31, 1994, an estimated 143,224 naturally produced young-of-year chinook salmon passed the Woodbridge Dam trap site. No statistical confidence interval for this estimate could be constructed from the data set because of variable environmental conditions during the time periods that were initially intended to serve as replicate trap efficiency tests. However, distinct differences between paired day and night trapping efficiency tests were detected by the analyses and abundance estimates were subsequently stratified by day and night time periods to improve resolution of the overall abundance estimate. Based on the stratified diurnal/nocturnal trapping efficiencies, it was estimated that about 70,600 (day) and 72,600 (night) young-of-year salmon passed Woodbridge Dam. The daily diurnal and nocturnal estimates of abundance, associated mean trap efficiencies, and the periods of estimation used to compute the overall abundance estimate are provided in Appendix 3. Figures 6 and 7 display the temporal distribution of daily estimated abundance and aggregated weekly estimates of abundance for young-of-year salmon passing the Woodbridge Dam trap site.




Figure 6. Estimated total daily abundance of young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.




Figure 7. Estimated total weekly abundance of young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.

Timing of the Downstream Migration of Juvenile Salmonids

As Figures 8 and 9 show, the majority of the 1993 brood of fall chinook salmon emigrated from the lower Mokelumne River during the months of April and May in 1994. Substantial increases in daily counts at Woodbridge Dam were observed beginning in the second and third week of April. The increased trap capture numbers were comprised almost exclusively of smolt-sized fish. This appeared to signal the beginning of a purposeful downstream smolt migration (Figure 9).

Very few fry-sized (TL\lesson mm) salmon were captured passing Woodbridge Dam and abundance estimates indicated that few naturally-produced salmon emigrated past Woodbridge Dam as fry during 1994. It is common to observe some proportion of a juvenile chinook salmon population to disperse downstream from the spawning grounds shortly after emergence (Healey 1991, Kjelson et al. 1982). Hydrologic conditions have been observed to have a great influence on the magnitude of the fry emigration in the Sacramento River with a greater proportion of fry emigrating from upstream river reaches during wet winters with high river flows than during drier years (Vogel et al. 1988). However, the destiny of these early migrating fry varies among populations, according to Healey (1991); while some migrate directly to estuaries, others may simply relocate to other suitable freshwater rearing habitat along the river's length. From the estimates of the weekly abundance of young-of-year salmon passing Woodbridge Dam shown in Figure 7, it can be seen that only a small proportion of the annual natural production (<1% through the week of April 10) moved below Woodbridge Dam and potentially to the estuary during this early fry migration. Therefore, most of the 1993 brood year reared to smolt size in the river reaches upstream from Woodbridge Dam.

Figure 10 provides the weekly trap counts of young-of-year and yearling chinook salmon and steelhead during January through July 1994. No estimates of total abundance for yearling salmon were made because no yearling salmon were available at this time of year for conducting trap efficiency tests. Observations on yearling salmon occurrence in the traps were possible and they were present through the week of May 15; however, not in great numbers. Steelhead were not very numerous at any time during the season. Yearling and some potentially age 2+ steelhead (>200 mm TL) were captured early in the season.

Figure 8. Timing of total estimated weekly abundance and size of downstream migrant young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.




Figure 9. Timing and size of downstream migrant young-of-year chinook salmon passing Woodbridge Dam during January through July 1994.




Figure 10. Weekly counts of juvenile chinook salmon and steelhead trapped at the Woodbridge Dam on the Mokelumne River during January through July 1994.

Size and Condition of Downstream Migrant Salmon

Daily records of average TL, FL, weight, and condition factor, as well as the range in size measurements of young-of-year and yearling salmon captured at Woodbridge Dam are provided in Appendices 4 and 5. Figures 11 and 12 show the mean fish size and range of size over the duration of the seasons that young-of-year and yearling salmon were captured. The majority of young-of-year salmon captured at Woodbridge Dam were captured as smolt-sized salmon. The size criteria for separating fry and smolt chinook salmon are based on size at smoltification data for chinook salmon reviewed by Healey (1991); none exists specifically for the Mokelumne River fall chinook salmon stock. Based on the abundance estimates for downstream migrant young-of-year salmon passing Woodbridge Dam, more than 99% emigrated as smolts during 1994. The size and number of young-of-year salmon increased abruptly during the second week in April signalling the onset of the smolt emigration. The size of smolts increased gradually for the duration of the season after the onset of emigration. The mean size of yearling salmon observed passing Woodbridge Dam remained primarily in the range of 150 mm TL to 175 mm TL during the period when they were observed in greatest abundance; although, the size of these fish ranged from about 75 mm TL to over 200 mm TL over the same period from October 1993 through February 1994.

The weight and condition factor of migrating young-of-year salmon followed a similar pattern to that of changes in TL (Table 4). Weight increased slightly during the fry migration ranging from 0.2 to 0.4 grams in average weight with average condition factors ranging from 4.49 x 10⁻⁴ to 5.58 x 10⁻⁴. The abrupt occurrence of smolts in the traps affected increases in averages and standard deviations for weight and condition factor as it did for TL. The weight and condition factor of smolts migrating by Woodbridge Dam generally increased throughout the smolt migration. Late in the season, during June and July, a decrease was observed in the condition factors of migrating smolts. This phenomenon may have been the result of higher metabolic requirements of the fish associated with warmer water temperatures occurring late in the season.




Figure 11. Daily average, maximum, and minimum total lengths of young-of-year chinook salmon captured at Woodbridge Dam during January through July 1994.




Figure 12. Weekly average total length and range in size of yearling chinook salmon captured in rotary screw fish traps and downstream migrant traps installed in the fishways at Woodbridge Dam during the period October 1993 through July 1994.


WEEK ENDING DATE	hrough Jul AVGTL (mm)	STDTL (mm)	MAXTL (mm)	MINTL (mm)	AVGWT (g)	STDWT (g)	AVGK	STDK	N
01/02/94			1000	2 1	1000	1000			(
01/09/94									(
01/16/94									(
01/23/94	10/10/19								(
01/30/94						1000	THE RESERVE OF		(
02/06/94	31	0.9	32	30	0.2	0.08	0.000551	0.000253	6
02/13/94	38	3,5	53	30	0.3	0.2	0.000492	0.000145	30
02/20/94	38	4.3	54	28	0.3	0.2	0.000472	0.000133	50
02/27/94	37	6	54	29	0.3	0.26	0.000558	0.000195	17
03/06/94	37	2.3	39	35	0.3	0.01	0.000496	0.000094	10
03/13/94	40	1.4	41	39	0.3	0	0.000471	0.00005	
03/20/94	41	2.1	42	39	0.4	0.21	0.000506	0.000239	- 2
03/27/94			- 0						2
04/03/94	38	2.8	40	36	0.3	0.07	0.000449	0.000028	- 2
04/10/94	91	6.8	108	72	5.9	1.28	0.000782	0.000056	66
04/17/94	91	7.5	113	72	5.8	1.48	0.000768	0.000048	197
04/24/94	91	7.2	112	63	6	1.4	0.000771	0.000052	282
05/01/94	91	6.6	111	72	6	1.35	0.000773	0.000059	277
05/08/94	93	7	115	75	6.5	1.54	0.000778	0.000052	293
05/15/94	94	6.4	123	76	6.5	1.46	0.000783	0.000045	235
05/22/94	95	7.8	117	68	7	1,79	0.000801	0.000052	280
05/29/94	97	7.8	118	78	7.5	1.85	0.000794	0.000053	226
06/05/94	100	8.7	122	75	8.1	2.16	0.000797	0.000053	136
06/12/94	104	9.2	124	85	9.2	2.48	0.000804	0.000062	96
06/19/94	104	9.3	130	86	9.3	2.93	0.000796	0.000061	99
06/26/94	109	9.3	140	74	10.8	2.9	0.000823	0.00006	345
07/03/94	109	9.7	149	85	10.7	3.1	0.000802	0.000053	249
07/10/94	111	10.3	144	92	11.3	3.49	0.000794	0.000074	182
07/17/94	116	11.1	143	85	12.8	3.99	0.000799	0.000051	147
07/24/94	116	13.1	142	91	8.2	4.46	0.000529	0.000058	41
07/31/94	120	13.3	140	93	14.1	4.61	0.000792	0.000062	31

Effects of Physical Environmental Conditions on Downstream Migrants

Diel Periodicity of Fish Migration Past Woodbridge Dam

The effects of photoperiod (day length) on the physiology of salmonid smoltification and salmonid migration behavior, particularly at passage obstacles such as dams, are well documented (Banks 1969, Greenstreet 1992, Hoar 1988, Long 1959, McKeown 1984, Vogel et al. 1988). The diel hourly patterns of migration of smolt-sized chinook salmon passing Woodbridge Dam were documented on two occasions in May 1994 during the height of the smolt emigration. These results are shown in Figure 13. The temporal patterns of diel migration were similar during both surveys. The greatest movements of chinook salmon smolts occurred during the night time and early morning daylight hours.

The diel water temperature cycle in the lower Mokelumne River may partially influence the observed diel periodicity of migratory behavior. Average daily water temperatures during the month of May were generally in the 60°F's. Daily maximum temperatures were in the mid to upper 60's. The preferred, or optimal physiological, water temperature range for juvenile chinook salmon is considered to be from 50 to 66°F (Brett 1952, Coutant 1977, Piper et al. 1982). Generally, the coolest temperatures were experienced during the night time and early morning hours on both survey dates. During periods when day time water temperatures are elevated above the thermal preferenda, or elevated near the upper optimal temperature, migration may be optimized bioenergetically during the time period when water temperatures are coolest. Additionally, when water temperatures are warmest during the day, potential predatory fishes may also be at their most active state (provided the temperatures are not elevated above their physiological optimums and tolerances), and juvenile salmon may migrate at night to minimize their risk of being preved upon. Higher night time passage of salmon smolts was observed in June 1993 during the dark and cooler hours of night when average daily water temperatures rose into the upper 50's to lower 60's range compared to earlier in May when average daily water temperatures were cooler (Vogel and Marine 1994).






Figure 13. Hourly abundance estimates and corresponding water temperatures for diel surveys of young-of-year fall chinook salmon migration by Woodbridge Dam during May 1994.

Water Temperature, River Flow, Rainfall, Turbidity, and Lunar Phase

Daily average river flow, water turbidity, and surface water temperatures are provided in Appendix 6 for the Woodbridge Dam trap site. Daily rainfall was measured at Camanche Dam by the National Weather Service and is included in the appendix tables.

Figure 14 shows the daily river flow, Woodbridge Canal diversions, and turbidity at Woodbridge Dam. Changes in river flow were primarily related to changes in releases from Camanche Dam. The resulting hydrograph exhibited periods of relatively constant flows punctuated by relatively rapid changes in flow occurring over the course of one or two days. Rainfall caused transient, low magnitude increases in river flow generally lasting less than three to five days. The effects of rainfall at Woodbridge Dam are somewhat accentuated by accretions caused by urban drainage from the city of Lodi (Jim Burgess, EBMUD, personal communication). Turbidity fluctuated widely over the season. Periods of rainfall and subsequent runoff caused transient increases in turbidity as did the pulsed, increased releases from Camanche Dam. Turbidity also could have been a function of algal production in Camanche Reservoir and Lake Lodi that subsequently moves in the river discharges.

Figures 15 and 16 show the hourly and average daily water temperatures recorded at the trapping site. Diel changes in water temperatures were very noticeable from the hourly readings logged at the site (Figure 15). We converted hourly readings or early morning and late afternoon readings to mean daily water temperatures for comparisons to the daily numbers of outmigrant salmon.

Researchers elsewhere have noted that salmon emigrations tend to occur in groups and pulses; these pulses may correspond to increased flow events. For example, USFWS salmon research by Kjelson et al. (1982) and Vogel (1989) reported increased downstream movements of fry chinook corresponding to increase river flows and turbidity, respectively. We examined potential migratory responses to these environmental parameters and the potential influence of water temperature, lunar phase, and precipitation. In each case, no general trend or cause and effect relationship was apparent (Figures 17 and 18).




Figure 14. River flow passing Woodbridge Dam, WID canal diversions, daily average turbidity (as measured by Secchi visibility), and rainfall at Woodbridge Dam trap site (RM 39) during January through July 1994.




Figure 15. Hourly water temperatures recorded at Woodbridge Dam during January through July 1994.




Figure 16. Average daily water temperature of the Mokelumne River at Woodbridge Dam during January through July 1994.




Figure 17. Comparison of estimated total daily abundance of young-of-year chinook salmon passing Woodbridge Dam with average daily river flows passing Woodbridge Dam and water clarity (measured as Secchi depth) during January through July 1994.

01/02 01/16 01/30 02/13 02/27 03/13 03/27 04/10 04/24 05/08 05/22 06/05 06/19 07/03 07/17 07/31 01/09 01/23 02/06 02/20 03/06 03/20 04/03 04/17 05/01 05/15 05/29 06/12 06/26 07/10 07/24 WEEK ENDING DATE




Figure 18. Comparison of estimated daily total abundance of young-of-year chinook salmon passing Woodbridge Dam with daily water temperatures, lunar cycle, and daily rainfall measured during January through July 1994.

Comparison of Juvenile Salmonid Downstream Migration During 1990-1994

Monitoring of juvenile salmon outmigration in the Mokelumne River was conducted during the spring of 1990, 1991, and 1992. The purposes for this monitoring were to determine the age, size and physical condition of the migrants and to identify the environmental variables influencing the migration patterns (Bianchi et al. 1992). Unlike the monitoring conducted during 1993 and most of 1994, prior years monitoring of outmigration at Woodbridge Dam relied on downstream migrant traps installed in the two fishways (due to lower flow conditions). Because the monitoring methodologies were not the same, direct comparisons of some data between years is not possible. However, there are some useful comparisons between years which may be made.

As observed in 1993, diel sampling conducted during 1994 showed a diel periodicity of migratory behavior. This crepuscular response pattern was also observed in 1990, 1991, and 1992 by Bianchi et al. (1992) in that the greatest movement was seen during the morning twilight hours; however, they did not notice any potential effect of temperature. Their results may have also been affected by conditions at the WID fish screens (Vogel 1992). The 1990 to 1992 studies were all conducted in the month of May when daily water temperature fluctuations were not more than 1.5°C and the influence of temperature may not be as acute. In fact, Greenstreet (1992) proposed a hierarchy of environmental cues eliciting migration of Atlantic salmon (Salmo salar) smolts down release ladders as spate (rain storm) > light intensity > water temperature. This hierarchy may be dynamic as critical thresholds for each of these factors may interact in eliciting migrational behavior of smolting salmonids.

The timing of smolt emigration past Woodbridge Dam during 1994 was similar to that observed in 1991 and 1992 but dissimilar to migration observed during 1990 and 1993 (Figure 19). In both 1990 and 1993, the peak emigration of smolts occurred during early June through mid June whereas in 1991, 1992 and 1994 the greatest majority of fish had migrated past Woodbridge Dam prior to June 1 (Figure 19). River flows during 1990, 1991, 1992 and 1994 were substantially lower during the principal migratory period than the river flow during the spring of 1993. Based on graphical presentations of the Bianchi et. al. (1992) data, it appears that water temperatures recorded in 1991 and 1992 at Woodbridge Dam were approximately 1 to 2 degrees Fahrenheit higher during comparable periods in 1993 which may account for some of the differences in migration timing between years. Water temperature data for 1990 were not available for direct comparison with 1993. The average daily water temperature recorded at Woodbridge Dam during April, May and June in 1993 was 56.3°F (S.D. 2.3) whereas the average daily water temperature at the same site and period in 1994 was 64.7°F (S.D. 3.1). This higher average daily water temperature in 1994 (approximately 8°F) may partially account for the earlier outmigration observed in 1994 than in 1993 (Figure 19).

The total numbers of young salmon estimated to have past Woodbridge Dam during April through July in 1993 and 1994 were substantially greater than during a similar time period in 1990, 1991, and 1992. Based on abundance index estimates in 1993 and 1994, 175,522 and




Figure 19. Comparison of weekly counts of downstream migrant chinook salmon at Woodbridge Dam for 1990, 1991 and 1993, and weekly abundance estimates of young chinook salmon at Woodbridge Dam for 1993 and 1994.

142,670 salmon, respectively, emigrated past Woodbridge Dam during April through July whereas only 78,179, 31,025, and 69,993 salmon were captured during a similar period in 1990, 1991, and 1992, respectively. Caution should be used in direct comparisons between years because of differences in sampling methods.

Assessment of Physical Injury of Juvenile Chinook Salmon Passing Woodbridge Dam

Eight tests on potential physical injury to young chinook salmon passing over Woodbridge Dam were performed during June 1 and 8, 1994. Of the 22 spill bays on Woodbridge Dam (Figure 2), tests were conducted in bay numbers 2 and 3. Results of these tests are given in Table 5. Our null hypothesis tested was that there would be no significant differences in the proportion of dead to live fish in comparable control and experimental groups of fish after four to seven days. We treated each comparison of mortality in control and experimental groups of fish independent from other tests (i.e., data were not pooled).

After four days, no mortality was noted among any of the control or experimental groups of fish. After seven days, only one of the eight tests showed a higher mortality in the experimental group of fish as compared to the control group, whereas six of the tests showed a higher mortality among control fish. Based on these results, we could not detect any measurable mortality resulting from physical injury for fish passing over spill bays 2 and 3 on Woodbridge Dam. We suspect that the mortalities which did occur among control and experimental fish after being held for four to seven days were primarily attributable to relatively warm water temperatures (>65°F).

These test results were much different than similar tests performed at the dam in 1993. In 1993, 8 of 14 fish release tests demonstrated highly significant differences in the proportion of dead fish in experimental releases over the dam as compared to their corresponding control groups. Sixty percent of the mortalities observed in the 1993 experimental groups occurred within the first four days following test releases (Vogel and Marine 1994).

Factors potentially influencing young salmon passing over the top of Woodbridge Dam and through the riprap immediately downstream of the dam are varied and complex. Most of the 22 spill bays on the dam (i.e., bay 4-22) are somewhat different in their physical and hydraulic configurations. The physical and hydraulic conditions fish are exposed to during their passage through or over the riprap downstream of each spill bay are different between bays. This latter circumstance is attributable to the non-uniform size, irregular shape, configuration, and distribution of the riprap material (mostly varying sizes of broken-up concrete) downstream of each spill bay. It would be very difficult to quantify those specific differences between spill bays because of the highly circuitous routes fish may pass over or through the riprap material. However, unlike bay numbers 4-22, water flowing over bays 1, 2 and 3 primarily passes onto smooth concrete downstream of the dam and into the dam's tailwater pool. This smoother route of passage for fish may account for the absence of physical-injury-related mortality noted in the 1994 tests. The 1993 tests where significant mortality occurred were performed in spill bays 9, 14 and 15, which pass flow into riprap downstream of the dam.

the first that dependent	BAYNEROMLET SIDEFACEAGOS	TESEDACIE	APPROX # OF PINFEL EASED	# OP FISH		CUM	TULATIVE	TVE MORTALITY ONUMBER FOLLOWING RECAPTURE	CUMULATIVE MORTALITY (NUMBER OF FISE) FOLLOWING RECAPTURE	OF FISH)		TOTAL	TOTALIOF	MEAN PL DEADING	MEANFL	MORTALITY	ADI. DIFF.
IESI OROOF				CAPTURED	IDAY	2DAYS	3DAYS	4DAYS	SDAYS	6DAYS	7DAYS	FISH		(mm)	(mm)	(%)	8
IA-EXPERIMENTAL IB-CONTROL	•	¥6/10/9	300	22.5	00	00	0.0	0.0	0-	0 =	- 6	1.5	27 67	28	TT.	3.6	(33)
2A-EXPERIMENTAL 2B-CONTROL	3	46/10/94	88	51 62	00	00	0 0	00	0.0	00	N) (N)	2.6	2.8	74	7.4	33.3	200
13A-EXPERIMENTAL 13B-CONTROL	9	96/10/9	000	2 %	00	00	0	00	00	0	00	00	n x	0	77.	00	00
14A-EXPERIMENTAL 14B-CONTROL	3	6/01/94	900	31	0	00	00	00		00	0-	0 1	n g	73	82 亿	0.0	(32)
1A-EXPERIMENTAL 18-CONTROL	2	608/94	900	75 26	00	00	00	00	00	1 3	- 5	64 80	35	812	84	5.4	(3.0)
2A-EXPERIMENTAL 2B-CONTROL	1	60894	98 8	335	00	00	00	00	0 44	0 1	07	0.50	28	77	8.6	82	(-8.2)
13A-EXPERIMENTAL 13B-CONTROL	2	60894	8 8	63	00	00	0.0	00	0-	0 -	on	0 %	£ 85	0 11	8,8	0.0	(-11.4)
14A-EXPERIMENTAL 14B-CONTROL	2	60894	88	7.4	00	00	00	00		0 -		84.5	n:	8	83	7.4	

Assessment of Survival of Juvenile Chinook Salmon Migrating Through the Sacramento-San Joaquin Delta During the Spring of 1994.

MRFI Chinook Salmon

Table 6 gives the release and recovery data for the approximately 207,000 hatchery fall-run chinook salmon coded-wire tagged at MRFI and released during the spring of 1994. Table 7 gives specific release data for each of the tag groups.

Table 6. Release and Recovery Information for Four Groups of Mokelumne River Fish Installation Coded-Wire Tagged Juvenile Fall-Run Chinook Salmon Captured at the Chipps Island USFWS Trawling Station, Spring 1994.

Tag Code	Release Date	Number of Fish Tagged	Date of First Catch	Date of Last Catch	Number of Fish Recovered	Days at Large	Minutes Sampled	Fraction of Time Sampled	Estimated Survival
6-48- 03	5-10-94	53,606	5-15- 94	5-26- 94	5	12	2,360	0.13657	0.08879
6-48- 04	5-10-94	49,864	5-15- 94	5-31- 94	6	17	3,160	0.12908	0.12119
6-48- 01	5-23-94	51,314	5-27- 94	5-31- 94	9	5	1,000	0.13889	0.16417
6-48- 02	5-23-94	51,418	5-27- 94	6-6-94	10	11	2,200	0.13889	0.18204

The USFWS formula for calculating estimated fish survival based on recoveries of tagged fish in trawling samples collected by the USFWS near Chipps Island is as follows.

Estimated Survival = R / [(M) (30 feet / 3900 feet) (Proportion of Time Sampled)]

Code ID	Code ID Egg Lot Brood	Brood	Release	D: Rele	Date Released	Rearing				Estimated No. Tagged		No./lb. at	No./Ib. Avg Length at in FL (mm)	Rearing	Stock of ReleaseGroum
	No.	Year	Location	First	Last	Type	Purpose	Tagged	Mortality Prior to Release	Released	Days	Release		Location	
6-48-03	Mixed	1993	New Hope Landing-Mok. R.	5/10/94	5/10/94	5/10/94 5/10/94 Hatchery	Delta Mortality Estimate	54,102	%6.0	53,606	22-until chk 26-until rel.	59	87.2	Mokelumne River Fish Installation	Mokelumne River
6-48-04	Mixed	1993	New Hope 5/10/94 5/10/94 Hatchery Landing-Mok.	5/10/94	5/10/94	Hatchery	Delta Mortality Estimate	50,220	0.7%	49,864	18-until chk 22-until rel.	51	91.9	Mokelumne River Fish Installation	Mokelumne River
6-48-01	Mixed	1993	New Hope Landing-Mok. R.	5/23/94	5/23/94 5/23/94 Hatchery	Hatchery	Delta Mortality Estimate	51,741	0.8%	51,314	31-until chk 33-until rel.	44	95.5	Mokelumne River Fish Installation	Mokelumne River
6-48-02	Mixed	1993	New Hope Landing-Mok. R.	5/23/94	5/23/94 5/23/94 Hatchery	Hatchery	Delta Mortality Estimate	51,841	0.8%	51,418	26-until chk 28-until rel.	44	95.5	Mokelumne River Fish Installation	Mokelumne River
6-1-13-	Wild	1993	WoodnikgDem 4/8/94 6/20/94	4/8/94	6/20/94	Wild	Survival & Contrib.	7,354	3.2%	7,119	5-72	563	87	Mokelumne River Wild	Mokelumne River Wild
6-1-13-	Wild	1993	Sacto. R. Rio Vista, CA.	6/21/94 7/31/94	7/31/94	Wild	Survival & Contrib.	1,182	11.4%	1,047	0	31	102	Mokelunne Piyar Wild	Mokelumne

These groups were mixed prior to trucking and tag shed check. 6-48-01 and 6-48-02 treated as a single composite group with regard to tag shedding, mortality and size. Tag groups 6-48-03 and 6-48-04 were combined (as a result of mixing of tag groups 6-48-01 and 6-48-02) and treated as a single composite group when released.

Adjusted for estimated shed tags and pre-release mortality.

Quality control based on two holding periods. Only small sample sizes kept for these checks.

Average size for entire time interval over which tag code was used.

where R = number of tagged fish recovered and M = number of fish tagged (Mark Pierce, USFWS, Stockton, pers. comm.). A calculated value of 1 would represent 100 percent survival. For all tagged groups released, recoveries by the USFWS at their Chipps Island trawling station and their estimated survival rates were very low. Similarly low recovery rates on prior year's MRFI coded-wire tagged fall-run chinook were also evident (Bianchi et al. 1992, Vogel and Marine 1994). Delta hydrologic conditions were variable during the periods following when tagged fish were released (Appendix 7). Because the numbers of tagged fish recovered for all tagged groups were very small, we do not believe that specific conclusions can be derived from these data at this time. Tag recoveries in the ocean sport and commercial fisheries and in adult fish returning to the river systems during the next two to four years will provide better information concerning the tagged fish released during 1994.

Wild Chinook Salmon Smolts Coded-Wire Tagged at Woodbridge Dam

Appendix 2 provides a daily record of the numbers of wild fall chinook salmon smolts captured and coded-wire tagged at Woodbridge Dam. Additional relevant data are provided in Table 7. Tagging was initiated on April 8, 1994 when a substantial increase in the numbers of smolt-sized salmon was observed in the traps. Two tag codes were used during the season. These two codes were allocated to essentially the first and second halves of the total migration of smolts as follows:

Dates of Application	Tag Code	Nos. Tagged	l* Avg. Size of Fish	Release Site
4/8/94 to 6/20/94	6-1-13-1-4	7119	87 mm TL	Mokelumne River
6/21/94 to 7/31/94	6-1-13-1-5	1047	102 mm TL	(Woodbridge Dam) Sacramento River (Rio Vista, CA)

^{*}includes 96.8% tag retention adjustment

No latent mortality was observed in two samples of the first tag code group of fish retained for tagging quality control. Two samples of 32 and 16 fish were held for 5 to 7 days, respectively, during the first tag code period. One hundred percent tag retention and 94% retention, respectively, were observed for these samples of this tag code group. No tag retention determinations could be made for the second tag code group since water temperatures were elevated at Woodbridge Dam during the period of application and fish could not be safely confined and held at those temperatures. Tagging reports with all the preceding information were submitted to CDFG during July and August 1994.

None of these tagged wild chinook salmon were reported as captured by the USFWS at their trawling station near Chipps Island. Because the numbers released were relatively small, no inferences can be made as to survival rates for these fish migrating through the Delta. As discussed for the MRFI hatchery coded-wire salmon, tag recoveries in the ocean sport and commercial fisheries and in adult fish returning to the river systems are expected to provide

better information concerning these two groups of fish.

Releases of PIT-Tagged Chinook Salmon in Lake Lodi

Figure 5 shows the locations where PIT-tagged chinook salmon were released in Lake Lodi on July 18-20, 1994. Table 8 and Appendix 8 give the results of those releases. Of 1,249 PIT-tagged salmon released, only 135 fish (10.8%) were recaptured in the two downstream migrant fish traps at Woodbridge Dam. The recapture rates for all release groups was consistently low for all seven releases, ranging from 6.9% to 14.5%. Because nearly the entire flow past Woodbridge Dam during this time of year was comprised of flow entering the high-stage fishway (via a culvert) or the low-stage fishway (the WID fish screen bypass outfall) (Figure 2), it was assumed the fish traps were 100 percent efficient in capturing fish choosing these passage routes. The fate of the fish not captured (89.2%) is unknown. Those fish could have migrated past the dam after August 1 when the traps were removed, remained in Lake Lodi, migrated to upstream locations, or die from unknown factors (e.g., predation).

Although mortality estimates for PIT-tagged fish are not possible for the previously described reasons, several interesting observations on fish behavior can be made. The median elapsed time between release and recapture for all fish was approximately 1.5 days. Eight fish were not recaptured until more than ten days after their release had elapsed (Appendix 8). There was a greater tendency for fish to use the WID fish screen bypass (101 fish or 75%) than the roadway culvert (34 fish or 25%) as a route of passage at the dam. We suspect that this behavior was largely attributable to the disproportionate flow split toward the fish screens (i.e., greater) than toward the dam. Fish utilizing the fish screen bypass exhibited a lower median recovery time than fish migrating through the roadway culvert (1.47 days versus 4.49 days, respectively). Fish in the immediate vicinity of the dam may have had difficulty locating the small submerged culvert opening under the roadway (Figure 2). It is interesting to note that the greatest proportion of fish released near Woodbridge Dam swam back upstream and through the fish screen bypass instead of through the culvert into the high-stage fishway (Table 8 and Figure 5). The one group of fish released just upstream of the WID fish screens showed the most rapid rate of migration (0.46 days recovery time). Excluding Release No. 7 in which only 2 fish were recovered, the furthest upstream release group showed the slowest median migration rate (3.84 days).

			Recovery Location:	Location:				
		High-Sta	High-Stage Fishway	Low-Sta	Low-Stage Fishway		Median Perovery	
Release Location*:	Total Number Released:	Number	Median Recovery Time (days)	Number	Median Recovery Time (days)	Total Recovered	Time (days)	Percent Recaptured
1 (RM 38.7)	200	3	10.48	18	1.55	21	1.55	10.5%
2 (RM 39.0)	200	3	4.48	18	0.46	21	0.46	10.5%
3 (RM 39.7)	200	9	4.98	23	1.46	29	1.46	14.5%
4 (RM 40.75)	200	8	4.61	16	1.47	24	1.47	12.0%
5 (RM 42.1)	204	10	3.85	8	1.82	18	3.84	8.8%
6 (RM 39.7)	216	4	3.97	16	0.83	20	0.83	9.3%
7 (RM 38.6)	29	0	N/A	2	6.47	2	6.47	%6.9
Totals	1249	34	4.49	101	1.46	135	1.47	10.8%
			* Release	* Release Locations:				
1=250 ft u/s of 7 2=50 ft u/s of W 3=Park Gazebo	1=250 ft u/s of WID Dam @ 2115 hrs, 7/18/94 2=50 ft u/s of WID screens @ 2105 hrs, 7/18/94 3=Park Gazebo @ 2115 hrs, 7/19/94	hrs, 7/18/94 5 hrs, 7/18/94 94				4=Concrete 5=Railroad I 6=Park Gaze	4=Concrete Pad @ 2100 hrs, 7/19/94 5=Railroad Bridge @ 1230 hrs, 7/20/94 6=Park Gazebo @ 1215 hrs, 7/20/94	rs, 7/19/94) hrs, 7/20/94 s, 7/20/94

Radio-Telemetry Assessment of the Migratory Behavior of Juvenile Salmonids Through Lake Lodi

Eighteen age 1+ hatchery-reared steelhead and one age 1+ fall chinook salmon that was captured in the rotary screw trap at Woodbridge Dam were radio tagged and released in Lake Lodi at two different locations. The results of this telemetry effort are summarized in Table 9.

Table 9. Summary of Results for Releases of Radio-Tagged Juvenile Salmonids in Lake Lodi During the Period of April - July 1994.

Date of Release	Location of Release	Species	N	# Approaching Dam	# Passing Dam	Delay in Passing Dan (days after first encounter)
4/22/94	Hwy 99 Br. (RM 43)	STH	4	2	1	5 days
5/27/94	Hwy 99 Br. (RM 43)	STH	5	1	0	N/A
6/11/94 1	Hwy 99 Br. (RM 43)	STH	4	0	0	N/A
6/16/94 2	Hwy 99 Br. (RM 43)	FCS (Age 1+)	1	0	0	N/A
7/7/94 3	40 m u/s from WID intake	STH	5	2	1	20 days

Three of four steelhead released moved upstream of the release site and remained upstream until transmitters failed,

Juvenile steelhead exhibited both upstream and downstream movements in Lake Lodi upon release during the period of observations from April through July 1994. Movements of five of the radio-tagged fish were tracked to Woodbridge Dam. A fairly slow rate of downstream movement under conditions during the period of study was observed for radio-tagged juvenile steelhead. The five fish that approached and encountered the dam did so over a period of time ranging from about 1.5 to 10 days. Three of these fish were released near the head of Lake Lodi approximately 5 river miles upstream from Woodbridge Dam near the state highway bridge crossing (Highway 99) and migrated to the dam at rates ranging from about 0.5 to 2.0 miles per day.

Of the five radio-tagged steelhead approaching Woodbridge Dam, only two were detected (either by telemetry or recapture in downstream migrant traps) to have passed the dam, and apparent delays in passing the dam for these two fish ranged from 5 to 20 days. Transmitter life

¹This salmon moved 3 river miles downstream to RM41 and remained in this vicinity, actively moving in response to boot traffic, for 6 days prior to failure of transmitter.

All five steelhead released for these observations remained in the vicinity of Lake Lodi Park or near WID intake or near dam. One radio-tagged steelhead was recaptured in the fish bypass outfall downstream migrant trap on 7/27/94, 20 days after release.

for the small radio tags ranged from 8 to 13 days and limited the time of observation; so the eventual fates for fish that remained in the vicinity of the dam at the time of transmitter failure and were not captured in the downstream migrant traps are not known.

The behavior of juvenile steelhead during the period of investigation probably was not representative of that of actively emigrating steelhead smolts. Most steelhead smolts (age 1 to age 2+ steelhead) in Central Valley streams begin migrating downstream during the first storm runoff events in the fall and continue to emigrate through the winter and early spring months (Hallock 1989). Use of steelhead smolts during the normal downstream migration period would likely produce very different results. The use of actively migrating salmonid smolts was originally planned for this task to produce more meaningful results. However, young-of-year fall chinook salmon were too small to outfit with radio tags even at the larger fish sizes occurring late in the season. We attempted to radio tag 10 young-of-year fall chinook salmon captured at Woodbridge Dam; but after recovery from the tagging surgery, all 10 fish died during a subsequent 24-hour post-tagging observation period. The single yearling fall chinook salmon captured and radio-tagged at Woodbridge Dam survived the required handling and tagging surgery, but its transmitter failed 6 days after its release.

Based on the experience gained during this season, it is recommended that yearling-sized fall chinook salmon be used in future radio telemetry evaluations of juvenile salmonid migratory behavior in Lake Lodi. Yearling salmon may be used as late as March and April for behavioral assessments of downstream migration with reasonable results (Vogel et al. 1988).

Lake Lodi Water Quality Monitoring

Appendix 9 gives the data for all water quality monitoring from May 26 through July 25, 1994 in Lake Lodi and the Mokelumne River. Figure 20 shows that a substantial increase in water temperature occurred from upstream to downstream areas during this entire period. In addition, thermal stratification in Lake Lodi was evident during all monitoring. Water was generally cooler at River Mile 39.0 in the right channel (facing downstream) as compared to the left channel near the WID screens (Figure 5), presumably because of the deeper water in the right channel (Appendix 9). PH, a measure of the hydrogen ion concentration of the water, ranged between 8.15 to 9.52. On some occasions, the deepest stations (approximately 15 feet) sampled in Lake Lodi exhibited a tendency of the highest pH values near the surface. These results may be attributable to higher algal and photosynthesis activity near the surface than near the bottom of the reservoir. All measured pH values were relatively high and approached the maximum recommended pH criteria for most fishes which is about 9.0 (EIFAC 1969, Piper et. al. 1982, Spotte 1970). Depending on site-specific conditions, these levels could be stressful to rearing salmonids. Dissolved oxygen (DO) levels during the season varied from 8.45 mg/l to 11.34 mg/l and 92.8% saturation to 124.5% saturation (Appendix 9). These values are within satisfactory ranges of fish. Specific conductance, which is an indirect measurement of total dissolved solids. ranged from 39.6 to 47.7 μs/cm. These values varied very little over the season and between locations (Appendix 9.)




Figure 20. Water temperature measurements (in Fahrenheit) for Lake Lodi and the Mokelumne River (May 26 to July 25, 1994).




Figure 20 (continued). Water temperature measurements (in Fahrenheit) for Lake Lodi and the Mokelumne River (May 26 to July 25, 1994).




Figure 20 (continued). Water temperature measurements (in Fahrenheit) for Lake Lodi and the Mokelumne River (May 26 to July 25, 1994).

Physiological Assessment of Smolt Development of Fall Chinook Salmon

The temporal development of gill Na⁺/K⁺ ATPase activity has been used successfully to characterize one of the many physiological metamorphoses that salmon undergo preparatory to their transition from an early life stage in freshwater to their ocean life stage (Hoar 1988). The underlying physiological processes reflected by changes in gill Na⁺/K⁺ ATPase have also been demonstrated to be affected by environmental factors such as photoperiod, water chemistry, and water temperature, as well as, biological factors such as disease, social interactions, and nutrition (Ewing et al. 1979, Lorz and McPherson 1977, Schreck et al. 1985, Wedemeyer et al. 1980, Zaugg 1982).

Smolt development was monitored in samples of downstream migrant salmon captured in the downstream migrant traps at Woodbridge Dam and in comparative samples collected on the rearing grounds in the river reaches upstream from Woodbridge Dam. Data collected from all fish sampled for physiological measurements are provided in Appendix 10 and Table 10 provides a summary of these results.

Table 10. Comparison of size, condition factor, gill Na+/K+ ATPase specific activity in samples of young-of-year chinook salmon collected in downstream migrant traps at Woodbridge Dam and by beach seining in the rearing reaches of the Mokelumne River during March through July 1994 (values are means with standard deviations in parentheses).


			Upstream I	Habitat				Woodbridge	e Dam	
Date	TL(mm)	Wt (g)	К	Na*/K* ATPase (um P/mgProt/hr)	N	TL(mm)	Wt(g)	К	Na ⁺ /K ⁺ ATPase (um P/mgProt/hr)	N
3/25/94	56 (6.1)	1.5	.000807 (.00004)	2.9 (1.97)	10					0
4/11/94					0	90 (7.8)	5.7 (1.64)	.000758 (.00003)	3.95 (0.77)	7
4/12/94	68 (12.2)	1.8 (0.90)	.000540 (.00008)	1.8 (0.80)	8					0
4/25/94	79 (5.7)	4.2 (0.77)	.000847 (.00004)	3.33 (0.86)	7	104 (8.5)	9.0 (2.18)	.000780 (.00006)	4.14 (0.78)	6
5/10/94	83 (2.3)	4.9 (0.66)	.000868	3.15 (0.54)	6	84 (5.9)	6.5 (1.65)	.00106 (.00007)	5.74 (1.4)	6
5/23/94	85 (4.6)	5.6 (0.48)	.000907 (.00008)	2.38 (0.92)	6	101 (4.6)	8.2 (1.1)	.000788 (.00005)	2.33 (1.57)	6
6/10/94					0	103 (6.1)	8.6 (1.18)	.000797 (.00006)	2.35 (1.03)	7
6/24/94	95	7.9	.000921	0.48	1	109 (5.1)	11.4 (1.67)	.000874 (.00004)	2.49 (1.02)	7
7/10/94					0	111 (12)	10,5 (2.22)	.000764 (.0001)	2.52 (1.38)	7
7/23/94					0	109 (7.8)	10.3 (2.49)	.000794	2.21 (1.63)	7

Size of fish sampled at both locations generally increased throughout the season. Fish migrating by Woodbridge Dam were generally significantly larger (≈=0.05) than fish collected on the rearing grounds, except on May 10. Condition factor of fish on the rearing grounds was generally greater than that of fish migrating past Woodbridge Dam. This difference in condition factor between fish on the rearing grounds and those passing Woodbridge Dam was also observed during 1993 by Vogel and Marine (1994) and is attributed to morphological changes (fish become less plump), which affect condition factor, that occur during smoltification for several species of salmonids (Hoar 1988, McKeown 1984, Woo et al. 1978).

Gill Na⁺/K⁺ ATPase activity also reflected potential differences in the smolt status of juvenile salmon as they rear in the lower Mokelumne River. Specific activity of gill Na⁺/K⁺ ATPase was higher throughout the season in fish migrating past Woodbridge Dam than in fish collected from the rearing grounds (Figure 18). This difference was statistically significant (P<0.05) on April 11 and again on May 10. Peaks of gill Na⁺/K⁺ ATPase activity for fish collected in the rearing habitats occurred simultaneous with the full moon in March and April, however, no cyclic changes in gill Na⁺/K⁺ ATPase activity were observed for fish passing Woodbridge Dam. Lack of distinct cyclic changes in gill Na⁺/K⁺ ATPase activity in wild coho salmon compared to that observed for hatchery-reared salmon was also noted by Rodgers *et al.* (1987); so, periodicity of this smolt indice should not necessarily be expected in samples from wild fish.

Gill Na*/K* ATPase activity remained relatively constant at lower levels for samples collected from fish passing Woodbridge Dam during June and July. Few fish remained on the rearing grounds during June and July and only one fish was collected there during those months despite persistent efforts to collect them. The specific nature of this decline in gill Na*/K* ATPase activity late in the season is not specifically revealed by the data set. It may be a characteristic of the population of late-migrating smolts, perhaps reflective of a slower smolt development in these fishes. Alternatively, it may occur in response to a threshold elevated water temperature. Decreased gill Na*/K* ATPase activity related to elevated water temperatures has been observed for laboratory populations of chinook salmon (Ewing et al. 1979, Wedemeyer et al. 1980, Zaugg 1982). However, this response in wild fish has not yet been confirmed.

Gill Na⁺/K⁺ ATPase activities, along with other indices of smolt development such as condition factor, of young-of-year fall chinook salmon passing Woodbridge Dam indicate that these fish are undergoing active smoltification preparatory to their transition to life in seawater. The use of gill Na⁺/K⁺ ATPase activity as an assessment tool for monitoring the effects of changes in environmental factors, particularly water temperature, on smolt development may be useful for evaluating different management options for the lower Mokelumne River. This year's experience indicates that it can detect spatiotemporal differences in gill Na⁺/K⁺ ATPase activity of actively migrating and rearing salmon. Additional assessment of this technique under differing hydrologic year types with different water temperature regimes would allow resolution of the competing hypotheses potentially explaining observations during 1994.



collected in the rearing reaches and as emigrants passing Woodbridge Dam on the Mokelumne River during March through July Figure 21. Temporal profile of mean gill Na+/K+ ATPase specific activity from samples of young-of-year fall chinook salmon 1994 (values are means of N=6 - 10 measurements, except for 6/24/94 rearing habitat sample in which N=1).

ACKNOWLEDGMENTS

The field crew of Vogel Environmental Services consisting of Bill Norman and Janet Yoshidome, Jose Setka and Rick Chapman (of Big Eagle and Associates) who collectively executed the daily fish trapping and riverine monitoring tasks throughout the salmon downstream migration season are gratefully acknowledged for their able assistance. Denisa Vogel is thanked for her work on day-to-day office administration associated with this project and for building many of the data files, figures, graphs, and tables for this report. Kathy Nolan also assisted in the preparation of this report. Sven Johnson's (VES) periodic guidance and advice on a variety of field sampling operations (particularly his design of the Woodbridge Dam rotary trap cabling apparatus and contribution to design of the incline plane trap) served to significantly improve the effectiveness of the downstream migrant monitoring program. The coded-wire tagging crew of Big Eagle and Associates deserve special recognition for their tagging operations the Mokelumne River Fish Hatchery. The cooperation of Woodbridge Irrigation District, Anders Christensen (WID Manager), and the WID staff is especially appreciated for allowing these important fishery resource investigations to be largely based from their property. The CDFG Rancho Cordova staff provided periodic guidance, assistance, and cooperation throughout this investigation; use of the agency's coded-wire tagging equipment was very much appreciated. The CDFG staff at the Mokelumne River Fish Hatchery provided especially valuable assistance during the coded-wire tagging operations at the hatchery; the work could not have been performed without their outstanding cooperation.

REFERENCES

Bagenal, T.B. and F.W. Tesch. 1978. Age and growth. Pages 101-136 in T.B. Bagenal (editor). Methods for Assessment of Fish Production in Fresh Waters. IBP Handbook No. 3. Blackwell Scientific Publications. Oxford, England.

Banks, J.W. 1969. A review of the literature on the upstream migration of adult salmonids. J. Fish Biol. 1:85-136.

Bianchi, E.W., W. Walsh, and C. Marzuola. 1992. Task reports of fisheries studies on the Mokelumne River 1990-1992. (Appendix A of the Lower Mokelumne River Management Plan). Report to East Bay Municipal Utility District, Oakland, California. BioSystems Analysis, Inc., Tiburon, California.

Brett, J.R. 1952. Temperature tolerance in young Pacific salmon, genus Oncorhynchus. J. Fish. Res. Board Can. 9: 265-323.

Carmichael, F. J. and Jr. Tomasso. 1988. Survey of Fish Transportation Equipment and Techniques. Progressive Fish Culturist. 50:155-159.

Coutant, C.C. 1977. Compilation of temperature preference data. J. Fish. Res. Board Can. 34: 739-745.

European Inland Fisheries Advisory Commission (EIFAC). Working party on water quality criteria for European freshwater fish. 1969. Report of extreme pH values and inland fishes. Copeia 1991:1109-1111.

Ewing, R.D., S.L. Johnson, H.J. Pribble, and J.A. Lichatowich. 1979. temperature and photoperiod effects on gill Na⁺/K⁺ ATPase activity in chinook salmon (Oncorhynchus tshawytscha). J. Fish. Res. Board Can. 36: 1347-1353.

Greenstreet, S.P.R. 1992. Migration of hatchery reared juvenile Atlantic salmon, Salmo salar L., smolts down a release ladder. 1. Environmental effects on migratory activity. J. Fish Biol. 40:655-666.

Hallock, R.J. 1989. Upper Sacramento River steelhead, Oncorhynchus mykiss, 1952-1988. A report to the U.S. Fish and Wildlife Service. 86 pp.

Healey, M.C. 1991. Life history of chinook salmon (Oncorhynchus tshawytscha). Pages 311-384 in C. Groot and L. Margolis (editors). Pacific Salmon Life Histories. University of British Columbia Press. Vancouver, British Columbia, Canada.

Hoar, W.S. 1988. The physiology of smolting salmonids. Pages 275-343 in W.S. Hoar and

D.L. Randall (editors). Fish Physiology. Academic Press, San Diego, California.

Hurlbert, S.H. 1984. Pseudoreplication and the design of ecological field experiments. Ecological Monographs 54: 187-211.

Johnson, S.L., R.D. Ewing, and J.L. Lichatowich. 1977. Characterization of gill Na⁺/K⁺ adenosine triphosphate from chinook salmon, Oncorhynchus tshawytscha. J. Exp. Zool. 199: 345-354.

Kjelson, M. A., P.F. Raquel, and F.W. Fisher. 1982. Life history of fall-run juvenile chinook salmon, *Oncorhynchus tshawytscha*, in the Sacramento-San Joaquin estuary, California. Pages 393-411 in V.S. Kennedy (editor), *Estuarine Comparisons*. Academic Press, New York.

Long, C.W. 1959. Passage of salmonids through a darkened fishway. US Fish and Wildlife Service Special Scientific Report-Fisheries No. 300. Washington, D.C. 13 pp.

Long, C.W., J. R. McComes, H. Mouk. 1977. Use of Salt (NaCl) Water to Reduce Mortality of Chinook Salmon Smolts, (Onchorhynchus tshawytscha) During Handling and Hauling. Marine Fisheries Review 39:6-9.

Lorz, H.W. and B.P. McPherson. 1977. Effects of copper and zinc on smoltification of coho salmon. U.S. Environmental Protection Agency, Ecol. Res. Ser. EPA-600/3-77-032, Corvallis, Oregon.

McKeown, B.A. 1984. Fish Migration. Timber Press. Portland, Oregon. 224 pp.

Neter, J. and W. Wasserman. 1974. Applied Linear Statistical Models. Richard Irwin, Incorporated, Homewood, IL.

Piper, R.G., I.B. McElwain, L.E. Orme, J.P. McCraren, L.G. Fowler, and J.R. Leonard. 1982. Fish Hatchery Management. U.S. Department of the Interior. Fish and Wildlife Service. Washington, D.C. 517 pp.

Rodgers, J.D., R.D. Ewing, and J.D. Hall. 1987. Physiological changes during seaward migration of wild juvenile coho salmon (*Oncorhynchus kisutch*). Can. J. Fish. Aquatic Sci. 44: 452-457.

Schreck, C.B., R. Patina, C.K. Pring, J.R. Winto, and J.E. Holway. 1985. Effects of rearing density on indices of smoltification and performance of coho salmon, Oncorhynchus kisutch. Aquaculture 45: 345-358.

Spotte, S.H. 1970. Fish and invertebrate culture. John Wiley & Sons, Inc. New York. 145 pp.

Summerfelt, R.C. and L.S. Smith. 1990. Anesthesia, surgery, and related techniques. Pages 213-334 in C.B. Schreck and P.B. Moyle (editors). *Methods for Fish Biology*. American Fisheries Society. Bethesda, Maryland.

Vogel, D.A. 1989. Tehama-Colusa Canal Diversion and Fishery Problems Study. Final Report. U.S. Fish and Wildlife Service Report No. AFF/FAO-89-06. April 1989. 33 pp. with appendices.

Vogel, D.A. 1992. Assessment of the Fish Passage Facilities at Lake Lodi in the Mokelumne River. Vogel Environmental Services. 42 pp.

Vogel, D.A., K.R. Marine, and J.G. Smith. 1988. Fish Passage Action Program for Red Bluff Diversion Dam: Final Report on Fishery Investigations. US Fish and Wildlife Service Report No. FR1/FAO-88-1. October 1988. 77 pp. with appendices.


Wederneyer, G. 1992. Transporting and Handling Smolts. World Aquaculture. 23:47-50.

Wedemeyer, G.A., R.L. Saunders, and W.G. Clarke. 1980. Environmental factors affecting smoltification and early marine survival of anadromous salmonids. Mar. Fish. Rev. June: 1-14.

Wilkinson, L., M. Hill, J.P. Welna, and G.K. Birkenbeuel. 1992. SYSTAT for Windows: Statistics, Version 5 Edition. Evanston, IL: SYSTAT, Inc., 1992. 750 pp.

Woo, N.Y.S., H.A. Bern, and N.S. Nishioka. 1978. Changes in body composition associated with smoltification and premature transfer to seawater in coho salmon (*Oncorhynchus kisutch*) and king salmon (*Oncorhynchus tshawytscha*). J. Fish Biol. 13:420-428.

Zaugg, W.S. 1982. Some changes in smoltification and seawater adaptability of salmonids resulting from environmental and other factors. Aquaculture 28: 143-151.



	10 00 00 00 00 00 00 00 00 00 00 00 00 0	38888888888888888888888888888888888888
The Fighted	8 800 7 750 8 800 7 700 7 700 7 750	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
L.B. Platmey M.S. Platmay Time Flathed	Mocturnal 16.00 17.00 17.00 16.00 16.00 16.00 16.00 16.00	17.08 17.08
H.S. Flattway	A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z	ZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZ
L.B. Flatmery	A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z	ZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZZ
Jo a		0 aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa
-	Fp0000040000004000	00200100+54004-044-000-000-0044-00-000000-0
	Mortal	-28 00100-2004-000-000-000-58 24400-14400000-0
		-4-4-8-8-4-5-6-5-8-5-8-5-6-5-6-6-6-6-6-6-6-6-6-6-6
randTotal	Ado	
arand Tota	20000000000000000000000000000000000000	。公司正在出口的证据的的问题。 《公司正证证明》(1)(1)(1)(2)(2)(2)(2)(2)(2)(2)(3)(3)(3)(3)(4)(4)(4)(4)(4)(4)(4)(4)(4)(4)(4)(4)(4)
Grand Tota	Capital	
	Capital	
Number	Capital	
Number	### Cupps Injuries Mortality Captur 2	**************************************
Number Number Number	### Cupps Injuries Mortality Captur 2	**************************************
Ad Clina fairning Mortality	Captured Ad Clips Injuries Mortality Captured 19 2 4 4 5 5 5 5 5 5 5 5	11. 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
mber Number Number Number Schulber Cantured Ad Cition Interior Morality	Captured Ad Clips Injuries Mortality Capture 19 2 4 4 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	11. 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
mber Number Number Number Schulber Cantured Ad Cition Interior Morality	Captured Ad Clips Injuries Mortality Capture 19 2 4 4 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	12. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
mber Number Number Number Schulber Cantured Ad Cition Interior Morality	Captured Ad Clips Injuries Mortality Capture 19 2 4 4 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	11. 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
Modality Captured Ad Clina Interior Modelling	Captured Ad Clips Injuries Mortality Capture 19 2 4 4 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	### 121 ### 200ml

Page 2 of 5

∢ l'	Total 24 00	23.50	2,88	24.00	24.00	1708	29.60	2,00	24.00	24.00	17.00	88	24.00	24.00	2,00	2,5	24.80	33.35	2328	22.55	228	328	23.00	22.22	22.25	222	828	22.75	81	19.75	23.00	228	222	23.25	22.75	23.75	23.00
9	Diurnal 7.00	88	889	6.50	9	8.7	000	8 8	6.50	6.50	9 00	88	2007	200	188	88.	200	929	6.75	6.75	6.75	6.75	0.00	929	7.26	88	999	6.50	02.9	329	6.75	6.50	9 9	0.75	6.76	7.75	6.75
	17.00	17.50	17.50	17.50	17,50	17,50	23.50	17.50	17.60	17,58	17.00	17.88	128	17.80	17.00	17.88	17.00	16.75	200	15.75	2 2 20	16.75	1625	16.25	15.75	16.00	16.25	16.25	16.50	16.25	16.25	16.00	16.25 16.25	16.25	16.00	16.26 18.50	16.25
H.B. Flatmeny	Trap (Yet)																																			zz	
L.B. Flatnerry	N N	22																																		zz	
10	Screw Traps		. 64	04.04	CHI	NW	CHIC	4 64	c4 c	4 64	40	4 64	CA CA	CI IN	1011	7 77	20.00	104.0	400	M (M)	N (N	64.60	1010	4 64	N 14 1	464	N 64	N N	24.0	1010	400	4 64 1	4 64	N 64	C4 C4	00	8
ota	0	00	0	00	-	00	00	0.0	00		0.0	201	0.0	0-		00	00	00	000	201	2.5	00	000	0 = 0	200	200	00	00	00	000	000	201	0.04	00	0 =	00	0.1
rand fotal Grand Total											10000						To the																			97	ALC: UNKNOWN
randTot																												0	00		. 0 .	. 0.6		-0	00		SECTION.
Ad Cline Interded	O.		ON.	4	44	9 47	ev es	4.	(O) (**	· = ·		7	- 6	9 4	•	- 64	9 9	40 K	100	100	- 61	410	00	9 22 9	3 12 4		. 10	- 9	NN	00	. 64.8	100	-	7.50	- 0		MAIN
Grand Total In	hou		9:	2 9	Z 9		-8	100	9.0	8	6 9	9 5	28	8 2	22	:2;	# C#	SI SI	185	200	2 82	2.2	85	8	. 15 15 2 2 3 3 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	25.5	10	2 18	(1) so	D.S	324	818) (T) (0.041	- N	w w	TANK!
Number	0	00	0.0	00	00		0 0	0	0 0	0	0	00	00	o +	00	001	00	00	00		00	00	00	0 1	000	000	000	00	00	00		00	000	000		000	
Number																												0	00	00		00	00	000	000	000	
Number Number Ad Clips Injuries I	2	00	24	00	mo		- 0	٥.	- 0	2	0	00	000	7 -	-0		- 1	- 0		0 0	-	-0	9 7	0 5	· · ·	00		0 64	- 0	00	0-	mc	00	000	000	000	
Number	6	4 74	Φ C	o m	en ev		10	10 4	0 4	8	6	9 4	1001	- 10	KO KO	10 0	77.		- 9	. 6. 2	10	o io	30 6	0 4	0 10	00	40	9 40 1	-	~-	0 11	10 F	-0	000	000	000	
Number	0	00	00	00	-0	00	00	00	0 0		00	00	000	0 0	-0	00	00	0 0	00	00	1	00	00			00	00	000	00	00	00	00	00	000	o c	000	of the
Number Number Number Number Captured Ad Clips Injuries Mortality																												00	00	0-	00	00	0 =	00	00+		
Number Ad Clips	ю.	4	0 4	e Tal	- 10	40	N IO	41	- 10	a) +	*	4 -	0.	e m	m w	- 4	900	o m	10 4	100	100	מופ	90	15	42	~ ₹	4 -		- 64	01	2.2	10 v			0 +		
Number	17	¥ 0	On u	12:	17	2:	3:	18	£ 12	Z.	3	2 =	80	2 9 :	21.2	12	2 12 2	17	2 23	₽4	28	2 2	4 8	86	128	21	==	8,	- 10	o 2	22	42	10 10		- CV 16	a 10 10	- Carrier
Date	12/17	278	12/20	12/2	12/23	12/26	1227	12/28	12/30	1231	01/02	0103	9010	10010	01708	01/10	01/12	01/14	91/16	01/13	91/10	0121	2210	01/24	72710	8210	0010	1020	22/03	200	2000	2008	12710	02/12	02714	02/16	The same

Page 3 of 5

4 L	Total 22.75	288	3.5	2250	23.73	222	2222	2828	3888 3888 3888	1888	2222 2222	828	222	2222	1888 1888 1888	828	23.75	2222 2223	2222	88888	2350
LE Fight of Barray Land Fighed	6.25	888	7.50	6.50	888	888	8.22	8888	8888	2,02	8888	228	NNS	5.25 2.25 2.25 2.25 2.25 2.25 2.25 2.25	8882	585	N 8 8	7.00	8888	8888	88
1	16.50	17,00	17,00	16.88	200	16.50	16.25 16.50	# # # # # # # # # # # # # # # # # # # #	16.25	16.75 16.50	# # # # # # # # # # # # # # # # # #	16.25 16.50 16.00	1625 1625 1625	8.85 8.85 8.85 8.85 8.85	25 5 5 5 25 5 5 5 25 5 5 5	18.25 16.26 16.50	16.50 16.50 16.75	16.25 16.25 16.25 16.25	25 25 25 25 25 25 25 25 25 25 25 25 25 2	625 625 625 625 625 625 625 625 625 625	16.50
N.S. Fishway		222	ZZ	ZZ	ZZZ															ZZZZ	
LS. Platiway	Trup (TR			222		ZZ			tzzz	ZZZ	ZZZZ	ZZZZ	ZZZ	ZZZ	2222	ZZZ:	ZZZ	ZZZZ	ZZZ	ZZZZ	ZZ
Jo #	Screw Iraps	10000			7.323			C4 C4 C4		TATE IS S											***
11 2	.0.	.00	00	000	0.00	000	000	0000	0000	0000	2000	0000	000	000	0000	0000	000	2000	1000	0000	00
Grand Total	- Colors																				
fandTotal																				0000	
Ad Clips	120	0.0	97	0.00	0.0	000	0000	0000	000	0000	1000	0000	00-0	000	00-0	0-00	000	0000	000	0000	00
GrandTotal	Ç, ç	10.04	04	000	700	NOI	9000	N F 0 0	0 - 0	0-00	,	-0-0	00-0	000-	-0-0	r 10 (4 C	0-0	000-	0-0	0000	00
r Number Mortality	00	00	00	enes.		000				0000			0000							0000	
Number	188																				
Number Ad Clips	00		7074	000		000						0000								2000	
Number Number Numbe Captured Ad Clips Injuries	00		7074	70000																0000	
Number	13 0		7074	70000				0000	000	0000		0000	0000	000-	-0-0	-0-0	0-0	.00-	0000		00
Number	13 0		7074	70000					000	0000		0000	0000	000-	.0-0-	-0-0	0000	.00-	0000	0000	00
Number	13 0		7074	70000					000	0000		0000	0000	0000		0000		000	0000	00000	00
	10 2 1 0 0		7074		00	000			000	0000		0000	0000	0000		0000		000	0000		00

10-	22.50	23.50	23.7	222	288	222	n n n	88888	23.25	3222	2222	2222	2222 2222	1258 1888 1888	222	2888	RRR	2888	222	82.
Time Fished	12 K						828	87.5 87.5 87.5 87.5 87.5 87.5 87.5 87.5	6.50 8.75 8.00 8.00 8.00 8.00 8.00 8.00 8.00 8.0	3255	5888	0 0 0 0 7 25 7 25	728	18 8	888	2888	22.5	188 188 188 188 188 188 188 188 188 188	882	0.00
Mortugual	14.00	16.25	16.25	1626	5 th 1	16.75	55 55 55 55 55 55 55 55 55 55 55 55 55	25 to	12.00 16.75 16.75 16.75	8 9 9 9 9	2 2 2 2 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	15.25 15.25 15.25 15.25	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	17.00 16.75 25.25	25 25 35 35 35 35 35 35 35 35 35 35 35 35 35	25 5 4 25 8 5 25 8 5	17.00	1675	2 5 5 5 5 5 5 5 5 5 5 5	555 555 555 555
L.S. Flathway H.B. Flathway	ZZ	22	ZZ	222	222	ZZ					ZZZZ									
L.S. Flathway True (VB)		22	zz	zzz	ZZZ	zz	ZZZI	ZZZ	zzz	ZZZ	ZZZZ	zzz	zzzz	ZZZ	ZZZZ	zzz	222	ZZZZ	ZZZ	2>>
Screw Trace																97.90.90				
2 ≥	000	00	000	200	000	000	0000	0000	2000	0000	0000	1000	0000	0.00	0000	1005				
Mortall	000																			
Ad Clips Injuries Mortally											0000									
Clips	000		000	200	000	000	000	0000	000	0000	0000	000	0000	000	0000	000	0000	000	0000	000
A B	100000						NOTE:								-				-	
Captured Ad		-	00+	-00	00	-00		00+0	000	0000	0000	000	0000	000	0000	000	0000	1000	0000	00
Ad Clips Injuries Mortality Captured	000	00	2000	000	000	000	000	0000		0000	0000	0000	2000	000	0000	000	0000	000	0000	000
Captured Ad Cilps Injuries Mortality Captured	000	000	2000	000	00	000		0000		0000	0000	0000	2000	0000		0000	0000	000	0000	
Captured Ad Cilps Injuries Mortality Captured		000	2000		00	000		0000		0000	0000	0000	2000	0000		0000	0000	000	0000	
Captured Ad Cilps Injuries Mortality Captured		000000000000000000000000000000000000000	,,,,,	000	000	000					0000	0000		0000		0000		000		
Injuries Mortality Captured Ad Cilps Injuries Mortality Captured Captured		000000000000000000000000000000000000000	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	000	000			0000	0000		0000	0000		0000		0000	0000			

Page 4 of 5

	randTotal	ips Injuries Mortality		00																							0	0			00	野田	18
Vumber Number Number Number Mumber Mortality of 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	ota		9 0	00	0	0	0.0	9.0	0.0	0	0	0 (0	0	0.6	0	00	00	0	00	0	0	0 0		0	0	0	0	0.0	0 0	0		
mbar Number Number Rumber reality O																																	
reality Captured A control of the co	unber	ortality o	0 0	00	0	0	00	00	0	0	0	00	0	0 (00	00	00	0	0 (00	0	01	0 0	0 0	0	0	0	00	0 0				
Number Number Number Number Number	mber	k	00	00	0	0	00																										
Number Number Polytides Mortality 0 0 0 0 0 0 0 0 0	Number	injunes	000	2270				0	0	0	0	00	. 0	0 0	0 0	00	00	0	0 0	20		0.0	0 0	0	0	0	0	0 0	0 0		00		e or end time.
Aumbor A	Number Number	Ad Cilps Injures		00	0	0 0	00		0	0 0	0	000		00	00	0	00	0	00		0 0	00	000	0	0	0 0	0	000	000	000	10	* ***	e or end time.
A Para co	Number Number Number	Capacine Actings injuries	00	00	0	0 (000	0000	0 0	0 0 0	0	000	10	000	000	00	00	0 0	0 0	20	0 0 0	0.0	000	0 0	0 0 0	0 0	0	000	30	000	00	1000	e or end time.
F # 5 # 5 # 5 # 5 # 5 # 5 # 5 # 5 # 5 #	Number Number Number Number	morranty Captured Ad cips injuries	00	00	0	0 (000	0000	0 0	0 0 0	0	000	00	000	000	00	00	0 0	0 0	000	0 0 0	00	000	0 0	0 0 0	0 0	0	000	200		000	* 540 1000	e or end time.
	Number Number Number Number	morrany Captured Ad Cips munes	00	00	0	0 (000	0000	0 0 0	0 0 0 0	0 0	000	00000	000	000	00000	00	0 0	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	000	0 0 0	00	000	0 0	0 0 0	0 0	0	000		000	000	* 540 1000	e or end time.
Notes:	Number Number Number Number Number Number	An Capa more more to the capacity of the capac	00	00	0	0 (000	0000	0 0 0	0 0 0 0	0 0	000	00000	000	000	0000	000000000000000000000000000000000000000	0 0 0		000	0 0 0 0 0	0 0 0 0		0 0 0 0	0 0 0 0 0 0	0 0 0					000	* erg con+ hrs 81 MC1	// Trapping effort cannot be computed due to minating received start false or and time. 2 No affarmont transmit the to habitate scheduler demand court product with sort of and

2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
Number N	Diama Diama	2000 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Number N	Nocturnal	46.00
Number N	A Plathousy The (YM)	
Number N	Trap (YAN)	
Control Municipa	Server Trape	-
Control Municipa		
The formation of Municipal	CWT CWT	600000000000000000000000000000000000000
Number Namber Namber Hamber Captured Granted Manipus Plantes COVT Captured	0000	000000000000000000000000000000000000000
Number Namber Namber Hamber Captured Granted Manipus Plantes COVT Captured	E COOO	
Captured Marinder Number Number Captured Captured Marinder Phylinis CAYT Captured Marinder Phylini	0000	
Author Mancher Harrison Municher Harrison Copyred Montally Palaries Copyred Palaries Copyred Montally Palaries Copyred P	Captured Captured	
Number Number Number Captured Metality Injuries CVT 115 114 115	Number Number Number Captured Montality Injuries CNT	000000000000000000000000000000000000000
Number Nu	er Number Number By Injuries CWT	
Author	S T	
	2 S	000000000000000000000000000000000000000

Page 2 of 5

100 Oct	8888	17.5	8.2.2	222	226	2000	222	1222	iana iana	ann.		224	2222	122	NE S	1221	in an	222	HAR!	8888	24.5
L.S. Plathway, M.E. Plathway, Time Fighed on Trap (YM) Trap (YM) Nocturnal Diamed	8888	7.00	9 9 9 9	089	7.00	8888	888	8 5 5 5	352	528	5555	322	2 2 2 2	322	888	22.63	338	222	855	8888	7.50
Noctumal I	2442	17.80	22 t t 25 25 25	222	24.00	17.00	17.00	0.71	1650	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	1 2 2 2 2 2 2 2 2	2 2 2 2 2 2 2 2	2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	144	282	1225	222	16.73 16.23 25.25	# # # # # 8 # #	1111 8888	17.00
Trap (YM) N	2222	zz	ZZZ	ZZI	ZZZ	2222	ZZZ	Z Z Z Z	ZZZ	ZZZ	ZZZZ	ZZZ	ZZZI	22	2222	222	222	ZZZ	ZZZ	ZZZZ	z
Trap (VM) T	20000	zz	zzz	zzz	zzz	Z Z Z Z	(ZZZ)	z z z z	ZZZ	zzz	zzzz	zzz	z z z :	zz	2222	222	222	zzz	XXX:	zzzz	z
E of La	-	100	N N N	C4 C4 C	400	N 14 14 1	00 00 00 0	M M M C	4000	~~~	инин	n n n	NNNI	400	unnı	4 (4 (4 ((1) (1) (1)	NNN	444	4 C4 C4 C4	7
- 2				Т		T												i			
Grand Total CWT	0000	00	606	000		0000	0000	0000	0000	000	000	000	0000	000	0000	000	0000	000	0000	0000	0
_	0000	00	000	000	000	0000	0000	0000	0000	0000	0000	000					000	000	0000	0000	0
ত .	0000	00	000	000	000			0000	000	0000		000	000		0000		000	000	-000	0000	0
_																					
		N.S.	V 00 00 00 00 00 00 00 00 00 00 00 00 00											10000			Mark I	-	2221	100-	1000
Captured				201															847		
Mortally Injuries CV/T	0000	001		000						0000				00		000	000				
Number Number Number Number Captured Montalty hybries CVVT	0000	00		000		•••	••••			0000	,000	>>>>	••••	00		.000	000	no-	- N-0 C	0000	0
Number Nu	0000	00:		000			••••			0000	,000	>>>>	••••	00	,,,,,	.000	000	no+	- 490		0
Number Number Number Number Captured Montalty hybries CVVT		001		000			0000			0000		0000		00			0000	000	- 490		0

Total Grand Total	00000	0 + 0 0	000	000	000	000	000	00	000	000	000	000	000	00	000	000	00		0 =	00	0-	00	ा च		N.	1 40 E	40
Grand	-0000	0000	000		000	001	000	00	300	000		0.00		0.0	0.00					7	0.0						
Grand Total Grand Total	Mortally																			7.5	0.0	-					N D
-	- 0 0 5 -	0 K	N 0 0	0 10 0	000	000	- 0	0-1	800	888	888	00-	6-	00	- 64.4	n y A	- Pari	28	≥G	25.55	X 3	8 2	210	25	83	88	ā Ņ
g.	3																										
																			2010								
ls	Ī												0	000	000	200	000	000	N.CH	- 10	00	0 9	21 E	00 10	100	28	000
Number	5																						10000	OS 10		- 14	
Number Number	00000	0000	000		000	000	000	000	000	000		000											10000	o 10		- 14	* P :
umber Number Number	00000	0000	000		000								00	000	000		000	001	00	00	00	00	0		00	00	
Veriber Number		0000	.000				000	000		000		000	00	000	000	000		001	00	00	00	00	-0	00	00	00	0110
Number Number Number Number		0000					000	000		000		000	00	000	000	000		001	00	00	00	00	-0	00	00	00	000
Number Number Number Number		0000					000	000		000		000	00	000	000	000	000) O (000 00	00	00	00	28 1	000	000	7.8	000
Number Number Number Number		0000					000	000		000		000	00	000	000	000	000) O (000 00	00	00	00	28 1	000	000	7.8	000
Andrew Number Number Number Number Number Number Number		0000					00-	000	,000	000		000	00	00:) 0 0 0	,00) O (000 00	00	00	00	28 1	000	000	7.8	000
Theory of the Control of Mander Namber Namber Daylor of Mander Namber Na		0000	.000					000	,,,,	000	,00	000	00	00:) 0 0 0	,00) O (000 00	00	00	00	28 1	000	000	7.8	000
Number		0000	.000					000	,,,,,	000	,00		00	000) 0 0 0	,00	38; 	000 000 000 000 000 000 000 000 000 00	1 0 47 0 0	0 0 0 0 0 0	2 2 93 17 0 0	3 2 540 28 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2 20 220 9 0 1	22 74 00 00 00 00 00 00 00 00 00 00 00 00 00	3 11 674 28 14 0 0	2 4 248 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Number Number Number Number		0000	.000					000	,,,,,	000			00	000) 0 0 0	,00	28: 28:	000 000 000 000 000 000 000 000 000 00	00	0 0 0 0 0 0	2 2 93 17 0 0	3 2 540 28 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2 20 220 9 0 1	22 74 00 00 00 00 00 00 00 00 00 00 00 00 00	3 11 674 28 14 0 0	000

Page 4 of 5

122	HH	Z Z	230	24.2	18.5	20.5	22.5	23.7	202	22.7	222	225	71.8	27.2	21	22.5	100	23.0	23.5	187	30.7	22.50	21	16	23.7	28.2	22.2	7	200	23.7	21.5	12	24.7	182	133	200										
222	7.90	200	2,00	M.S.	8.50	6,75	7.8	27	2,2	6.75	88	88	6.75	9.00	2,75	2,5	18	6.50	250	3 4	7.50	625	1 P	88	2,00	200	81	g y	8.75	123	6.75	8.75	10.50	3.00	20 8	3 5	1	*	4	•		-			-	
100	16.25	16.50	16.00	17,00	12.00	16.75	15.50	16.50	16.00	16.00	200	16.50	16.75	18,25	15.00	15.50	16.50	16.50	1625	16.75	22.23	16.25	4 4	18.50	16.75	17,00	14.25	18.00	15.50	14.50	18.75	18.50	14.25	15.25	16.50	46.36	15.50	4	×	T :	t 1	ı s	×			4 4
	zz	zz	2.2	22	2	22	2	Z)	zz	z	2 2	Z 2	z	Z	z	Z 2	z	Z	22	z	z	2	2 2	2	z	z	z	2 2	Z	Z	Z	ZZ	X	z	22	2	>	>	>	>- 3	->	>	>- 3	- >	>- >	->
777	zz	zz	zz	22	z	22	2	22	z	z	z	zz	z	z	z	zz	z	z	2 2	z	z	z	Z 2	2	z	z	2:	2 2	z	z	z	zz	z	z	22	>	. 3-	>	>	> >	- >	>	>>	- >-	>>	- >
9					7.50	-				-				-							+	-			_	-				-	_		_					0	0	00	0 0	0	00	0 0	00	0 0
																																										Ī		Ī		
200	718	232	368	106	290	22	177	25	113	19	3 1	88	43	23.5	7.4	120	17	OR S	3:	12	35	27	Q e		-	9	28	1.5	2	100000	37	đ t	11	w	8 0	63	g	104	3	2 5	77	40	49	29.5	17	11
	C4 FF	0 5	00	**	n			C4 C	9.40	0	N 4	•	PK.	0.0	0.7			000	V 6	N	स	ra .	-	0	0	0.				0	0.1	40	-	0.0	0 0		n	n	n.	* 6	1 193	0		1-	00	
																														200																
000	1 0	O 41	ω -	41	•	0.0	* #5		4	0	= "	10	-	0 -		4.54	0	0.	-0	0	0		0	0	0	0	00	To Street St.	0	0		00	0	00	5 0	0	0	6	0	- 4	0	+	N E			0
	38	34.0	96	241	18. 18.	7.8	3	8 4	05	<u> </u>	8 9	17.5	8	83	2 %	123	5	= 2	Ç	건	8	97 1	10	7	-	= 7	9 5	18	14		31	12	11	Φ'0	14	2	68	124	95	3 6	E	Ŧ	5 5	8	28	14
							Ē																														*		***							
					Ī	Ī			ı	Ī					Ī	Î			Ī				Ī				Ī	Ī	Ī	Ī					Ī	Ī			Ī	-11			Ī			
non	1C ea	9	13 25	4	=	27	1	00	30	7	107	7	0.	•	-	0	0	- 0	9	3	F9.3	* 5	0	0	0	~ *	n a		0	0	2.5	200	-		0	12	Installed.	7.	* **	- 1	53	1	nn	10	~ *	-
	00	0 - 0	00	F4 ==	0	- (1	0	00		0 -	7.5		0	0.0	0 0		0		0	9	0 0	00	00	0	0	0 0	0 0	0	0	0		0	0	0 0	00	0	freezy	0 1		- 0	-	n		0	00	0
000	- 01	9 10 1	00	00	-	00	0	00	N	0.			00	9 +	- 0		0	00	0		0	- 5	0	0	0	00	9 0	0	0	0	- 0	00	0	00	0	0	6	0 0	0 0	0	0	0 (0 0	0	0 -	. 0
non	g: 10 1	0.10.1	v en	94	N.	- 40	7	0.0	*	C4 =	e 10		90	200	**		0			9	24	n c	. 0	0	0	0 1	0.0	. 00	0	0		. 01		- 0			- Явтюче						2 10	-	~ 15	-
				43.41							-	-14				-			_																		8	N.			2					
20 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	3 2 2	3 3 3	355	88	582	8 23	170	8 ~	Z.	28	8 7	28	28	3.5	17	9	1	, E	-	12	21	12	a	*		3.5	2 27	7	*	-:	::	2	9	n a	17	37	8	8 5	2 %	3 %	200	25	# F	7.	무지	18
000	N + 1	2 2 4	9 49	N *	n	00	*	٧ 0	+	7	- 04	0	N	9 0	-	0	-	04.00	0	e4	re r	N +	-	0	0 0	00			-	0 1		. 0	- 0	00	0		10		-	2 64	14	0 1	2 (4	-	00	-
	0.00	o (% (o =	- 1-	m	00	n.	- 0	es :	0 1		n		0.0	2 (4	-	0	0 +	. 0	0	0 0	0 0	0	0	0 (0 00	-	0	0 (0	0 0	00	. 0	0	0	n «	> +		0		۷.0	0	- 0	0
000	00000																																													
000		Jane 1			-								2012	20		Jps		4	1155	40		510		1		100	2722	77-2-		608	202					22	-					100	4155			22
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	881	199	359	227	294	2 22	5	0 00	78	76	2 4	8	# 8	2.5	10	4	47	2 2	-	4	A 8	3 =	on on	*	- 1	7 8	R S	15	es	- :	9 0	9	0	n a	17	42	8	2 :	67	101	19	# :	\$ 12	z	- F	16
SCHOOL STREET ST	5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	25 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	28 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	25 1 100 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	25 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	100 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	25	25	2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	108	150	150	100	1988 1989 1989 1989 1989 1989 1989 1989	150	100 100	100	100 100	100 100	100 100	10 10 10 10 10 10 10 10	100 100	100 100	100 100	100 100	100 100		200				1					100 100	100 100	100 100	100 100	100 100		### 19 10 10 10 10 10 10 10	10 10 10 10 10 10 10 10	### ### ### ### ### ### ### ### ### ##

CMI	のくとのないとしているとものとなるなどはいないのはない。	8536
Total Paris	007000707000000000000000000000000000000	130
Michigan P	0000+04-0-0040-00+0-00-0-	135
Complete Com	5¥54858445550000++5××00×4×+	304
- Control of the last of the l	og-8;****noooonoo-onono	823

| S of | Life | Part |

A No trapping due to performance of physical triusy tests at WICO.
--

Age 0 Fall Chinook Salmon YOY NOCTURNAL TOTALS

Woodbridge Dam

		mber Captur	ed	Number Mortality			No.	mber Injurie			lumber CWT			Time Flahed	
	LS.	H.S.		L.S.	H.S.		L.S.	H.S.	I SOUTH	L.S.	H.S.	AND THE REAL PROPERTY.	LS.	H.S.	
Date 06/20	Fishway	Flahway	Total	Fishway	Flshway	Total	Fishway	Fishway	Total	Fishway	Fishway	Total	Fishway	Fishway	Total
06/21	37		37	0		0									
06/22	67		67	0		ő	3		1			0			
06/23	12	84	96	0	3	3	0		3		1000	61	22.00		22.0
06/24	11	37	48	0	0	ő	0	3	3	1	70	80	18.25		18.2
06/25	7	80	87	1	0	9		1		10	30	40	16,25	16.50	32.7
06/26	32	69	101	2	2	- 1	0	3	3		80	86	16.50	16.75	33.2
06/27	8	43	51	ő	0	ō	0	2	2		67	97	17.25	16,50	33.7
06/28	8	26	34		0	0	0	2	2		43	51	18.50	17.00	35.5
06/29	5	43	48	0		1		0	0	570	26	33	17.00	17.50	34.5
06/30	9	24	33	0	2	2		2	3		41	46	17,00	17.25	34.2
07/01	5				0	0	1	1	2		24	33	17,00	17.75	34.7
07/02		19	24	0	0	0	0	1	1	5	19	24	16.50	17.00	33.50
07/02	- 5	5	11	0	1	1	0	0	0	4 (100)	4	10	17,50	18.50	36.00
	14	7	21	0	0	0	0	0	0		7	21	16.50	16.75	33.26
07/04	14	2	16	0	0	0	1	0	1	14	2	16	18.00	18.25	36.25
07/05	20	11	31	0	0	0	1	0	1	20	11	31	17.00	17.25	34.25
07/06	8	5	13	0	0	0	.0	0	0	8	5	13	17.50	17.50	35.00
07/07	11	3	14	0	0	0	0	0	0	11	3	14	17.50	17.25	34.75
07/08	10	8	18	0	0	0	1	0	1	10	8	18	16.00	16.50	32,50
07/09	4	28	32	0	0	0	0	0	0		23	27	14.75	15.25	30.00
07/10	- 11	39	50	0	1	1	0	0	0		33	44	14.50	14.25	28.75
07/11	16	22	38	0.	0	0	0	0	0		22	38	15.75	16.25	32.00
07/12	12	2	14	0	0	0	0	1	1	12	2	14	16.75	17.25	
07/13	3	14	17	0	1	11	0	0	0		13	16	16,45	16.50	34,00
07/14	4	13	17	0	0	0	0	1	1	1 4	12	16	17.50	17.25	32.95
07/15	1	13	14	0	1	1	0	0	0	7	12	13	16.25	16,75	34.75
07/16	3	13	16	0	0	0	0	0	ō		13	16	16.75		33.00
07/17	3	2	5	0	0	0	0	0	ō	3	2	5		17.00	33.75
07/18	0	5	5	0	4	1	0	0	0	0	- 5		17.25	17.25	34.50
07/19	3	5	a	0	0	0	0	0	0		5	8	16.75	16.25	33.00
07/20	4	- 1	5	0	1	1	0	o	0	1	0	0.75	12.25	18.50	30.75
07/21	4	1	5	0	0	0	0	0	0	2		4	15.00	14.75	29.75
07/22	1	0	1	0	0	0	0	0	0	6	0	3	16.50	17.00	33,50
07/23	2	3	5	0	31	4	0	ő	0	0	0	0	16.00	17.00	33,00
07/24	0	7	7	0	0	0	0	ő	0	0	7	0	24,50	16.75	41.25
07/25	0	7	7	0	ő	0	0	0	0	0	7	7	16,00	16.50	32,50
07/26		3	4	0	1	1	0	0	0	0		7	17.75	18.25	36.00
07/27	4	2	3	0	ò	0	0	0		0	2	2	16.25	16.75	33.00
07/28	0	Ž.	4	0	,	1	77.0		0	1	2	3	16.25	17.00	33.25
07/29	2	ō	2	0	0	20.75	0	0	0	0	3	3	16.50	16.25	32.75
07/30	-	3	4	0		0	0	0	0	2	0	2	16.75	16.75	33.50
07/31	0	2	7.1	0	0	1	1	0	1	1	3	- 4	16.25	16,25	32.50
4//31	v		,	0	1	1	0	0	0	0	0	0	16.25	17.00	33.25
ALS	360	654	1014	4	17	21	10	17	27	304	606	910	875,20	641.00	1316.20

Notes: Low-stage fishway began operation on 6/25/94; high-stage fishway began operation on 6/23/94.

Appendix 2 (continued). June - July 1994 Downstream Migrant Fishway Traps

	No	mber Captur	ed	Min	mber Mortal	tv	A.C.	mber injurie			Total Control		_	-	
	L.S.	H.S.	944	L.S.	H.S.	-y	LS.	H.S.	19		umber CWT			Time Fished	
rte	Fishway	Flahway	Total	Flahway	Fishway	Total	Flshway		Total	LS. Fishway	H.S. Fishway	Total	LS.	H.S.	-
06/20		-	17.75				- Commey	rissimal	1 Octal	Pinteray	risaway	10139	Fishway	Fishway	Total
06/21	11		111	.0		0	0		0	11		11	7.25		
08/22			0			0			0			0	1.25		7.2
06/23	18	10	28	0	0	0	0	0	0	18	6	24	7.00		0.0
06/24	10	4	14	0	0	0	2	0	2	10	4	14	7.00	6.50	13.5
06/25	6	11	17	0	0	0	ō	4	- 7	6	11		7.75	7.25	15,0
06/26	3	8	11	0	0	0	0	0				17	6.50	5.75	12.2
06/27	9	12	21	0	o o	o o	0			3	8	- 11	7.00	7.00	14.0
6/28	5	2	7	0	0	0	2	8.1	1	8	12	20	5.50	7.00	12.5
06/29	1	2	3	0	ő	0	2	1	3	5	2	7	7.50	7.25	14.7
6/30	2	6	8	0			- 3	0	31	1	2	3	7.00	6.25	13.2
7/01	3	2	5	0	0	0	- 3	0	1	2	. 6	7	7.25	6.50	13,7
7/02	3	3	7		0	0	0	0	0	3	2	5	7.75	7.75	15,5
7/03	3			0	0	0	0	0	0	4	3	7	6.25	5.00	11.2
	3	2	6	0	1	1	0	0	0	3	1	4	7.25	7.50	14.7
07/04		0	1	0	0	0	0	0	0	. 1	0	1	5.75	5.50	11.2
7/05	10	7	17	0	0	0	0	0	0	10	7	17	7.50	7.25	14.75
7/06	0	0	0	0	0	0	0	0	0	0	0	0	5.25	5.25	10.50
7/07	8	2	10	0	0	0	2	.0	2	8	2	10	8.00	8.25	16.25
7/08	1	0	- 1	0	0	0	0	0	0	1	0	1	7.00	6.25	13.25
7/09	5	17	22	.0	0	0	0	0	0	5	17	22	10.00	10.00	20.00
7/10	10	8	18	0	0	0	0	0	0	10	1	11	9.50	8.75	18.25
7/11	. 4	10	5	0	0	0	0	0	0	4	1	5	7.75	7.50	15.25
7/12	4	7	11	0	2	2	0	0	0	4	5	9	7.25	7.50	14.75
7/13	0	4	4	.0	0	0	0	0	0	0	4	4	7.00	7.25	14.25
7/14	2	5	71	0	0	0	0	0	0	2		7	7.50	7.00	14.50
7/15	1	0	11	0	0	0	0	0	0	1	0	1	7.25	7.25	14.50
7/16	0	1	1	0	0	0	0	0	0	0	4	41	7.50	6.75	14.25
7/17	0	- 1	1	0	0	0	0	0	0	0	4	- 28	7.25	7.25	
7/18	2	2	4	0	1	1	0	1	1	2	- 4	3	11,25	10.75	14.50
7/19	0	0	0	0	0	0	0	o	0	ō	0	0	11.50		22.00
7/20	0	0	0	0		0	0	0	0	0	0	0	5.25	11.25 5.50	22.75
7/21	2	0	2	0	0	0	o o	Ö	ő	0	0	0			10.75
7/22		0	01	0	0	0	0	0	ő	o o	0	0	8.00	7.25	15.25
7/23	1	4	5	0	0	0	o.	0	0	0	2	2		6.50	6.60
7/24	0	0	0	0	0	0	o o	0	o.	0	ő	ő	7.75 6.00	7.75	15.50
7/25	0	0	0	0	ő	0	0	0	0	0	0	0		5.50	11,50
7/26	0	1	1	0	ő	0	0	0	0	0	1	1	8.00	8.00	16,00
7/27	1	24	2	0	o	0	0				73.5	7.0	7.00	7.50	14.50
7/28	ò	3	3	0	ŏ	0	0	0	1	0	0	0	7.50	6.25	13.75
7/29	0	0	0	0	0	0		0	0	0	3	3	7.25	7.25	14,50
7/30	0	3	3	0			0		0	0	0	0	7.50	7.75	15.25
7/31	0	0	0	0	0	0	0	0	0	0	3	3	7.75	7.00	14.75
1101	U:	0	0	0	.0	0	0	0	0	0	0	0	7.50	7.50	15.00
s	127	129	256	0	4	4	8	5	13	ERR	232	232	290,75	281.25	572.00

Notes: Low-stage fishway began operation on 6/21/64; high-stage fishway began operation on 5/23/64,
// Unable to tend fish bypess outfall trap in the low-stage fishway due to excessive spill in spill bay \$1.

Appendix 2 (continued). June - July 1994 Downstream Migrant Fishway Traps
YOY DAILY TOTALS

	Grand Total	Grand Total	Grand Total	Grand Total	Total Timed
Date	Captured	Mortality	Injuries	CWT	Fished
06/20	48	0	THE PARTY OF THE P	127022-127022	THE RESERVE OF THE PARTY OF THE
06/21 06/22	46 67	0	1	11	7.25
06/23	124	0	3	61	22.00
06/24	62	0		104	31.75
06/25	104	1	3	54 103	47.75
06/26	112	4	2	103	45.50 47.75
06/27	72	0	3	71	48.00
06/28	41	1	4 2 3 3	40	49.25
06/29	51	2	4	49	47.50
06/30	41	0	3	40	48.50
07/01	29	0	THE RESERVE OF THE PARTY OF THE	29	49.00
07/02	18	1	0	17	47.25
07/03	26	1	0	25	48.00
07/04 07/05	17	0	1	17	47.50
07/05	48 13	0 0	1	48	49.00
07/07	24	0	0 2	13	45.50
07/08	19	o o	1	24 19	51.00 45.75
07/09	54	0	o o	49	50.00
07/10	68	1	0	55	47.00
07/11	43	0	0	43	47.25
07/12	25	2	1	23	48.75
07/13	21	1	0	20	47.20
07/14	24	0	1	23	49.25
07/15	15	1	0	14	47,50
07/16	17	0	0	17	48.00
07/17 07/18	6 9	0	0	6	49.00
07/19	8	2 0	1 0	7 8	55.00
07/20	5	1	ő		53.50 40.50
07/21	7	ó	ő	4	48.75
07/22	1	ō	0	Ö	39,50
07/23	10	1	0	2	56.75
07/24	7	0	0	2 7	44.00
07/25	7	0	0	7	52.00
07/26	5	1	0	3	47.50
07/27	5 7	0	1	3	47.00
07/28		1	0	6 2 7	47.25
07/29	2 7	0	0	2	48.75
07/30 07/31	1	0	1 0	7	47.25
07/31		"	U	0	48.25
TOTALS	1270	25	40	1142	1888.20

Grand Total L.S. Fishway	Grand Total H.S. Fishway
48 67 30 21 13 35 17 13 6 11 8 10 17 15 30 8 19 11 9 21 20 16 3 6 2 3 3 2 3 4 6 1 3 0 0 1 0 0 1 0 0 1 0 0 1 0 0 1 0 0 0 0	94 41 91 77 55 28 9 2 18 5 5 8 45 47 23 9 18 13 14 3 7 5 1 1 0 7 7 7 7 4 3 7 0 6 1 1 1 0 1 0 1 1 0 1 0 1 1 1 1 0 1
487	783

Notes:

Low-stage fishway began operation on 6/21/94; high-stage fishway began operation on 6/23/94.

Appendix 3. Estimated Daily Abundance of Downstream Migrant Salmon - Jan-July 1994 Woodbridge Dam - Mokelumne River, CA

Note:	Differences	in	totals may	be	attributable	to	rounding	
-------	-------------	----	------------	----	--------------	----	----------	--

	YOY#	YOY#	TRAPEFF	TRAPEFF	EST#YOY	EST#YOY	EST#YOY
DATE	DAY	NIGHT	DAY	NIGHT	DAY	NIGHT	TOTAL
01/01	0	0					1,000
01/02	0	0					
01/03	0	0					
01/04	0	0					
01/05	0	0					
01/06	0	0					
01/07	0	0					
01/08	0	0					
01/09	0	0					
01/10	0	0					
01/11	0	0					
01/12	0	0					
01/13	0	0					
01/14	0	0					
01/15	0	Ö	0.179	0.278	0	0	
01/16	0	0	0.179	0.278	0	0	
01/17	0	0	0.179	0.278	0	0	
01/18	ő	0	0.179	0.278	0	0	
01/19	0	o	0.179	0.278	0	0	
01/20	0	0	0.179	0.278	0		
01/21	O	0	0.179	0.278		0	
01/22	0	0	0.179		0	0	-
01/23	0	0		0.278	0	0	
01/24	0		0.179	0.278	0	0	
01/24	0	0	0.179	0.278	0	0	
01/26	0	0	0.179	0.278	0	0	
01/27	0	0	0.179	0.278	0	0	
		0	0.179	0.278	0	0	
01/28	0	0	0.179	0.278	0	0	
01/29	0	0	0.179	0.278	0	0	
01/30	0	1	0.179	0.278	0	4	
01/31	4	0	0.179	0.278	22	0	2
02/01	0	2	0.179	0.278	0	7	
02/02	0	0	0.179	0.278	0	0	
02/03	0	0	0.179	0.278	0		
02/04	0	4	0.179	0.278	0	14	1-
02/05	0	0	0.179	0.278	0	0	1
02/06	0	0	0.179	0.278	0	0	(
02/07	0	0	0.179	0.278	0	0	(
02/08	1	1	0.179	0.278	6	4	9

Appendix 3. Estimated Daily Abundance of Downstream Migrant Salmon - Jan-July 1994 Woodbridge Dam - Mokelumne River, CA

Note: Differences in totals may be attributable to rounding

02/09 02/10 02/11 02/12	0 4 2	NIGHT 1	DAY 0.179	TRAPEFF	EST#YOY DAY	EST#YOY NIGHT	EST#YOY TOTAL
02/10 02/11 02/12	4		0.179	0.0-0			
02/11 02/12		0	100000000000000000000000000000000000000	0.278	0	4	4
02/12	2		0.179	0.278	22	0	22
		3	0.179	0.278	11	11	22
00140	3	10	0.179	0.278	17	36	53
02/13	0	5	0.179	0.278	0	18	18
02/14	1	16	0.179	0.278	6	58	63
02/15	1	13	0.179	0.278	6	47	52
02/16	2 5 2	6	0.179	0.278	11	22	33
02/17	5	1	0.179	0.278	28	4	32
02/18	2	1	0.179	0.278	11	4	15
02/19	0	0	0.179	0.278	0	0	0
02/20	0	3	0.179	0.278	0	11	11
02/21	0	1	0.179	0.278	0	4	4
02/22	0	0	0.179	0.278	0	ó	0
02/23	2	3	0.179	0.278	11	11	22
02/24	0	7	0.179	0.278	0	25	25
02/25	1	1	0.179	0.278	6	4	9
02/26	0	0	0.179	0.278	0	ō	0
02/27	0	3	0.179	0.278	0	11	11
02/28	0	1	0.179	0.278	O	4	4
03/01	2	1	0.179	0.278	11	4	15
03/02	0	2	0.179	0.278	0	7	7
03/03	0	1	0.179	0.278	0	4	4
03/04	0	1	0.179	0.278	Ö	4	4
03/05	0	2	0.179	0.278	0	7	7
03/06	0	0	0.179	0.278	0	Ó	Ó
03/07	0	0	0.179	0.278	ő	Ö	0
03/08	0	2	0.179	0.278	Ö	7	7
03/09	0	0	0.141	0.043	0	o	Ó
03/10	0	0	0.141	0.043		Ö	0
03/11	0	0	0.141	0.043	0	Ö	0
03/12	0	0	0.141	0.043	0	0	0
03/13	0	0	0.141	0.043	0	o	0
03/14	0	0	0.088	0.027	0	0	0
03/15	0	0	0.088	0.027	0	0	0
03/16	0	0	0.088	0.027	0	0	0
03/17	1	0	0.088	0.027	11	0	11
03/18	ó	0	0.088	0.027	0	0	0
03/19	0	1	0.088	0.027	0	37	37

Appendix 3. Estimated Daily Abundance of Downstream Migrant Salmon - Jan-July 1994 Woodbridge Dam - Mokelumne River, CA

Note: Differences in totals may be attributable to rounding

	YOY#	YOY#	TRAPEFF	TRAPEFF	EST#YOY	EST#YOY	EST#YOY
DATE	DAY	NIGHT	DAY	NIGHT	DAY	NIGHT	TOTAL
03/20	0	0	0.088	0.027	0	0	0
03/21	0	0	0.088	0.027	0	0	0
03/22	0	0	0.088	0.027	0	0	0
03/23	0	0	0.088	0.027	0	0	0
03/24	0	0	0.163	0.295	0	0	0
03/25	0	0	0.163	0.295	0	0	0
03/26	0	0	0.163	0.295	0	0	0
03/27	0	0	0.163	0.295	0	0	0
03/28	0	0	0.163	0.295	0	0	0
03/29	0	0	0.163	0.295	0	0	0
03/30	1	0	0.163	0.295	6	0	6
03/31	0	0	0.063	0.236	0	0	Ö
04/01	1	0	0.063	0.236	16	Ō	16
04/02	0	0	0.063	0.236	0	0	0
04/03	0	0	0.063	0.236	Ō	ő	ő
04/04	0	1	0.063	0.236	Ö	4	4
04/05	0	2	0.063	0.236	O	8	8
04/06	0	5	0.063	0.236	O	21	21
04/07	0	14	0.063	0.236	0	59	59
04/08	0	7	0.063	0.236	0	30	30
04/09	0	7	0.063	0.236	0	30	30
04/10	0	43	0.063	0.236	0	182	182
04/11	0	68	0.063	0.236	0	288	288
04/12	2	15	0.063	0.236	32	64	95
04/13	3	49	0.063	0.236	48	208	255
04/14	1	53	0.063	0.236	16	225	240
04/15	3	48	0.063	0.236	48	203	251
04/16	0	24	0.063	0.236	0	102	102
04/17	0	63	0.063	0.236	ō	267	267
04/18	0	95	0.063	0.236	0	403	403
04/19	17	97	0.063	0.271	270	358	628
04/20	26	546	0.063	0.271	413	2015	2427
04/21	11	199	0.063	0.271	175	734	909
04/22	9	224	0.063	0.271	143	827	969
04/23	6	127	0.063	0.271	95	469	564
04/24	5	77	0.063	0.271	79	284	363
04/25	O	144	0.063	0.271	0	531	531
04/26	14	341	0.063	0.271	222	1258	
04/27	26	478					1481
04/2/	20	4/0	0.063	0.271	413	1764	2177

Appendix 3. Estimated Daily Abundance of Downstream Migrant Salmon - Jan-July 1994 Woodbridge Dam - Mokelumne River, CA

Note:	Differences	In	totals may	be	attributable to rounding	
-------	-------------	----	------------	----	--------------------------	--

LWANES	YOY#	YOY#	TRAPEFF	TRAPEFF	EST#YOY	EST#YOY	EST#YOY
DATE	DAY	NIGHT	DAY	NIGHT	DAY	NIGHT	TOTAL
04/28	5	219	0.071	0.234	70	936	1006
04/29	10	249	0.071	0.234	141	1064	1205
04/30	10	68	0.071	0.234	141	291	431
05/01	3	103	0.071	0.234	42	440	482
05/02	0	108	0.071	0.234	0	462	462
05/03	5	197	0.071	0.234	70	842	912
05/04	26	132	0.071	0.234	366	564	930
05/05	8	222	0.071	0.234	113	949	1061
05/06	5	77	0.071	0.234	70	329	399
05/07	45	199	0.071	0.234	634	850	1484
05/08	12	491	0.071	0.234	169	2098	2267
05/09	13	359	0.071	0.234	183	1534	1717
05/10	50	67	0.071	0.234	704	286	991
05/11	14	227	0.071	0.234	197	970	1167
05/12	2	294	0.071	0.234	28	1256	1285
05/13	27	50	0.071	0.234	380	214	594
05/14	16	22	0.071	0.234	225	94	319
05/15	7	173	0.071	0.234	99	739	838
05/16	0	86	0.071	0.234	0	368	368
05/17	0	8	0.004	0.010	O	800	800
05/18	41	78	0.004	0.010	10250	7800	18050
05/19	2	17	0.004	0.010	500	1700	2200
05/20	114	76	0.004	0.010	28500	7600	36100
05/21	45	42	0.004	0.010	11250	4200	15450
05/22	21	91	0.004	0.010	5250	9100	14350
05/23	6	44	0.004	0.010	1500	4400	5900
05/24	9	20	0.004	0.010	2250	2000	4250
05/25	2	74	0.004	0.010	500	7400	7900
05/26	7	19	0.024	0.226	292	84	376
05/27	11	41	0.024	0.226	458	181	640
05/28	0	17	0.024	0.226	0	75	75
05/29	1	10	0.024	0.226	42	44	
05/30	ó	21	0.024	0.226	0	93	86 93
05/31	10	1	0.024	0.226	417	4	421
06/01		12	0.024				
06/02	/3			0.226	0	53	53
06/03	2 5	34	0.024	0.226	83	150	234
	10	23	0.024	0.226	208	102	310
06/04	10	15	0.024	0.226	417	66	483
06/05	0	9	0.024	0.226	0	40	40

Appendix 3. Estimated Daily Abundance of Downstream Migrant Salmon - Jan-July 1994 Woodbridge Dam - Mokelumne River, CA

Note:	Differences in	totals may	be attributable to rounding
-------	----------------	------------	-----------------------------

inute. Deletelices (il picals	YOY#	YOY#	TRAPEFF	TRAPEFF	EST#YOY	EST#YOY	EST#YOY
DATE	DAY	NIGHT	DAY	NIGHT	DAY	NIGHT	TOTAL
06/06	0	4	0.024	0.226	0	18	18
06/07	0	1	0.024	0.226	0	4	4
06/08	8	3	0.024	0.226	333	13	347
06/09	5	20	0.024	0.226	208	88	297
06/10	12	29	0.024	0.226	500	128	628
06/11	3	15	0.024	0.226	125	66	191
06/12	0	2	0.024	0.226	0	9	9
06/13	0	1	0.024	0.226	0	4	4
06/14	21	19	0.024	0.226	875	84	959
06/15	10	12	0.024	0.226	417	53	470
06/16	3	10	0.024	0.226	125	44	169
06/17	1	10	0.024	0.226	42	44	86
06/18	1	5	0.024	0.226	42	22	64
06/19	0	9	0.024	0.226	0	40	40
06/20	0	17	0.024	0.226	0	75	75
06/21	12	42	1.000	1.000	12	42	54
06/22		69	1.000	1.000	0	69	69
06/23	28	96	1.000	1.000	28	96	124
06/24	14	48	1.000	1.000	14	48	62
06/25	17	87	1.000	1.000	17	87	104
06/26	11	101	1.000	1.000	11	101	112
06/27	21	51	1.000	1.000	21	51	72
06/28	7	34	1.000	1.000	7	34	41
06/29	3	48	1.000	1.000	3	48	51
06/30	8	33	1.000	1.000		33	41
07/01	5	24	1.000	1.000	8 5 7	24	29
07/02	7	11	1.000	1.000	7	11	18
07/03	5	21	1.000	1.000	5	21	26
07/04	1	16	1.000	1.000	1	16	17
07/05	17	31	1.000	1.000	17	31	48
07/06	0	13	1.000	1.000	0	13	13
07/07	10	14	1.000	1.000	10	14	24
07/08	1	18	1.000	1.000	1	18	19
07/09	22	32	1.000	1.000	22	32	54
07/10	18	50	1.000	1.000	18	50	68
07/11	5	38	1.000	1.000	5	38	43
07/12	11	14	1.000	1.000	11	14	25
07/13	4	17	1.000	1.000	4	17	21
07/14	7	17	1.000	1.000	7	17	24
200 (March	100.0		1.000	1.000		3.6	24

Appendix 3. Estimated Daily Abundance of Downstream Migrant Salmon - Jan-July 1994 Woodbridge Dam - Mokelumne River, CA

Note:	Differences	in totals	may be	attributable	to rounding
-------	-------------	-----------	--------	--------------	-------------

DATE	YOY# DAY	YOY# NIGHT	TRAPEFF DAY	TRAPEFF NIGHT	EST#YOY DAY	EST#YOY NIGHT	EST#YOY TOTAL
07/15	1	14	1.000	1.000	1	14	15
07/16	1	16	1.000	1.000	1	16	17
07/17	1	5	1.000	1.000	1	5	6
07/18	4	5	1.000	1.000	À	5	
07/19	0	8	1.000	1.000	Ô	8	9
07/20	0	5	1.000	1.000	0	5	
07/21	2	5	1.000	1.000	2	5	5
07/22	0	1	1.000	1.000	0	1	1
07/23	5	5	1.000	1.000	5	-	10
07/24	0	7	1.000	1.000	0	5	10
07/25	0	7	1.000	1.000	0	7	1
07/26	1	4	1.000	1.000	1	,	-
07/27	2	3	1.000	1.000	2	4	5
07/28	3	4	1.000	1.000	2	3	5
07/29	0	2	1.000	1.000	0	4	/
07/30	3	4	1.000	1.000	0	2	2
07/31	Ö	1	1.000	1.000	3	1	7

TOTAL: 1021 7993 70627 72597 143224

0 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	VGTL (mm)	AVGFL (mm)	AVGW (g)	r AVGK	STOTL	STOFL	STOW	STDK	MAXTL	MINTL (men)	MAXVVT (g)	MINWT (9)
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4										VIII)	107	(5)
444444444444444444444444444444444444444												
444444444444444444444444444444444444444												
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4												
4 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5												
4444444444444												
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4												
	32	30	0.3	8.09E-04	0.7	0.7	0.07					
	100		0.0	0.000-04	9.7	0.7	0.07	2.83E-04	32	31	0.3	0.2
- 3	31	30	0.1	4.22E-04		0.0						
		30	0.1	4.22E-U4	1.0	0.6	0.06	1.50E-04	32	30	0.2	0.1
	20											
	38	37	0.2	3.95E-04	0.7	0.7	0.00	0.00E+00	38	.37	0.2	0.2
	11	39		CONTRACTOR	0.0	0,0			41	41		757700
	10	38	0.3	4.44E-04	2.5	2.5	0.06	4.27E-05	42	36	0.3	0.2
	35	34	0.3	6.64E-04	3.4	2.9	0.05	2.53E-04	39	30	0.3	0.2
	39	38	0.3	5,35E-04	4,3	3.7	0.27	1.35E-04	53	31	1.2	0.2
	37	36	0.2	3.83E-04	0.6	0.6	0.00	1.89E-05	38	37	0.2	0.2
	39	37	0.3	4,43E-04	4.4	3.9	0.25	1.54E-04	54	34	1.2	0.1
31		37	0.3	4.68E-04	5.6	5.4	0.21	9.77E-05	51	28	0.8	0.1
3		38	0.3	5.52E-04	2.2	1.7	0.13	1.47E-04	43	36	0.6	0.2
38		37	0.3	4,54E-04	0.9	0.9	0.04	7.57E-05	40	36	0.4	0.2
38	18	37	0.3	6.03E-04	4.2	4.2	0.00	1.87E-04	41	35	0.4	0.3
100	00	17400									AMERICA II	11.000
3		30	0.1	3,40E-04	2.4	2.4	0.00	8.56E-05	32	29	0.1	0.1
38	18	37	0.3	5.47E-04	0.0	0.0	0.00	0.00E+00	38	38	0.3	0.3
							1707	SEASONE SEE	1970	1255	100000	0.0
38	8	37	0.3	5.38E-04	1.1	1.6	0.00	4.79E-05	39	37	0.3	0.3
40	0	39	0.4	5,13E-04	7.0	6.9	0.33	1.18E-04	54	35	1.0	0.2
34	4	32	0.3	8.68E-04	7.1	7.1	0.00	5.12E-04	39	29	0.3	0.2
			900	100000000000000000000000000000000000000	6.4	250	2,0000	2.2000000000000000000000000000000000000	1000	4400	0.0	0.0
32	2	31	0.2	4.85E-04	2.1	2.1	0.07	1.22E-04	34	31	0.2	0.4
38		37	0.2	3.64E-04	0.0	0.0	0.00	0.00E+00	38		0.2	0.1
37		36	0.3	5.26E-04	2.1	1.4	0.00	9.71E-05		38	0.2	0.2
37		36	0.3	5.95E-04	1.4	1.4	0.00	6.81E-05	39	36	0.3	0.2
36		35	0.2	4.29E-04	0.0	0.0			38	36	0.3	0.3
35		34	0.2	4.66E-04	0.0		0.00	0.00E+00	36	36	0.2	0.2
38		36				0.0	0.00	0.00E+00	35	35	0.2	0.2
26	nut.	- 50	0.3	4.67E-04	2.1	2.1	0.01	5.45E-05	39	36	0.3	0.2
								CAL BUTTON				
40	U	39	0.3	4.71E-04	1.4	0.7	0.00	4.98E-05	41	39	0.3	0.3
			0.5	6.75E-04	0.0	0.0	0.00	0.00E+00	42	42	0.5	0.5

DATE	AVGTL	AMESES	ALICHAIT	411000			A Control of the	inook saimo			Woodbrid	Ac Datti	
03/18/94	(mm)	AVGFL (mm)	AVGWT	AVGK	STDTL	STDFL	STDWT	STDK	MAXTL (mm)	MINTL (mm)	MAXWT	MINWT	
3/18/94	39	37	0.2	3.37E-04	0.0	0.0	0.00	0.000-00		VI.AV	(g)	(g)	-
3/20/94			1000	0.016-01	0.0	0.0	0.00	0.00E+00	39	39	0.2	0.2	
3/21/94													
3/22/94													
13/23/94													
03/24/94													
03/25/94													
03/26/94													
03/28/94													
03/29/94													
03/30/94	36	34	0.2	4.00E-04	0.0	102120	1621223						
33/31/94		-54	0.2	4.29E-04	0.0	0.0	0.00	0.00E+00	36	36	0.2	0.2	
04/01/94	40	38	0.3	4.69E-04	0.0	0.0	0.00	0.000 00	1000				
04/02/94			3,753.75	11001	0.0	0.0	0.00	0.00E+00	40	40	0.3	0.3	
14/03/94													
)4/04/94	76	68	3.4	7.75E-04	0.0	0.0	0.00	0.00E+00	70	200	277	1205	1
34/05/94	96	87	6.8	7.79E-04	3.5	4.2	0.85	1.09E-05	76 98	76	3.4	3.4	
14/06/94	88	80	5.4	7.85E-04	8.9	8.4	1.60	3.22E-05		93	7.4	6.2	83
14/07/94	92	85	6.2	7.71E-04	9.3	8.2	1.74	6.18E-05	95 108	76	6.9	3,5	
14/08/94	89	80	5.3	7.57E-04	6.0	5.3	1.09	7.39E-05	95	72	9.0	3.3	1
4/09/94	91	83	5.8	7.61E-04	6.5	5,9	1,40	3.74E-05	97	80 82	6.5	3.7	13
4/10/94	91	83	6.1	7.97E-04	5.4	5.1	0.97	5.57E-05	103	81	7.4	3.9	- 2
14/11/94	92	83	6.0	7.66E-04	5.8	5.2	1.20	4.06E-05	106	83	8.2 8.9	4.8	3
4/12/94	88	81	4.8	7.81E-04	7.8	7.5	1,15	5.08E-05	105	72	6.1	4.3	3
4/13/94	91	83	5.8	7.60E-04	8.2	7.5	1.59	5.15E-05	108	72	9.8	2.7	1
4/14/94	91	83	5.9	7.72E-04	7.3	6.1	1.29	5.09E-05	112	80	8.8	3,4 4,1	3
4/15/94	91	83	5.8	7.52E-04	8.5	7.3	1,56	4.04E-05	111	72	10.9	2.8	3
4/16/94	91	83	5.7	7.47E-04	6.5	5.4	1.19	3.56E-05	102	78	8.5	3.8	2
4/17/94	92	84	6.4	8.04E-04	7.9	7.1	2.00	5.94E-05	113	79	12.4	3.8	3
4/18/94	91	83	5.9	7.67E-04	6.1	5,4	1,29	5.69E-05	106	83	9.0	4.1	3
4/19/94 4/20/94	91	83	5.9	7,64E-04	7.8	6.8	1,29	5.84E-05	105	63	8.2	2.3	46
4/21/94	90	82	5.9	7.94E-04	7.8	6.9	1.58	5.33E-05	112	70	11.6	2.8	55
4/22/94	91 94	83 85	5.9	7.59E-04	6.6	6.0	1.25	4.26E-05	106	77	8.6	3.6	4
4/23/94	92	84	6.2	7.45E-04	7.5	6.8	1.53	4.14E-05	107	74	0.0	2.9	38
4/24/94	91	83	6.0	7.61E-04 8.00E-04	6.6	6.3	1.38	5.27E-05	107	76	9.4	3.2	36
4/25/94	91	83	6.0	7.93E-04	7.4	6.7	1.39	5.43E-05	107	71	9.2	3.0	35
4/26/94	91	83	6.0	7.78E-04	6.8	6.2	1,28	6.03E-05	100	77	7.6	3.2	30
4/27/94	92	84	6.2	7.69E-04	7.0	5.7	1.30	8.47E-05	111	79	10.9	3.7	4
1/28/94	90	82	6.0	7.95E-04	8.5	6.3	1.41	5.41E-05	107	76	9.4	3.5	55
4/29/94	91	83	5.8	7.61E-04	5.3	7.7 4.6	1.58	5.96E-05	106	72	9.4	2.7	35
4/30/94	91	83	5.9	7.59E-04	7.4	6.6	1.12	3.93E-05	103	82	8.8	4.0	40
5/01/94	92	84	6.1	7.65E-04	4.2	3.8	0.96	5.75E-05 4.32E-05	108	79	10.2	3.5	40
5/02/94	93	85	6.4	7.85E-04	6.3	5.7	1.40	7.92E-05	100	85	8.0	4.6	33
5/03/94	90	81	5.6	7.61E-04	6.1	5.7	1.34	4.28E-05	110	81 82	10,7	3.8	30
5/04/94	93	84	6.3	7,77E-04	6.8	6.2	1.36	4.39E-05	109	79	10,3	3.9	35
5/05/94	95	87	6.8	7.81E-04	6.2	5.6	1.48	5.54E-05	106	78	9.8	3.8	55
106/94	93	84	6.2	7.69E-04	7.5	6.7	1.53	4.73E-05	106	75		3.6	36
107/94	94	86	6.7	7.83E-04	7.9	7.2	1.78	4.37E-05	115	75	9.1 12.0	3.1	35
1/08/94	96	87	7.0	7.84E-04	7.4	6.5	1.68	5.58E-05	115	81	11.3	3.2	60
5/09/94	96	87	6.9	7.74E-04	6.6	6.3	1.57	5.03E-05	108	79	10.4	4.1 3.8	42
110/94	94	85	6.4	7.72E-04	6.9	6.3	1.59	4.56E-05	123	79	13.6	3.4	43 60
11/94							1840	Section of the Control of the Contro	5775	1876	10.0		0
112/94	Care.	100	112131	Anna Curation									0
1/13/94	93	85	6.4	7.78E-04	5.6	5.1	1,15	3.81E-05	107	76	9.3	3.5	57
V14/94	93	84	6.4	8.00E-04	6.5	6.0	1.44	4.32E-05	109	82	10.4	4.3	38
V15/94	92	84	6.4	8.02E-04	6.3	5.9	1.51	4.52E-05	107	81	11.1	4.2	37
V16/94	96	87	7.4	8.22E-04	6.9	5.8	1.55	6.72E-05	112	86	10.1	4.9	30
17/94	90	82	5.9	7.91E-04	6.9	6.4	1.27	4.04E-05	97	80	7.1	4.2	7
V18/94	96	88	7.3	8.07E-04	7.1	6.3	1.76	4.35E-05	112	80	11.9	3.9	60
/19/94	93	84	6.6	8.03E-04	6.2	5,6	1.40	7,35E-05	105	77	9.2	3,7	19
/20/94	96	87	7.1	7.98E-04	7.2	6.5	1,70	4.11E-05	110	80	10.8	3.8	53
/21/94	94	85		7.90E-04	9,3	8.5	1.95	5.12E-05	117	68	12.6	2.6	60
/22/94	95	86	7.1	8.00E-04	8.3	7,6	1.98	5.56E-05	114	78	11.7	3.6	51
/23/94	98	89	7.6	8.02E-04	8.9	7,7	2.04	4,36E-05	114	81	12.1	4.5	30
/24/94	97	88	7.3	7.94E-04	7.4	6.8	1.79	4.39E-05	116	78	12.1	3.6	46
/25/94	97	88	7.4	7.96E-04	7,9	7.0	1.83	7.12E-05	115	83	12.4	4.5	60
/26/94	100	91	8.0	7.86E-04	7.2	6.8	1.62	3.68E-05	114	88	11.4	5.1	24
/27/94	99	90	7.7	7.89E-04	7.1	6.5	1.85	4.61E-05	118	88	13.8	5.4	40
/28/94	94	86	6,8	8.02E-04	7.8	7.5	1.79	4.35E-05	114	85	11.7	4.9	17
/29/94	97	88	7.3	7.87E-04	8.8	8.2	2.28	5.50E-05	110	87	11.3	4.8	9
/30/94	100	91	8.1	8.00E-04	8.6	7.8	2.02	5.43E-05	117	86	11.8	4.8	20
/31/94	102	92	8.2	7.68E-04 7.89E-04	6.3	5.2	1.60	4.72E-05	110	91	10.3	5.6	11
V01/94	102	92	8.5		6.9	6.3	1.78	4.99E-05	109				

DATE	AVGTL	AVGFL	AVGWT	AVGK	STDTL	STOFL	STDWT	STDK	MAXTL	MINTL	MAYAN	11110000	-
A	(min)	(mm)	(g)				CIDITI	OIUK	(mm)		MAXWT	MINWT	N
06/02/94	96	88	7.4	8.05E-04	11.5	10.2	2.61	4,90E-05	122	(mm)	(3)	(g)	
06/03/94	101	92	8.2	7.72E-04	7.2	6.5	1.97			75	14.6	3.6	32
06/04/94	102	93	8.8	8.07E-04	8.6	8.0		4.41E-05	115	87	12.7	4.8	27
06/05/94	97	89	7,9	8.52E-04	6.4		2.40	6.51E-05	121	88	16.2	5.2	25
06/06/94	109	99	9.8	7.67E-04		5.5	1.38	6.51E-05	108	90	9.9	6.5	9
06/07/94	90	81			7.1	6.6	1.23	8.38E-05	115	101	11.0	8.9	4
06/08/94			6.2	8.50E-04	0.0	0.0	0.00	0.00E+00	90	90	6.2	6.2	
	105	96	9.7	8.19E-04	9.5	9.2	3.06	5.01E-05	122	94	16.4		1
06/09/94	103	95	9.1	8.05E-04	9.1	8.5	2.46	7.27E-05	124	87		6.5	10
06/10/94	102	93	8.7	7.94E-04	9.9	8.9	2.52				15.6	5.9	25
06/11/94	106	96	9.7	8.16E-04	7.8	7.5		5.25E-05	120	85	15.3	5.0	37
06/12/94	108	99	11.0	8.61E-04			2,16	6.61E-05	116	90	13.0	5.0	17
06/13/94	94	86			12.7	11.3	3,39	3.51E-05	117	99	13.4	8.6	2
06/14/94	106	96	6,6	7.95E-04	0.0	0.0	0.00	0.00E+00	94	94	6.6	6.6	1
06/15/94			9.5	7.93E-04	7.7	7.2	2.21	5.37E-05	125	94	15.8	6.1	37
	106	96	9.6	7.87E-04	10.0	9.6	3,48	7.44E-05	130	93	18.9		31
06/16/94	104	94	9.3	8.19E-04	10.2	9.4	3.06	3.75E-05	124	91		5.4	22
06/17/94	100	91	7.9	7.86E-04	5.7	5.0	1.47	6.31E-05	107		15.8	5.8	13
06/18/94	109	100	10.8	8.03E-04	14.5	12.7	5.02			89	10.4	5.7	11
06/19/94	102	92	8.7	8.03E-04	12.2			4.15E-05	130	90	19.0	5.6	6
06/20/94	103	94				11,1	3.51	8.64E-05	127	86	15.8	5.4	9
06/21/94	108		9.3	8.15E-04	13.0	11.7	3.78	3.04E-05	130	81	18.8	4.1	17
		98	10.8	8.31E-04	8.9	7.7	2.88	5.27E-05	127	89	17.8	5.4	
06/22/94	112	102	12.0	8.55E-04	8.5	7.9	2.64	8.74E-05	127	91	17.2		47
06/23/94	110	101	11.1	8.04E-04	10.7	9.8	3.30	5.51E-05	140	74		6.3	32
06/24/94	111	101	11.6	8.33E-04	9.1	8.3	3.10				22.7	3.9	70
06/25/94	106	97	9.9	8.18E-04	7.7	7.1		5.63E-05	139	87	23.5	4.8	55
06/26/94	107	98	10.2	8.22E-04			2.42	6.25E-05	128	82	18.3	4.3	53
6/27/94	109	100	10.8		8.6	7.9	2.53	6.00E-05	133	87	19.5	5.6	71
06/28/94	108			8,12E-04	9.6	8.8	3.14	5.42E-05	133	87	19.6	5.0	59
		98	10.1	7.95E-04	8.1	7.4	2.30	5.02E-05	122	89	15.0	5.2	
6/29/94	108	99	10.5	8.10E-04	8.4	7.5	2.61	7.96E-05	124	93	15.3		40
06/30/94	110	100	10.9	8.07E-04	10.4	9.5	3.28	4.13E-05	135			6.5	38
7/01/94	109	99	10.5	7.90E-04	6.9	6.1	2.15			95	20.9	6.6	41
7/02/94	108	96	10.5	7.89E-04	12.2			4.29E-05	122	98	15.7	7.3	29
7/03/94	112	102				10.9	4.13	4.08E-05	140	90	22.4	5.7	17
7/04/94	110	100	11.6	7.93E-04	13.2	12.1	4.37	4.05E-05	149	85	24.1	5.3	25
7/05/94			10.9	8.00E-04	11.2	10.4	3.87	6.16E-05	138	93	22.0	6.5	17
	109	99	11.3	7.84E-04	8.4	8.5	2.81	4.86E-05	133	92	20.0	6.9	
7/06/94	109	99	10.5	7.99E-04	9.1	8.3	2.61	2.53E-05	124	97	V-C7407 (PG)		48
7/07/94	111	101	11.3	8.03E-04	8.6	8.2	2.86	6.50E-05	135		15.1	6.9	13
7/08/94	115	105	12.8	8.04E-04	14.6	13.7	5.61			95	20.0	6.9	24
7/09/94	111	101	11.2	8.06E-04	11.1			5.78E-05	144	96	25.3	6.5	19
7/10/94	112	102		CONTRACTOR OF THE PARTY OF THE		11.4	2.95	6.81E-05	135	92	18.0	7.0	29
7/11/94			11.3	7.81E-04	10.4	9.6	3.79	1.26E-04	142	100	23.2	2.0	32
	115	104	12.4	8.04E-04	9.3	8.5	3.31	5.76E-05	141	95	23.6	6.6	43
7/12/94	117	107	13.8	8.17E-04	11.2	10.4	3.92	4.22E-05	136	99	20.5	7.5	
7/13/94	116	106	13.0	8.02E-04	14.3	12.5	4.82	4.54E-05	141	85			23
7/14/94	117	107	13.1	7.91E-04	11.9	11.3	5.21	6.22E-05			23.7	5.2	20
7/15/94	111	101	11.1	7.87E-04	9.9	8.9			143	100	27.0	7.4	24
7/16/94	121	109	14.0	7.80E-04			2.84	3.45E-05	127	94	16.2	6.2	14
7/17/94	108	99			9.8	9.3	3.36	4.42E-05	138	103	19.4	8.4	17
			10,6	8.11E-04	12.3	10.9	3.92	3.26E-05	122	93	15.9	6.4	6
7/18/94	108	99	10.1	7.43E-04	12.0	13.7	5.67	1.00E-04	127	91	18.3	5.2	7
7/19/94	120	113			10.2	7.6		0.0000000000000000000000000000000000000	133	100	196.90		
7/20/94	110	99	10.4	7.71E-04	11.6	11.1	3.78	5.58E-05	119	97	444	6.4	13
7/21/94	112	101	11.1	7.67E-04	14.2	12.1	4.25	6.16E-05	133		14.1	6.7	4
122/94	137	124	20.3	7.89E-04	0.0	0.0				95	17.1	6.8	7
/23/94	127	115	18.5				0.00	0.00E+00	137	137	20.3	20.3	.1
1/24/94				8.60E-04	21.9	18.4	10.11	4.80E-05	142	111	25.6	11.3	2
	116	106	13.0	7.87E-04	16.3	15.7	6.20	5.91E-05	141	101	23.3	8.2	7
7/25/94	119	108	13.3	7.85E-04	9.8	8.5	3.44	6.61E-05	127	103	17.2	8.1	
/26/94	117	106	13.3	7.81E-04	17.2	15.2	5.36	4.88E-05	133				7
7/27/94	125	114	16.6	8.49E-04	10.2	9.0				93	19.6	5.7	4
7/28/94	117	106					4.08	7.59E-05	140	118	23.0	12.0	5
			12.6	7.74E-04	14.7	13.1	4.28	3.68E-05	133	94	18.1	6.4	6
					42.4	25	2 44	D DOM DE	100	72.22.21			
7/29/94	128	117	16.9	8.10E-04	6.4	3.5	3.11	2.86E-05	132	123	19.1	14.7	2
	128 120	109	14.0	7.74E-04	14.3	12.5	5.55	6.72E-05	136	123 96	19.1	14.7 6.4	7

DATE	AVGTL	AMORI			33 to 3uly	1994	Yearling Ci	ilnook Sal	mon			Woodbridg	
10/0	(mm)	AVGFL (mm)	AVGWT (p)	AVGK	STOTL	STDFL	STOWT	STOK	MAXTL	MINTL	MAXWT		- 0.0
10/02	2			12.5					(mm)	(mm)	(a)	MINV/T (g)	N
10/03	3												
10/04													
10/05	,												
10/07													
10/08													
10/09													
10/10													
10/11													
10/12 10/13													
10/14													
10/15													
10/16													
10/17													
10/19													
10/20													
10/21	143	133			26.9	25.0							
10/22	148	138			27.0	25.8 26.4			198	80			31
10/23	153	143			23.1	22.9			219	102			58
10/25	162 162	151 151			19,9	19.5			195 205	109 110			36
10/26	145	135			18.8	18.3			197	112			54
10/27	152	141			19.2	0.0			145	145			72
10/28	156	145			21.9	18.4 20.8			197	120			57
10/29	143	131			17.9	16.4			195 175	122			36
10/31	144 152	133 139			21.6	21.1			190	95 111			40
11/01	153	141			20.1	19.1			192	124			55 23
11/02					29.6	28.0			215	112			21
11/03	161	149			17.6	16.7			190				
11/04	161 162	149 149			23.8	22.8			196	111 98			33
11/06	159	146			19.4	18.4			196	120			61
11/07	153	141			21.0	19.7 17.5			199	109			69 71
11/08	149	137			18.3	17.8			189	105			54
11/09	152 162	139			18.4	17.4			191 185	111			63
11/11	174	149 160			17.5	16,7			193	112			79
11/12	164	152			15.0 18.9	14.1			205	125			73 61
11/13	163	150			16.5	15,9 16,0			197	118			68
11/14	154	140			18.4	18.0			199 200	123			56
1/15	152 148	140 136			15.9	15.4			187	119 120			64
1/17	160	148			20.6	19.5			195	77			34 60
1/18	163	150			18.1	17.3 22.5			193	113			47
1/19	161	148			26.0	24.8			205 195	100			63
1/20	158 157	146 144			18.6	18.2			185	105 109			63 40 47 35 43
1/22	145	133			20.9	19.8			191	104			35
1/23	173	159			19.3 15.5	18.2 14.9			189	106			43
1/24	163	150			21.9	20.6			197	124			61
1/25	149	139			18.1	16.0			195 185	121 113			35
1/26 1/27	154 158	142			20.4	19.2			189	98			35 26 62
1/28	160	145 148			17.2	16.7			193	115			61
1/29	171	158			18.4 16.7	17.5 15.8			200	107			59
1/30	159	147			21.1	20.3			215 199	123 101			91
2/01	169	155			19.7	18.9			211	117			84
2/02 2/03	167	153			19.0	17,9			202	128			59 34 32 43 25 15
2/04	169	155 155			15.0 21.0	15.1			205	132			32
2/05	169	154			20,5	19.9 20.0			218	109			43
2/06	161	148			24.3	22.4			215 208	120 123			25
2/07	160	147			26.6	24.6			203	125			9
2/08	163	151			22.5	21.5			197	110			37
2/09 2/10	171	158 156			16.2	15.7			215	131			52
2/11	163	149			19.7 22.9	19.2 21.8			196	120			36
2/12	170	156			17.5	17.1			197 200	110			26
2/13	168	154			18.0	16.9			186	135			37 52 36 26 37 8
	164	150			13.2	12.6 17.0			184	141			14
2/14 2/15	166	152			17.9				196	119			

DATE	AVGTL (mm)	AVGFL (mm)	AVG	1110	STOTL	STDFL	STD	WT ST	W +111			Woodbrid	ge Dan
12/16	161	146	(g	7			0,0	WT STE	77.74	1000	MAXW	MINWT	N
12/17	165	152			18.3	16.8			(mm)	(mm)	(g)	(g)	
12/18	160	146			13.9	13.2			193	122			37
12/19	155	142			23.5	21.9			188	128			26
12/20	175				24.5	21.5			190	110			40
12/21	164	160			17.1	15.8			180	123			18
12/22		151			20.8	20.9			205	151			В
	179	165			17.8	17.1			198	116			15
12/23	157	144			19.7				201	136			16
12/24	159	144				19.0			187	112			15
12/25	171	156			19.8	18.2			187	127			20
12/26	181	166			15,3	14.6			197	136			19
12/27	179	164			19.5	17.9			205				14
12/28	186	169			21.3	20.4			208	143			11
12/29	168	154			16.0	14.9			209	123			30 25 36
12/30	172	157			19.2	18.0			197	152			25
12/31	168	155			20.8	19.9			203	122			36
01/01	170	156			19.8	19.0			215	131			17
01/02	172				17.0	14.8			181	115			29
01/03	167	158			20.0	19.7			201	152			3
01/04		152			25.3	23.7			201	131			16
	178	164			21.3	20.2			205	121			18
01/05	172	157			19.4	18.3			205	123			15
01/06	170	155			22.7	21.5			207	123			60
01/07	181	166			10.3	9.5			205	125			20
01/08	178	164			16.6				198	163			15
01/09	169	155			26.6	15.6			197	135			16
01/10	178	163			22.5	24.8			207	119			27
01/11	170	155			23.6	21.2			207	123			17
01/12	179	164			23.8	21.9			207	123			26
01/13	186	171				22.0			210	122			42
01/14	183	167			19.5	16.9			214	137			92
01/15	181	165			19.9	17.8			211	135			32
01/16	173	159			21.3	18.6			212	135			28 30
01/17	185	169			19.4	18.3			192	115			30
01/18	173				12.8	10.9			212	165			18
01/19	176	161			12.7	13.4			195	125			13
01/20	183	162			16.4	15.6			205				15
01/21		168			19.0	18.0			210	144			32
01/22	188	174			12.9	12.8			212	141			21
01/23	191	177			15.8	15.2			224	165			18
	177	163			18.5	18.2				164			20
01/24	188	172			18.4	16.6			251	146			40
01/25	180	165			19.0	17.4			217	151			45
01/26	179	164			17.1	16.3			215	119			87
01/27	188	172			15.2	13.1			211	129			69
01/28	184	168			15.9	13.5			210	157			18
01/29	182	167			15.1	13.8			213	161			21
01/30	181	167			8.7	8.8			208	157			12
01/31	166	151			18.5	16.3			192	162			15
02/01	176	161	41.6	7.44E-04	19.5	18.0	12.70	0.700.00	181	156			3
02/02	175	161	39.3	7.20E-04	15.9	15.7	12.70	3.76E-05	205	115	65.8	12.3	25
02/03	162	149	32.4	7.59E-04	13.8	13.3	10.50	1.07E-04	204	130	54.0	16.6	23
02/04	168	155	35.7	7.44E-04	9.0	9.1	4.86	8.25E-05	180	139	38.1	23.5	8
12/05	177	161	42.0	7.33E-04	17.8	16.1	4.95	3.25E-05	181	154	43.5	28.4	11
12/06	172	158	40.3	7.88E-04	20.7	18.8	12.02	5.56E-05	212	125	76.7	14,3	35
2/07	182	166	46.4	7.53E-04	18.0		11.43	9.89E-05	202	145	56.0	28.0	10
2/08	186	169	47.3	7.38E-04	19.1	16.4	13.34	4.57E-05	218	133	76.3	19.5	38
2/09	173	156	10.00	1.000	24.2	17.3	14.44	3.58E-05	217	152	72.1	24.1	21
	166	150	36.9	7.71E-04		25.0	Walter St.	-	196	117			9
	170	154	32.2		28.2	25.2	15.08	6.83E-05	197	115	58.8	13.2	9
	189	174	W6.4	6.43E-04	32.6	30,3	15.38	1.04E-04	208	144	52.5	21.5	5
	170	155			2.1	2.8			190	187	100000		
2/14	76		2.4	7 000	17.7	16.0			191	147			7
		70	3.1	7.06E-04	0.0	0.0			76	76	3.1	3.1	
	176	160	41.3	7.44E-04	15.0	13.9	10.80	7.71E-05	193	136	54.2	20.2	1
	169	154	37.0	7.51E-04	21.7	20.8	13.04	3.97E-05	192	148	51.1		6
	174	157	41.2	7.47E-04	28.1	25.5	16.26	4.11E-05	192	125		25,2	6
	182	166	44.9	7.32E-04	16.9	15.8	11.64	3.82E-05	215	130	55.8 76.5	14.9	5
	184	168	46.8	7.51E-04	9.8	9.8	7.05	5.44E-05	202	167	76,5	15.9	42
	178	161	42.0	7.40E-04	15.2	15.1	11.26	4.99E-05	192		57.5	34.3	18
2/21	165	152	36.7	7.85E-04	25.5	24.7	16.89	1.10E-05		162	53.1	32.5	5
2/22				and the same	500	1000	100	1.102-00	183	147	48.6	24.7	2
	196	181	58.6	7.75E-04	5.7	4.9	8.91	511505	200	400		1223	0
2/24		3416511	0.000000		3.400		0.01	5.11E-05	200	192	64,9	52,3	2
2/25													0
2/26	174	160	39.1	7.40E-04	3.7	2.8	5.45	E 70F 0F	4770	240	7225-27	N2-12-12-02	0
2/27	WKE	1117721	2000	1.700.07	0.7	2.0	5.12	5.72E-05	176	171	42.9	35.7	3
													0
2/28													
2/28 3/01	173	158	36.7	7.08E-04	8.5	3.5	3.96	2.77E-05	179	167	39.5	33.9	0

Appendix 5.	Size and C	Condition	Database - Oc	ctober	1993 to July 19	994

Vesting	Chinook Salmor	
) casming	CHIHOOK Saimor	ä

Woodbridge Dam

TE.	AVGTL	AVGFL	AVGWT	AVGK	STOTL	STOFL		CIIIIOOK Saii				Woodbridge
3/02	(mm)	(mm)	(g)	AVOR	SIDIL	SILIFL	STDWT	STDK	MAXTL (mm)	MINTL	MAXWT	MINWT
3/03	455	440	100						Unitro	(mm)	(g)	(9)
3/04	155	140	29.2	7.57E-04	22.6	21.2	12.66	6.94E-06	171	139	20.4	0.00
							V635	TOTAL STREET	OAEMC.	100	38,1	20.2
3/05	00000	12000	12330									
3/06	189	174	58.2	8.63E-04	16.3	14.8	13.29	2.48E-05	200	499		
3/07	137	125	19.1	7.43E-04	0.0	0.0	0.00	0.00E+00		177	67.6	48.8
3/08						(2)(2)	0.00	0.000	137	137	19.1	19.1
3/09												
V10												
V11	165	150	20.0	4.45E-04	0.0	0.0	0.00	0.00E+00	400	124400	144.000	
V12	170	153	38.6	7.87E-04	4.2	2.8	1.63		165	165	20.0	20.0
V13						2.0	1.00	9.20E-05	173	167	39.7	37.4
/14	142	131	16.0	5.59E-04	0.0	0.0	0.00	0.005.00	0.000	DOMESTIC .		
/15				0.0000000000000000000000000000000000000	0.0	0.0	0.00	0.00E+00	142	142	16.0	16.0
/16												
/17	139	126	20.9	7.78E-04	0.0	0.0	0.00	0.005.50				
/18	147	135	27.3	8.59E-04	0.0	0.0	0.00	0.00E+00	139	139	20.9	20.9
/19	175	155	36.9	6.89E-04			0.00	0.00E+00	147	147	27.3	27.3
20	167	152	34.3	7.36E-04	0.0	0.0	0.00	0.00E+00	175	175	36.9	36.9
21			44.4	7,500-04	0.0	0.0	0.00	0.00E+00	167	167	34.3	34,3
22	139	128	21.0	7 825 04	0.0	7.65	7/29030	ULHEREN AL				100,000
23	100	120	21.0	7.82E-04	0.0	0,0	0.00	0.00E+00	139	139	21.0	21.0
24												21.0
25												
26 26	107	400	22223	21002000	12450-							
	167	150	39.3	8.44E-04	0.0	0.0	0.00	0.00E+00	167	167	39.3	39.3
27								-		200	-	55.5
28												
29	2000	1922										
30	160	142	30.0	7.32E-04	0.0	0.0	0.00	0.00E+00	160	160	30.0	30.0
31	***	444	WESST	20 (200 (200 (200 (200 (200 (200 (200 (201000		3012	N. State		50.0
01	185	166	49.2	7.77E-04	0.0	0.0	0.00	0.00E+00	185	185	49.2	49.2
02									100	100	40.2	49.2
03	179	162	42.3	7.38E-04	0.0	0.0	0.00	0.00E+00	179	179	42.3	40.0
04	168	154	35.3	7.41E-04	0.0	0.0	0.00	0.00E+00	171	163	38.3	42.3
25	158	144	31.4	8.01E-04	7.8	4.9	4.38	6.00E-06	163	152		30.7
06						C. Seeder		0.002-00	100	152	34.5	28,3
37												
08	126	118	15.2	7.60E-04	0.0	0.0	0.00	0.00E+00	126	126	46.0	45.0
)9					1000		9.00	D.00E-00	120	120	15.2	15.2
10												
11												
12												
3												
4	198	178	59.2	7.63E-04	0.0	0.0	0.00	0.00E+00	198	486	60.0	
5						4.0	0.00	0.000-00	180	198	59.2	59.2
6												
7												
8												
9												
0												
1												
2												
3												
4	220	205			0.0	0.0	0.00	0.000-00	200	220		
5	151	135	28.6	8.31E-04	0.0	0.0	0.00	0.00E+00	220	220	255	02220
6			20.0		0.0	0.0	0.00	0.00E+00	151	151	28.6	28.6
7												
8	182	167	49.7	8.24E-04	0.0	0.0	0.00	0.005.00	400		Charles	2322
9		101		0.242-04	0.0	0.0	0.00	0.00E+00	182	182	49.7	49.7
0												
1												
2												
3	132	125	24.5	0.255.01	0.0	0.5						
4	102	125	21.5	9,35E-04	0.0	0.0	0.00	0.00E+00	132	132	21.5	21.5
5												
6												
7												
3												
9												
0	215	200	56.7	5.71E-04	0.0	0.0	0.00	0.00E+00	215	215	56.7	56.7
0	210			Dellenito St.	V 4 2 2 2 2 1 1 1	7027	1000000		2.70	2.00	5007	- Marie
0	100											
1	510											
1 2	*.15											
0 1 2 3	210											
	-14											

E	AVGTL (mm)	AVGFL (mm)	AVGWT	AVGK	STOTL	STDFL	STDWT	STDK	(mm)	MINTL (mm)	MAXWT (a)	MINWT (g)	
5/17	0.440	pierry	107						prod		100	197	
5/19 5/20													
5/21													
5/22 5/23													
5/24													
5/25													
5/26 5/27													
5/28													
5/29													
5/31													
6/01													
6/03													
6/04 6/05													
6/06													
6/07													
6/09													
6/10													
6/12													
6/13	168	145	37.9	7.99E-04	0.0	0.0	0.00	0.00E+00	168	168	37.9	37.9	
6/15	100	1,144									108218		
6/16 6/17													
6/18													
6/19													
6/21													
6/22													
6/24													
6/25 6/26													
6/27													
6/28													
6/30 7/01													
7/02													
7/03													
7/04 7/05													
7/06													
7/07 7/08													
7/09 7/10													
7/11													
7/12 7/13													
7/14													
7/15													
7/16													
7/18													
7/19 7/20													
7/21													
7/22 7/23	182	165	46.2	7.66E-04	0.0	0.0	0.00	0.00E+00	182	182	46.2	46.2	
7/24	11/2	17.5	0.000	ENMIRE S	2102	838	5000	MASSESS	(1987)	-	27075	237	
7/25													
7/27													
7/28													
7/30													
7/31													

E	AVG RIVERQ	CANALQ	AVG*	MAX (F) MIN	SECC AM	HIDEPTH (c	m) AVG	RAINFALL	BAROPRESS	MOONAGE	SUNDIEC	St Nice
V11 V12							1000		TO HAT PAGE	UNIVERESS.	MOUNAGE	SUNRISE	SUNSET
V13													
114	81 135								0.00		29	711	183
	178		63.8	68.9	61.8	160	170	165	0.00	29.95 29.90	0	712	183
l	178		61.4	61.8	61.0	100	100	100	0.00	29.90	1 2	713 714	182 182
	178		60.6	61.4	60.1				0.00	29.99	3	715	182
	429 831		59.7 59.2	60.5 59.9	59.1				0.00	30.08	4	716	182
	884		58.7	59.3	58.8 58.2	120	115	117.5	0.00	30.08	5	718	182
	909		59.0	59.7	58.7	125	130	127.5	0.00	30.05 30.03	6 7	719 720	182 181
	912		58.7	59.1	58.4	127.5		127.5	0.00	30.02	8	721	181
	917 750		58.7 58.8	59.3 59.3	58.2 58.4	130	130	130	0.00	29.99	9	722	181
	318		59.0	59.5	58.4	130	130 130	130 130	0.00	29.97 30.00	10	724	181
	290		58.8	59,5	58.2	130	130	130	0.00	30.01	12	725 726	181
	268 254		59.3 59.0	59.7	58.7	130	120	125	0,00	29.88	13	727	181
	248		58.9	59.5 59.5	58.6 58.2	130	130	130 125	0.00	29.82 29.95	14	729	180
	241		58.8	59.5	58.2	130		130	0.00	29,95	15 16	730 631	180 170
	545		59.1	50.7	58.6	120	0.22	120	0.00	30.01	17	632	170
	517 349		59.0 58.1	59.5 58.9	58.6 56.9	30 70	60	45 70	0.00	30,19	18	634	170
	335		57,1	58.9	55.4	60		60	0.00	30,12 30,00	19	635 638	170
	331		57.3	58.9	55.8	50	40	45	0.00	30.02	21	637	170 170
	332 334		57.1	58.8 58.6	55.6	45	45	45	0.00	29.92	22	639	165
	337		57.0 56.9	58.6	55.4 55.4	45 50	50	45 50	0.00	29.93 30.04	23	640	170
	338		56,6	58.2	55.2	50	50	50	0.00	30.12	24 25	641 642	170
	345		58.7	58.2	55.4	50	50	50	0,00	29.94	26	644	170
	373 351		57.2 57.9	58.7 59.3	55.9 56.9	30 52	40	35	1.00	29,84	27	845	170
	344		57.1	58.0	56.3	60	55 65	53.5 62.5	0.26	29.84 29.91	28	848	165
	342		56.1	57.2	55.0	55	50	52.5	0.00	30.05	1	649	165 165
	345 345		55.0	55.9	54.0	55	55	55	0.00	30.09	2	650	165
	345		54.1 54.6	55.6 56.1	52.7	65 45	60 45	62.5 45	0.00	30.12	3	851	165
	342		55.7	57.2	54.1	50	45	47.5	0.00	30,09	4 5	652 653	165 165
	340		56.1	57.4	55.0	55	55	55	0.00	30.28	8	655	185
	339 337		55.5 54.9	56.7 56.1	54.1 53.8	70 75	70 60	70 67.5	0.00	30.16	7	658	165
	338		54,6	55.8	53.4	50	45	47.5	0.00 trace	29.98 30.03	8	657 658	165 165
	337		56.0	57.4	54.5	45	50	47.5	0.00	30.21	10	700	165
	334		55.5	56.3	54,3	55	55	55	0.00	30.23	11	701	165
	337 340		53.1 52.4	54.0 53.8	51.8 51.1	100	75 80	70 90	0.00	30,17	12	702	164
	339		53.0	54.5	51.1	55	50	52.5	0.00 trace	30.21 30.11	13 14	658 659	164 164
	360		53,1	54.1	52.0	50	55	52.5	0.00	29.97	15	700	164
	393 379		53.5 54.7	54.1 55.9	53.1 53.6	50	45	47.5	0.34	29.94	16	701	164
	350		56.0	57.2	54.9	20 70	20 70	20 70	0.77	30,16 30,36	17 18	702 704	164 164
	336		55.0	55.8	54.1	80	80	80	0.00	30.35	19	705	164
	328 326		54.3	55.4	53.1	80	60	70	0.00	30.27	20	708	164
	325		54.0 54.3	54.9 55.4	53.1 52.9	70 55	60 60	65 57.5	0.00	30,18 30,04	21	707	164
	324		53.9	64.7	52.9	60	85	62.5	0.00	30.08	22 23	708 709	164 164
	323		53.2	54.5	51.8	90	70	80	0.00	30.04	24	710	164
	328 328	1.00	53.4 54.1	54,3 55,0	49.6 53.6	80 60	60	70 60	0.00	30.01 30.12	25 28	711	164
	316		55.4	56.3	54.7	80	70	75	0.01	30.12	27	711 712	164
	329		55.5	56.1	54.3	80	55	67.5	0.00	29.77	28	713	164
	316		54.3	55,0	53.2	65	55	60	0.61	30.16	29	714	164
	311 326		52.7 52.3	53.8 53.2	51.8 51.3	100 65	65 45	82.5 55	0.00	30.00 29.87	0	715	184
	312		52.8	53.6	51.8	45	55	50	0.03	30.01	1 2	716 716	164
	271		52.6	53.2	51.8	85	70	77.5	0.00	30.11	3	717	164
	254		51.4	52.2	50.4	100	100	100	0.00	30,13	4	718	164
	252 250		51.2 49.8	51.8 51.0	50.4 46.9	100	100 90	100	0.00	30.12 30.18	5	718	164
	249		48.8	49.6	48.4	85	85	85	0.00	30.23	7	719 719	164 164
	248		48.5	49.2	47.2	90	100	95	0.00	30.21	8	720	164
	248		49.0	49.2	48,5	100	100	100	0.00	30.32	9	720	164
	246 246		48.6 47.8	48.9 48.4	48.2 47.2	100	100	100	0.00	30.35 30.47	10 11	721	165
	248		47.2	47.7	45.2	100	100	100	0.00	30.21	12	721 722	165
	245		47.2	47.5	46.9	100	100	100	0.00	30.02	13	722	165
	243		47.3	48.0	46.9	80	100	90	0.05	30.15	14	722	165
	243 241		48.7	49.9 50.3	47.9 48.5	100	100	100	0.06	30.32 30.30	15	723 723	165
	241		49.1	49.7	48.0	100	100	100	0.00	30.30	17	723	165
	241		49.3	49.7	48.5	100	100	100	0.00	30.18	18	723	165
	241		49.1	49.6	48.5	100		100	0.03	30.31	19	724	165

ATE	RIVERQ	CANALQ	AVG*	TERTEMP (F			HIDEPTH (and the same	DESCRIPTION OF THE PARTY OF THE	cestemme:	CVVVVVICE C	300000
01/02	RIVERQ 241	ONNINE	49.4	MAX 50.1	MIN 45.7	AM 80	PM 90	AVG 85	RAINFALL 0.00	BAROPRESS		SUNRISE	SUNSE
01/03	239		50.2	50.8	49.7	100	80	90	0.00	30.35	20	724	16
1/04	242		50.2	50.6	49.9	80	80	80		30.24	21	724	16
1/05	241		49.6	49.9	49.4	85	100	92.5	0.02	30.16	22	725	16
1/08	238		48.4	49.2	47.5	100	90	95	0.00	30.20	23	725	16
1/07	239		47.3	48.0	46.4	100	90	95	0.00	30.29	24	725	17
1/08	241		47.1	47.7	46.2	100	100	100	0.07	30.30	25	725	17
/09	240		48.4	49.8	47.4	100	100	100		30.18	26	724	17
1/10	239		49.0	49.8	48.2	95	100	97.5	0.00	30,15	27	724	17
111	238		47.8	49.1	46.5	100	100		0.00	30.23	28	724	17
/12	185		47.8	48.4	46.9	90		100	0.00	30.28	0	724	17
1/13	159		47.7	48.2	47.0	100	100	95	0.00	30.35	1	724	17
1/14	153	- 1	47.0	47.7	48.4	100	100	100	0.00	30.27	2	724	17
1/15	151		47.1	47.5			100	100	0.00	30.13	3	723	17
1/16	150		47.5	48.4	48.5	100	100	100	0.00	30.11	4	723	17
/17	150				46.5	100	100	100	0.00	30,14	5	723	17
1/18	151		48.0	48.7	47.0	100	100	100	0.00	30.19	6	722	17
/19	149		48.2	48.9	47.0	100	100	100	0.00	30.09	7	722	17
/20	148		48.4	49.1	46.9	100	100	100	0.00	30.03	8	721	17
			48.7	49.4	47,7	100	100	100	0.00	30.13	9	721	17
1/21	148		48.9	49.6	48.0	80	80	80	0.00	30.19	10	720	17
1/23	148 174		49.3	50.1	48.5	90	100	95	0.01	30.04	11	720	17
			51.3	52.4	50.3	100	100	100	0.74	29.90	12	718	17
1/24	169		51,3	52.2	50,6	60	60	60	0.39	29.89	13	718	17
1/25	159		49,6	50.6	48.5	80	70	75	0.13	29.97	14	717	17
1/26	152		50,1	50.8	49.4	60	90	75	0.00	30.11	15	718	17
1/27	146		49.9	50.8	49.2	100	100	100	0.00	30.02	16	718	17
1/28	144		48.9	49.9	48.0	100	100	100	0.00	30,14	17	715	17
	143		48,3	49.1	47.2	100	90	95	0.00	30.33	18	714	17
1/30	144		47.6	48.4	46,9	80	100	90	0.00	30.28	19	713	17
1/31	144		47.7	48.4	46.9	100	100	100	0.00	30.28	20	713	17
10%	144		47.9	48.4	47.0	90	90	90	0.00	30.30	21	712	17
2/02	144		47.8	48.2	46.9	100	100	100	0.00	30.11	22	711	17
2/03	142		47.8	49.1	46,9	100	100	100	0.00	30.02	23	710	17
2/04	143		49.1	50,3	48,5	100	100	100	0.00	30.03	24	709	17
2/05	144		50.0	50.8	49.1	100	100	100	0.00	30.08	25	708	17
2/08	154		51.1	51.8	50.3	90	100	95	0.87	29.84	28	707	17
2/07	172		50.3	51.5	49.8	50	55	52.5	0.62	29.54	27	706	17
2/08	165		48.5	50.3	47.4	55	55	55	0.62	29.84	28	705	17
2/09	151		47.7	49.6	46.4	75	80	77.5	0.00	30.22	29	704	17
2/10	150		49.1	50.1	48.2	75	80	77.5	0.00	30.07	0	703	17
2/11	143		49.7	50.6	48.7	75	85	80	0.00	30.24	1	702	17
712	143		50.3	52.0	48.9	100	100	100	0.00	30,39	2	701	174
2/13	144		51.6	53.1	50.1	100	100	100	0.00	30.27	3	700	174
2/14	144		52.7	54.0	51.3	100	90	95	0.24	30.14		659	17
2/15	144		53.8	54.3	52.9	95	85	90	0.00	30.07	5	657	174
2/16	145		54.3	55.4	53.1	80	75	77.5	0.00	29.82	6	656	174
2/17	178		54.9	56.5	53.4	60	40	50	0.46	29.63	7	655	17
2/18	166		55.9	57.1	54.3	50	15	32.5	0.28	29.82	8	654	17
2/19	184		58.4	57.6	54.9	55	75	65	0.16	29.86	9	653	17-
2/20	175		56.6	57.6	55.2	65	60	62.5	0.38	29.99	10	651	17
2/21	169		58.2	57.2	55.0	75	75	75	0.15	30.14	11	650	17
2/22	157		58.4	57.2	55.8	65	80	72.5	0.15	30.23	12	649	17
2/23	150		55.2	58.1	54.0	75	90	82.5	trace	30.16	13	647	170
2/24	148		55.3	56.1	53.8	95	95	95	0.00	30.12	14	646	175
2/25	145		56.2	57.1	55,4	75	85	80	0.00	29.93	15	645	17
V28	145		57.0	57.6	56.1	85	85	85	0.07	30.02	16	643	17
727	148		57.1	57.8	56.3	100	90	95	0.10	30.11	17	642	17
V28	144		56.6	57.4	55.6	140	130	135	0.00	30.13	18	841	17
V01	142		56.1	57.1	55.2	95	105	100	0.00	30.17	19	639	17
V02	141	-	57.0	58.2	56.1	95	85	90	0.00	30,11	20	638	18
WD3	140		58.0	59.9	57.1	85	85	85	0.00	30.10	21	636	180
W04	139		58.1	59.5	57.4	95	80	87.5	0.00	30.10	22	635	18
3/05	143		58.0	58.4	57.8	95	95	95	0.00	29.97	23	634	180
80%	144	170	57.3	58.4	56.3	90	90	90	0,15	29.93	24	632	181
3/07	123	0	57.7	58.9	56.9	120	120	120	0.00	29.96	25	631	180
3/08	114	0	57.2	58.4	56.3	105	125	115	0.00	30.02	26	629	180
8/09	112	0	57.9	59.5	56.7	60	100	80	0.00	30.07	27	628	18
3/10	112	0	58.6	59.7	57.8	70	80	75	0.00	30.06	28	626	18
V11	106	0	58.8	59.5	58.2	95	90	92.5	0.00	30.11	0	625	18
V12	105	0	58.0	58.7	57.4	95	125	110	0.00	30.28	1		
V13	108	0	57.3	57.8	56.7	110	125	117.5	0.00	30.24		622	18
¥14	104	0	57.2	57,8	56.5	120	110				2	621	18
3/15	103	0						115	0.00	30.04	3	619	181
3/16			57.2	58.2	56.3	125	140	132.5	0,00	29.98	4	618	181
	99	0	58.5	60.3	58.9	200	190	195	0.00	30.03	5	616	18
3/17	99	0	60.5	81.8	59.3	140	180	160	0.00	29.96	6	815	181
V18	98	0	61.2	62.0	60.5	195	185	190	0.00	29.83	7	613	181
3/19	95	0	61.7	63.0	60.8	165	190	177.5	0.00	29.88	8	612	181
3/20	91	0	62.1	63.2	61.0	200	200	200	0.00	30.05	9	610	181
3/21	97	0	62.4	63.2	61.4	180	175	177.5	0.00	30.06	10	609	181
3/22	97	0	62.9	83.6	62.0	175	135	155	0.00	29.99	11	607	182
3/23	108	0	63.6	64.8	62.4	130	140	135	0.00	29.90	12	606	182
3/24 3/25	112	0	63.7	64.6	62.8	130	125	127.5	0.00	29,69	13	604	182

ATE	AVG RIVERQ	CANALQ	AVG.	TERTEMP (F	MIN	AM	HIDEPTH (c		DAINEALL	DADCOORCO	MODELLOS	en management	2000000
03/26	115	30	63.5	84.2	62.8	155	200	177.5	RAINFALL 0.00	BAROPRESS 30.03	MOONAGE 15	SUNRISE 601	SUNSET 182
03/27	116	54	61.9	63.0	61.0	190	190	190	0.00	30.08	16	600	182
33/28	105	54	61.2	61.8	60.8	150	170	160	0.00	30.12	17	558	182
3/29	103	54	60.6	62.2	59.5	160	150	155	0.00	30.15	18	557	182
3/30	112	48	60.4	61.4	59.5	175	135	155	0.00	30.20	19	555	182
V31	103	49	61.3	62.8	59.9	130	140	135	0.00	30,14	20	554	182
01	95	42	62.7	84.2	61.4	135	145	140	0.00	30.07	21	551	182
102	102	52	64.0	85.8	62.6	145	140	142.5	0.00	30.04	22	550	182
03	109	56	64.6	66.0	63.4	125	150	137.5	0.00	30.03	23	648	192
04	104	84	65.9	67.7	64.6	140	130	135	0.00	30.02	24	647	1930
05	101	95	66,0	66.7	65.2	145	140	142.5	0.00	30,02	25	645	193-
/06	108	87	66.1	67.3	64.8	150	150	150	0.00	30.04	28	644	
/07	114	85	66.4	67.9	65.2	145	170	157.5	0.00	30.04	27	642	1930
80	112	85	65.8	66.7	64.8	140	145	142.5	0.00	29.94	28	641	
9	115	82	85.6	66.2	65.2	160	160	160	0.21	29.98	29	639	193
10	114	80	64.4	65.0	63.6	160	170	165	0.00	30.06	0	638	1936
11	113	75	64.2	64.8	63.6	135	150	142.5	0.22	30.09	1	636	1940
12	115	73	63.0	63.8	61.6	175	200	187.5	0.00	30.06	2	635	1941
3	116	81	60.6	61.6	59.7	130	170	150	0.00	29.93	3	633	1942
4	115	79	58.0	59.5	57.2	140	135	137.5	0.00	29.87	4	632	1942
5	114	85	58.1	59.3	57.4	150	145	147.5	0.00	29.93	5	631	1943
8	112	87	59.2	59.9	58.7	160	145	152.5	0.00	30.02	6	629	1944
7	121	82	60.8	61.8	59.9	140	140	140	0.00	30.04	7	628	
18	129	83	61.8	62.8	61,0	125	120	122.5	0.00	30.01	8	626	1945
19	155	88	62.6	63.6	61.8	130	120	125	0.00	30.02	9	025	1947
0	162	88	63.0	63.6	82.2	120	115	117.5	0.00	29.95	10	624	1948
1	160	90	63.3	64.4	62.6	140	130	135	0.00	29,98	11	622	1949
2	155	104	63,9	64.8	63.2	150	145	147.5	0.00	29.95	12	621	1950
3	157	112	84.2	65.0	63.8	145	165	155	0.08	29.80	13	620	1951
24	173	111	64.7	65.2	64.2	130	130	130	0.18	29.88	14	619	1952
25	185	106	63.5	64.8	82.6	115	105	110	0.28	29.80	15	617	1953
28	188	90	62.5	63.4	62.2	145	145	145	0.59	29.87	16	616	1953
27	202	71	62.2	62.8	61.4	160	150	155	0.00	29.87	17	615	
28	177	100	63,5	65.2	62.2	160	145	152.5	0.20	29.99			1954
9	173	102	65.5	66.9	64.6	165	160	162.5	0.00	30.09	18	614	1955
0	179	102	67.0	68.3	66.0	150	160	155	0.00	30.08	19	612	1958
11	177	102	68.8	67.3	66.5	145	135	140	0.00	30.02	20 21	611	1957
22	180	99	66.1	67.3	65.6	155	140	147.5	0.00	30.00	22	610	1958
13	163	100	66.0	67.1	65.2	145	140	142.5	0.00	30.00	22 23	608	1959
04	154	106	64.7	65.8	63.4	150	145	147.5	0.00	29.90	24	605	2000 2001
05	153	115	62.3	63.2	61.2	150	150	150	0.00	29.84	25	604	2002
100	152	116	60.3	61.0	59.3	145	145	145	0,00	29.93	26	602	2003
7	172	106	59.4	60.3	58.7	130	130	130	0.79	30.01	27	601	2003
18	168	102	59.5	59.9	58.9	130	120	125	0.00	29.98	28	600	2004
09	159	100	59.2	60.1	58.6	110	120	115	0.00	29.97	29	559	2005
0	160	100	60.2	61.4	59.3	115	160	137.5	0.00	29.95	0	558	2006
11	158	102	61.9	63.8	60.5	110	150	130	0.00	29.94	1	557	2007
12	154	100	64.0	65.4	62.8	140	150	145	0.00	29.90	2	557	2008
3	151	99	65.4	66.9	64.2	130	145	137.5	0.00	29.85	3	558	2009
4	151	103	66.4	67.7	65.2	130	170	150	0.00	29.81	4	555	2010
15	148	104	64,9		30112	120	125	122.5	0.00	29,94	5	554	2012
6	146	102	63.0			120	120	120	0.00	29.89	6	553	2012
17	158	96	62.4			130	130	130	0.10	29,86	7	552	2013
8	167	94	61.3			140	140	140	0.05	29.94	8	551	2014
9	162	86	59.9			155	140	147.5	0.00	30.05	9	551	2015
0	177	66	59.4			125	120	122.5	0.00	30.00	10	550	2018
21	164	56	60,4			150	170	160	0.00	29.91	11	549	2017
22	151	58	61.5			160	145	152.5	0.00	29.90	12	549	2017
23	144	65	63.9			110	140	125	0.00	29.92	13	548	2018
24	134	82	65,8			180	145	162.5	0.00	29.84	14	547	2019
25	138	98	66.7				145	145	0.00	29.78	15	547	2020
28	129	107	68.9	72.7	66.5	140	185	162.5	0.00	29.81	16	548	2021
27	131	104	66.4	67.3	65.4	185	140	162.5	0.00	29.89	17	546	2021
28	128	108	66.3	67.7	65.2	170	135	152.5	0.00	29.93	18	545	2022
29	121	106	66.5	68.6	65.2	150	150	150	0.00	29.88	19	545	2023
30	126	106	67.0	68.1	66.0	150	150	150	0.00	29.76	20	544	2023
31	131	114	66.5	67.7	65.8	120	145	132.5	0.00	29.94	21	544	2024
101	137	114	65.3	66.0	84.8	145		145	0.00	29.99	22	543	2025
102	137	124	65.5	66.9	84.4	170	120	145	0.00	29,91	23	543	2026
03	132	132	65.7	66.7	64.8	135		135	0.00	29.93	24	543	2028
04	129	130	65.3	68.7	64.4	140	140	140	0.00	29.97	25	542	2027
105	126	128	65.2	66.2	64.6	160	140	150	0.00	29.94	26	542	2027
/06	126	120	65.2	66.7	64.4	155	145	150	0.00	29.99	27	542	2028
/07	120	127	64.5	65.0	64.0	120	155	137.5	0.00	30.00	28	542	2029
/08	125	128	64.5	65.2	83.8	185	125	155	0.00	29.96	29	542	2029
109	134	142	65.1	68.7	64.4	180	175	177.5	0.00	29.87	0	541	2030
10	142	152	68.4	67.7	65.6	170	130	150	0.00	29.80	1	541	
11	141	168	87.2	68.8	66.0	185	185	175	0.00	29.80	2		2030
12	133	174	67.3	69.0	66.2	150	170	160	0.00	29.80	3	541	2031
из	155	179	68.6	67.3	65.6	130	140	135	0.00			541	2031
		185	85.1	88.2	64.0	155	120	137.5	0.00	29.83	5	541 541	2031 2032
	2,355,04.3		200.1					101.0	0.00	29.80	- 51	261	2012
114	153 149	186	64.2	65.2	63.0	130	180	155	0.00	29.88	6	541	2032

DATE	AVG	WID		TERTEMP (F)	SECC	HIDEPTH (d	rn)					
	RIVERQ	CANALO	AVG*	MAX	MIN	AM	PM	AVG	RAINFALL	BAROPRESS	MOONAGE	SUNRISE	SUNSET
06/17	103	186	64.0	65.8	62.4	170	200	185	0.00	29.97	8	541	203
06/18	. 71	180	64.8	66.0	63.8	200	200	200	0.00	29.90	9	541	2033
06/19	85	173	65.9	67.9	64.8	160	150	155	0.00	29.87	10	542	2033
06/20	79	165	67.3	68.8	66.0	140	130	135	0.00	29.95	11	542	2034
08/21	73	145	67.0	68.8	88.2	180	175	177.5	0.00	29.98	12	542	2034
08/22	70	133	68.0	69.0	67.1	190		190	0.00	29.95	13		
06/23	44	132	68.5	69.8	67.3	100	210	210	0.00	29.98	14	542	2034
08/24	30	133	69.4	70.7	87.9		210	210	0.00	29.90		542	2034
06/25	29	127	70.1	71.4	68.8				0.00	29.88	15	543	2034
06/26	42	115	70.5	71.8	69.2	180	180	180	0.00		16	543	2034
08/27	52	110	71.0	71.8	69.6	100	100	100		29.90	17	543	2035
06/28	37	122	71.4	72.5					0.00	29.89	18	544	2035
06/29	29				70.3				0.00	29.92	19	544	2035
06/30		140	72.0	73.4	70.7				0.00	29.89	20	544	2035
	28	148	72.4	73.4	71.4				0.00	29.87	21	545	2035
07/01	28	147	72.0	73.9	71.4				0.00	29.85	22	545	2034
07/02	28	158	72.4	73.2	71.4				0,00	29.83	23	548	2034
07/03	28	158	723	73.2	71.2				0.00	29.79	24	546	2034
07/04	28	154	71.9	72.7	70.9				0.00	29.78	25	547	2034
07/05	31	156	71.9	73.4	70.5				0.00	29.85	26	547	2034
07/08	54	149	71.0	72.1	69.6				0.00	29.90	27	548	2034
07/07	43	134	71.0	72.1	69.8			11	0.00	29.81	28	549	2033
07/08	30	131	71.7	73.2	70.3				0.00	29.77	0	549	2033
07/09	29	140	72.4	73.9	71.2				0.00	29.82	1	550	2033
07/10	28	140	73.0	74.3	71.8				0.00	29.89	2	550	2032
07/11	28	145	73.1	74.6	71.8	180	150	165	0.00	29.89	3	551	
07/12	28	149	73.1	74.6	71.8	170	140	155	0.00	29.84	4		2032
07/13	28	155	72.9	73.9	71.4	170	140	170	0.00	29.80		552	2032
07/14	29	150	72.8	74.1	71.4	110		170	0.00	29.76	5	552	2031
07/15	29	150	72.4	73.2	70.9		180	180	0.00	29.79	7	553	2031
07/16	29	140	72.1	73.2	70.9	190	180	185				554	2030
07/17	38	128	72.3	73.6	70.9	170			0.00	29.86	8	554	2030
07/18	58	123	72.0	73.6	70.7		180	175	0.00	29.88	9	555	2029
07/19	43	129	71.3	72.3		180	180	180	0.00	29.90	10	558	2028
07/20					70.3	170	150	160	0.00	29.94	11	557	2028
	32	138	71.0	72.3	69.8	170	170	170	0.00	29,94	12	557	2027
07/21	32	148	70.3	71.2	69.2	160	170	165	0.00	29.92	13	558	2027
07/22	38	158	70.3	72.1	68.8	150	150	150	0.00	29.90	14	559	2026
07/23	36	159	69.6	70.9	68.1	170		170	0,00	29.95	15	600	2025
07/24	31	159	69.2	70.7	67.9	160	150	155	0.00	30.01	18	600	2024
07/25	31	154	70.1	71.8	68,6	170	170	170	0.00	29.96	17	601	2024
07/26	31	152	70.3			210	190	200	0.00	29.92	18	602	2022
07/27	30	159	71.4			180	170	175	0.00	29.89	19	603	2021
07/28	30	160	71.4			160	160	160	0.00	29.84	20	604	2020
07/29	31	163	72.5			170	190	180	0.00	29.80	21	605	2020
07/30	31	167	71.4			160	120	140	0.00	29.82	22	605	2018
07/31	30	166	71.4			150		150	0.00	29.92	23	806	2018

Notes:

* Average of two measurements (AMPM) during day in bold; all others average of hourly datalogger measurements.

* Average of two measurements (AMPM) during day in bold; all others average of hourly datalogger measurements.

* Mokelumne River flow data from U.S.G.S. gaging station #11325500 at Woodbridge, CA.

* Water temperatures were recorded hourly with a Ryan TM2000 submersible thermograph installed in pool #6a of low-stage fishway.

* Secchi depth measured twice daily in pool #9a of low-stage fishway, or from screw trap platform located about mid-channel below Woodbridge Darn, or immediately upstream of spil bay #1 in Lake Lodi.

* Rainfall measured by National Weather Service station at Camanche Reservoir N., San Joaquin Co., CA.

* Barometric pressure measured hourly and average daily value computed by National Weather Service station at Stockton, CA.

* Lunar and solar data compiled from tables in the Old Farmer's Almanac, 1994 edition, Yankee Publishing, Dublin, NH.

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994

Page 1 of 7	TOTAL OUTFLOW INDEX	40.049	40,049	40,404	10,010	10,468	10,000	10,000	70007	11,104	11 510	11 045	11 097	10 432	10.421	9.760	CZP 6	268.6	10,524	10,807	10 785	10.459	10,386	8.884	9,302	8 249	12 140	18,200	19 522	16 722	12.551	12,023	200 000
		7.734	R K37	ROMA	6.236	6.260	4 030	4 565	9.784	3 112	3 133	4 027	3.541	4 258	3,696	4 071	4 071	4.069	3 159	3,120	3.516	3,917	3,518	4,752	4,502	6.989	6 284	5,886	6.569	7.550	8.665	6,919	450 757
	NET CONSUMPTIVE TOTAL USE DEMAND	(ROOM)	(00/2)	(800)	(800)	(000)	(post)	(ope)	(000)	(006)	(006)	(1,000)	(1,000)	(1,000)	(1,000)	(1,000)	(1 000)	(1,000)	(1,000)	(1,000)	(1,000)	(006)	(006)	(006)	(006)	(300)	(006)	(006)	(800)	(006)	(006)	(006)	1000 007
	TOTAL	8 331	7227	6.814	6 136	6 160	5,832	A 76K	4 881	4 012	4 033	5.027	4.541	5,256	4,696	5.071	5 071	5,069	4,159	4,120	4,516	4,817	4,418	5,652	5,402	7,889	7,184	6,786	7,469	8,450	9,565	7,819	101 057
	BYRON-BETHANY IRRIGATION DIST.	0	0	0	0	0	0	00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	c
	CLIFTON COURT FOREBAY INFLOW	4 194	3.184	2.791	1.891	1.993	1 996	2 199	2 194	1,997	1,999	2,993	2,492	3,197	3,288	3,995	3,998	3,996	3,194	3,199	3,596	3,895	3,503	4,744	4,502	7,004	5,991	4,000	3,562	4,062	5,135	3,472	108 368
	CONTRA COSTA PUMP	104	103	105	104	102	105	8	72	75	99	19	88	103	109	108	105	108	109	105	106	107	107	103	101	101	94	8	91	36	88	88	3 001
	TRACY	4,033	3,950	3,918	4,040	4,065	3,731	3,486	2,395	1,951	1,968	1,967	1,96,1	1,956	1,289	968	898	2967	828	816	814	815	808	808	8	784	1,089	2,692	3,816	4,283	4,331	4,249	70.590
	TOTAL COLUMNS 1, 2 & 3	17,780	17,023	16,692	16,138	5 13,744 138 1,769 16,748 4,040 7 13,658 138 1,699 15,727 3,486 8 12,690 138 1,917 14,945 2,395 10 12,671 138 1,917 14,632 3,731 10 12,671 138 1,917 14,632 1,963 11 12,678 138 1,923 1,963 1,961 12 12,644 138 1,856 1,962 1,961 12 12,604 138 1,856 1,963 1,961 13 12,604 138 1,856 1,961 1,961 14 12,123 138 1,856 1,462 1,961 14 13,604 138 1,856 14,171 1,289 14 13,604 13,834 1,861 1,961 1,961 15 12,605 13,834 1,862 1,961 1,961 15 12,60																											
	SAN JOAQUIN RIVER NEAR VERNALIS	1,561	1,557	1,716	1,789	1,836	1,999	1,931	1,917	1,917	1,903	1,856	1,856	1,844	1,856	1,802	1,632	1,569	1,601	1,607	1,658	1,749	1,684	788,1	1,658	1,749	1,951	1,999	1,869	1,769	1,723	1,690	54.895
	SACRAMENTO TREATMENT PLANT	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	28	138	138	138	138	138	138	136	138	138	138	138	138	138	4,278
	SACRAMENTO RIVER AT FREEPORT	16,091	15,328	14,838	14,211	13,744	13,791	13,658	12,890	12,578	12,611	13,078	12,644	12,606	12,123	11,891	11,773	11,956	11,944	12,182	12,506	12,489	12,082	11,941	12,008	13,351	16,335	21,949	24,084	22,365	19,355	17,114	445,515
	DATE	-	2	60	**	9	9	7	89	on .	10	-	12	13	14	2	90	17	9	19	8	21	RI S	57	77 %	91	9	77	28	8	8	31	TOTAL

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994 rebruary 1994

TOTAL OUTFLOW INDEX	13 941	11.892	11 687	11 160	11.449	11 194	6 105	5.781	13.502	27,609	26,649	23,158	20,258	19,285	17,607	15,043	12.946	12,377	12,900	16,392	20,714	22,540	27 233	27,204	24 130	20.467	17.967	16,099		177.367
DEMAND	3.369	3.459	3 085	3 002	2 485	2 491	7.57	9.501	8,525	5,123	6,197	5,994	5,941	6,383	6,001	6,083	6,138	5,667	6,102	5,209	5,196	5,087	4 232	3,613	3 940	4.859	6 189	5,373		445 825
NET CONSUMPTIVE USE	(006)	(800)	(800)	(800)	(800)	(SOO)	(800)	(800)	(800)	(700)	(200)	(002)	(700)	(700)	(00/)	(009)	(009)	(009)	(009)	(800)	(009)	(009)	(200)	(200)	(909)	(200)	(200)	(200)		(18 700)
TOTAL P	4 269	4 259	3.895	3.802	3.285	3 291	8.371	10,301	9,325	5,823	6,897	6,694	6,641	7,063	6,701	6,683	6,738	8,267	6,702	5,809	5,796	5,687	4,732	4,113	4 44D	5 359	5 689	5,873		ARA KOK
BYRON-BETHANY IRRIGATION DIST.	o	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		c
CLIFTON COURT FOREBAY INFLOW	0	0	0	395	0	0	4,464	5,994	9,000	1,475	2,617	2,501	2,446	2,898	2,497	2,503	2,483	2,000	2,485	1,599	1,593	1,502	572	495	1,055	1,967	2 309	2,522		53 393
CONTRA COSTA PUMP	8	26	25	26	28	26	8	88	8	88	88	100	96	100	108	121	114	110	103	102	103	26	90	82	101	91	131	118		2 786
TRACY	4,170	4,162	3,788	3,310	3,188	3,194	3,817	4,219	4,235	4,260	4,191	4,093	4,099	4,085	4,096	4,059	4,131	4,157	4,104	4,108	4,100	4,088	4,080	3,536	3,284	3,301	3,249	3,233		108 347
TOTAL COLUMNS 1, 2 & 3	17,310	15,351	14,782	14,162	13,934	13,685	13,676	15,282	22,027	32,732	32,846	28,150	26,199	25,668	23,608	21,126	19,084	18,044	19,002	21,601	25,910	27,627	31,465	30,817	28,070	26,326	23,151	21,472		623 107
SAM JOAQUIN RIVER NEAR VERNALIS	1,652	1,620	1,601	1,582	1,567	1,551	1,561	1,632	1,809	2,792	2,736	2,548	2,277	2,034	1,910	1,802	1,769	1,749	1,842	2,125	2,314	2,373	2,418	2,441	2,336	2,190	2,076	2,013		56300
SACRAMENTO TREATMENT PLANT	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	38	138	138	138	138	138	138		3.864
SACRAMENTO RIVER AT FREEPORT	15,520	13,593	13,043	12,442	12,239	11,996	11,987	13,512	20,080	29,802	28,972	26,464	23,784	23,496	21,560	19,186	17,177	16,157	17,022	19,338	23,458	25,116	28,909	28,238	25,596	22,998	20,937	19,321		562.943
DATE	-	2	m	4	0	9	7	100	6)	10	Ξ	12	9	14	12	16	11	80	19	59	21	7	23	24	32	26	27	88	3 5	TOTAL

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994

	2			4.0			- 1	0									25			200	1000			033			913			538				
Page 3 of 7	TOTAL OUTFLOW INDEX	4.4.50	100,44	10,00	10,000	00'5	14,007	14,905	13,91	14,40	19,00	40.40	10,13	12,37	14,065	5.2.2	11,71	1771	11,311	10,120	44,006	122.1	10.6201	86+04	40.240	935	796.0	0,620	a CT a	7,738	10.263	11.047	0.00	12,016
	TOTAL	5.497	1,877	1 604	1,697	000	0/0/0	0,940	4,836	4,463	2000	4,000	4,570		4,049	1 900	4.358	4 118	1 300	4 110	130	3 977	3 776	3 506	3,676	4 130	2.764	2,862	8CE V	4 171	2,053	724	900 000	4,130
	NET CONSUMPTIVE USE	TADON	(00)	(400)	10077	(201)	(00%)	(000)	(000)	(30%)	(200)	(202)	(00)	(coc)	(000)	(BOX)	(2007)	(2007)	(2007)	(100)	(1001)	(400)	(100)	(100)	(100)	0		0.0	100	400	200	300	1000 3/	(168)
	TOTAL	5 897	5.077	5.081	5.087	6,030	4.040	8,460	4 700	4 605	900	4 910	4 770	4.744	4 647	4 53G	4 556	4316	4 894	4219	4 304	4077	3.876	3.688	3.776	4,130	3.754	3.863	4 228	4 071	1.853	424	123 230	4,288
	BYRON-BETHANY IRRIGATION DIST.	0	0	0			9 0	9 0	0.0		200	3.2	8	30	19	24	=	9		9 67	0	22	8	10	18	28	25	180	25	25	52	64	KNR	16
	CLIFTON COURT FOREBAY INFLOW	2817	1.859	2.199	2 306	7000	1 304	2 200	2,305	2.463	787.6	2.792	2,156	1 900	1,799	1 696	2.494	2.195	2.498	1,696	1,495	1,583	1,791	1,592	1,698	2,109	1,770	1,893	1,688	1,243	838	0	59 547	1,921
	CONTRA COSTA PUMP	47	0	0	89	140	151	149	99	140	145	144	147	142	142	142	140	145	131	129	135	138	136	136	139	137	133	135	137	137	15	129	3.883	125
	PUMP	3,233	3,218	2,882	2,713	2,711	2,705	2 707	2 239	2,002	2,001	2,006	2,497	2,732	2,725	2,716	1,933	1,991	1,965	2,407	2,674	2,378	1,969	1,968	1,865	1,912	1,876	1,860	2,448	2,716	909	328	70.304	2,268
	COLUMNS 1, 2 & 3	20,081	20,309	20,333	19,545	19,235	18,845	18,770	18.951	19,009	18,648	17,745	17,449	16,609	16,155	16,045	15,567	15,633	15,507	14,515	15,289	15,201	14,296	13,722	14,024	13,481	13,121	13,383	13,050	11,897	12,316	11,771	500,512	16,146
Commence of the commence of th	NEAR VERNALIS	1,961	1,896	1,890	1,903	2,020	2,329	2,321	2,351	2,388	2,494	2,456	2,418	2,351	2,314	2,358	2,373	2,396	2,594	2,433	2,381	2,373	2,284	2,190	2,147	2,111	2,147	2,147	2,104	2,034	1,978	1856	68,988	2,226
-	TREATMENT PLANT	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	136	138	138	138	138	138	138	138	133	138	138	138	138	138	4,278	138
STATE CANDERS OF STATE	ATFREEPORT	17,992	18,275	18,305	17,504	17,077	16,378	16,311	16,462	16,483	16,018	15,151	14,893	14,120	13,703	13,549	13,056	13,099	12,775	11,844	12,780	12,690	11,874	787	11,739	11,232	10,838	11,098	10,808	9,725	10,200	111'6	427,246	13,782
	DATE		2	m	4	9	9	7	89	6	9	=	12	52	4	12	16	17	18	6	8	21	2 2	23	24	R	ę:	27	100	R	8 3	5	TOTAL	AVERAGE

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994

TOTAL OUTFLOW	MDEX	70,002	0897	8,140	8,355	7,936	6,615	6 677	8 527	6.253	8414	7,323	7.176	6 967	8,978	1769	6.881	6.887	6971	5.590	6,819	6917	6.940	6,873	6,889	7.748	8.051	8 868	8915	080 6	8,556	Contract in a s	222,044	(,401
	DEMAND	070'1	3,220	3,230	3,354	3,689	3,668	3 503	3.847	3.437	3.553	2.943	3,433	2 790	2729	2 843	2 168	1881	1 910	2874	2,117	2367	2,922	2,857	2.805	2,695	2374	2822	3 621	4 379	4,338	00 760	69,706	7,369.7
MPTIVE	USE	000	000	000	700	800	800	006	006	900	1,000	1,000	1,000	1,000	1,000	1,100	1,100	1,100	1,100	1,200	1,200	1,200	1,200	1,300	1,300	1,300	1300	1,400	1 400	1 400	1,500	94 000	31,000	1,000
	1 1 200	0.350	2,000	7,090	2,664	2,889	2,868	2,603	2.947	2,537	2,553	1,943	2,433	1,790	1,729	1,743	1,066	781	810	1,674	917	1,167	1,722	1,357	1,505	1,395	1,074	1.422	2221	2,979	2,838	99+09	20,100	6000'1
BYRON-BETHANY	ANDRA I KUN DIST.	3 8	5 5	8 5	8	113	100	111	111	76	83	32	99	109	114	125	101	101	72	26	112	134	126	8	25	78	141	38	8	75	0	2010	7,400	30
CLIFTON COURT B	8	800	200	0 (0	445	396	144	490	345	783	138	183	0	393	145	0	0	0	896	162	400	406	11	411	361	157	0	804	1,240	992	00,000	276	2
CONTRA COSTA		117	437	900	250	28	141	135	143	145	150	135	149	148	142	120	141	146	148	147	143	150	156	55	151	146	142	138	113	146	160	4 232	111	
TRACY	873	2 142	2818	2 860	7,000	413	2,429	2,435	2,425	2,123	1,703	1,704	2,151	1,753	1,308	1,603	1,026	736	734	728	724	751	1,286	1,241	898	2967	916	1,323	1,670	1,668	1,686	46 778	1 559	
COLUMNS 1, 2 & 3	11,588	10 923	11 436	44 700	200	079'11	10,283	10,180	10,374	9,690	296'6	10,266	10,609	9,757	9,707	9,814	9,027	8,768	8,881	8,454	8,936	9,284	9,862	9,530	9,69,4	10,443	10,425	11,690	12,536	13,459	12,894	311.810	10 394	
NEAR VERNALIS	38	1,769	1,703	1 947	2007	007,	1,658	1,588	1,514	1,514	1,6,7	1,728	1,526	1,447	1,423	1,400	1,335	1,353	1,411	1,341	1,318	1,312	1,358	1,364	1,551	2,282	2,760	3,230	3,579	3,695	3,273	55,534	1851	C 1000
TREATMENT PLANT	138	138	138	138	200	900	136	8	138	138	138	138	2	100	138	8	138	138	138	138	138	87	138	8	8	138	138	8	138	138	138	4,140	138	
SACRAMENTO RIVER AT FREEPORT	8,614	9,016	9,594	9729	0.754	1000	79,40	6,454	8,722	8,038	8,152	6,399	8,945	8,1/2	8,146	8,276	7,554	7,277	7,332	6,975	7,480	1,834	8,366	8,028	8,003	8,013	7,527	8,322	6,819	9,626	9,483	252,136	8,405	
DATE	7	2	60	7	W.	2.6	1.0	- 5	0	0	2	- 5	N.	2 :	T.	0	9	17	92	0.00	₹ 2	7	2 2	25	57	12	92 1	/7	28	2	30	TOTAL	AVERAGE	

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994

2	1.54					-					-		غند	1	200			200	Liter		96,00	(40)										
TOTAL OUTFLOW	0 874	7.64	7 488	6.044	0,344	1000	7,870	7 184	8 201	9.653	10,875	10,028	9,013	8,192	8,009	7,925	2000,	940,7	6.770	6,534	6.379	6.786	5,712	6,891	4 380	3,855	4 409	3.800	4 180	3,949	940	210,131
TOTAL	3 301	3,005	2,468	2018	2,010	0.000	2000	4.745	4.153	4,345	3,484	3,563	3,772	3,428	3,094	3,926	0,100	3.154	3.736	3,914	4,069	4,042	5,006	3,190	5,191	5,462	5.752	6.075	5.016	4,232	200 343	120,313
NET CONSUMPTIVE USE	1 400	1,500	1 500	1 800	1,000	200	1,000	1,700	1,700	1,800	1,800	1,800	1,900	006	1,900	2,000	2,000	2,100	2,100	2,100	2,200	2,200	2,200	2,300	2300	2,300	2,400	2,400	2,500	2,500	61 100	
TOTAL	1 801	1.565	898	1 318	1 296	4 400	3 2	3.045	2,453	2,545	1,684	1,783	1,872	1,528	1,194	978'1	4.483	1,054	1,636	1,814	1,869	1,842	2,806	980	2,891	3,162	3,352	3,875	2,516	1,732	59 243	20,4,00
BYRON-BETHANY IRRIGATION DIST.	78	76	75	79	63	77	15	76	÷	82	49	F	187	9,7	9,0	\$ 8	76	2 23	8	33	53	111	135	76	92	8	88	2	8	139	2 179	1
CLIFTON COURT FOREBAY INFLOW	47	248	0	323	198	9	300	2,150	1,377	1,409	549	637	768	200	98	000	399	0	669	749	834	798	1,89,1	0	1,870	1,875	1,497	1,800	93	0	21,903	100
CONTRA COSTA PUMP	164	159	155	152	147	145	140	136	134	138	191	161	3 5	701	5 5	147	146	139	128	122	119	127	124	127	161	181	183	181	183	187	4,672	2000
TRACY	1,666	1,234	888	822	1,014	828	866	835	953	1,027	1,033	1,036	1,024	200	200	1,014	1,014	884	898	976	960	200	979	629	897	1,199	1,765	1,787	2,370	1,684	34,817	
TOTAL COLUMNS 1, 2 & 3	11,872	10,676	9,654	9,862	5,707	9,684	10,011	11,929	12,354	13,998	14,239	13,589	12,780	11 103	11.851	11,094	10,831	10,135	10,506	10,448	10,448	10,628	10,718	10,081	10'8	9,317	10,161	9,875	9,136	8,181	336,444	40.000
SAN JOAQUIN RIVER NEAR VERNALIS	2,556	2,069	1,789	1,664	1,545	1,447	1,967	2,667	2,880	2,824	2012	2,049	1.876	1,697	1,594	1,477	1,441	1,620	2,255	7,517	2,556	2,333	2,200	2,013	1,710	1,441	/96/	906'1	1,278	1,185	61,181	4.004
SACRAMENTO TREATMENT PLANT	138	138	138	138	138	138	138	138	138	138	000	200	138	138	138	138	82	138	138	3 5	2 5	2 0	0 00	000	130	138	138	138	200	38	4,278	400
SACRAMENTO RIVER AT FREEPORT	8,178	8,469	7,727	8,060	8,024	8,089	7,916	9,134	9,336	11,036	186,11	200,000	9 606	9.268	10,119	8,479	9,252	8,377	8,113	1,183	# C	101.0	0,500 %	000'1	(7/7)	200 / / O	0,0,0	6,431	08/1/	0000	270,985	0.744
DATE		2	m	4	40	9	7	00	on s	2:		4 5	1 4	10	16	17	18	18	8 2	4.5	32	25	26.	2 60	200	77	9 8	9 8	8:	ñ	TOTAL	AVEDAGE

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994

	DATE	-	7	n	4	10	9 49	0 1		000	n s	01		77	2.3		0 9	200	0	9 9	30	35	3.5	3.5	25	57	96	07 6	77	97	52	8 50	TOTAL	AVEDAGE
	SACRAMENTO RIVER AT FREEPORT	6,880	1,470	7,155	7,582	7 544	0000	0,003	6,223	6,688	6,704	085,	1367	1981	7,000	7,990	006.7	7.433	2002	are a	0000 a	87/0	0000	CAT B	2010	2000	21778	670'6	8,845	8,335	9,310	9,014	239,643	7 088
	SACRAMENTO TREATMENT PLANT	215	215	215	215	215	214	200	212	215	215	215	215			017			340	210	0.70	217	316	216	210	017	270	210	216	215	215	215	6.450	216
	SAN JOAQUIN RIVER NEAR VERNALIS	1,159																									001,1	P.	1,138	1,094	1,078	994	32 688	+ 000
	TOTAL COLUMNS 1, 2 & 3		9,850							7,907						9,262				9,142							10,932				10,603			0.000
	TRACY 3 PUMP	888								902												2,035							1,700	1,696	1,698	1,700		
	CONTRA COSTA PUMP	155				E.	700	700		213				215																	236	234	6 167	10170
	CLIFTON COURT FOREBAY INFLOW	652	1 398	EPB	1	98	878	3	3	200	104	757	400	9	954	421	342	٥	0	429	833	290	0	381	0	160	009	450	1,356	188	806	495	00073	(4,930
	BYRON-BETHANY IRRIGATION DIST.							73	160		185							161				17									122			4,123
	TOTAL					1,760	-				856	1,521	1291	840	1,835	1,809	2,015	1,656	1,685	2,122	2,503	2,452	2,601	2,580	1,918	1,962	2,382	2.218	3,157	2794	2618	2,288	20.000	179'00
	NET CONSUMPTIVE TOTAL USE DEMAND					2,700				2,800																					3,800			96,300
	DEMAND	4 039				4,460				3.751																			6 957	6 504	6.418	6,188		153,121
Lade e of	TOTAL GUTFLOW INDEX	e e	0000	500	4,08	4,40	4.37																	4,420	4,619	4.642	4.450	4 520	A 101	0307	4.485	4,035		125,680

Appendix 7. Delta Outflow (in CFS), January 1994 - July 1994 July 1994

7 017	TOTAL OUTFLOW INDEX	2 0.00	0,54.0	7 183	5,128	4 525	808	5.083	5,028	4 908	5,594	5.204	5,106	4.591	4.101	4,073	4 307	4,152	4 029	4,484	4.964	4,892	4,609	4,557	4,583	4,586	3.945	3.525	2 990	2.476	2.506	3,025	124 030	4.323	The same of the sa
Page 7 of 7		22	3 %	3 5	35	37	. 50	75	8	17	28	24	122	100	77	22	2	00	59	93	92	9	37	37	00	20	g	13	50	-	2	9	- 95	2	
	DEMAND	e e	R.T.	. 0	8 061	8 4	6.3	6.4	8 9	9 441	10.43	11.00	10,645	10.7	11.17	10.8	10.38	10,78	10.55	9.30	7.87	7,840	7,86	7,93	8,10	8,588	8.883	9,118	9.45	10,18	9.93	8,576	771 55	8,760	-
	NET CONSUMPTIVE USE	4000	4,000	4000	4,100	4 100	4 100	4,100	4 200	4 200	4,200	4300	4,300	4,300	4,300	4,400	4,400	4,400	4.400	4,500	4,500	4,500	4,500	4,500	4,600	4,600	4,600	4,600	4,600	4,600	4,600	4,600	135 100	4,358	
	TOTAL	2687	275	1 060	1861	2337	2 288	2375	2782	5.241	6,226	6,724	6,345	6,418	6,877	6,492	5,980	6,390	8,158	4,809	3,476	3,340	3,387	3,437	3,500	3,988	4,283	4,518	4,855	5,591	6,330	3,976	136 456	4,402	
	BYRON-BETHANY IRRIGATION DIST.	583	76	78	76	-60	76	8	122	89	76	82	96	83	142	96	96	96	37	88	98	72	99	88	78	92	25	74	80	8	19	8	2510	81	
	CLIFTON COURT FOREBAY INFLOW	785	768	0	0	403	906	1,249	1,293	2,654	2,718	2,693	2,272	2,039	2,467	2,083	1,98,1	2,613	2,298	1,496	1,016	1,193	1,205	1,300	1,352	1,857	2,089	2,390	2,694	3,423	3,150	1,781	54.406	1,755	
	CONTRA COSTA PUMP	223	224	223	211	210	306	213	213	213	216	214	224	217	218	223	217	218	216	215	215	212	222	222	228	206	212	210	305	215	211	508	6.683	216	
	TIMCY	1,772	1,809	1,813	1,816	1,815	1,254	1,012	1,408	2,432	3,368	3,689	3,943	4,245	4,314	4,272	3,878	3,655	3,681	3,198	2,331	2,007	2,026	2,005	1,896	2,001	1,997	1,992	2,036	2,036	2,030	2,038	77.877	2,512	
	TOTAL COLUMNS 1, 2 & 3	10,616	10,858	10,143	11,179	10,962	11,214	11,558	12,018	14,349	16,020	16,228	15,751	15,309	15,278	14,965	14,687	14,942	14,587	13,793	12,940	12,732	12,496	12,494	12,683	13,154	12,828	12,643	12,445	12,667	12,436	11,601	405,576	13,083	
	SAN JOAQUIN RIVER NEAR VERNALIS	898	932	952	1,068	1,057	1,121	1,100	1,004	596	537	85	892	206	897	942	827	200	888	1,010	1,031	1,162	1,260	1,355	1,453	1,563	1,545	1,551	1,538	1,465	1,370	1,204	35,129	1,133	
	SACRAMENTO TREATMENT PLANT	215	215	215	215	215	215	198	198	198	198	198	198	361	8	198	198	198	88	198	138	198	198	158	198	198	198	198	198	198	198	188	8,240	201	
	SACRAMENTO RIVER AT PREEPORT	8,412	9,711	8,976	9,896	069'6	9,878	10,280	10,816	13,162	14,885	15,036	14,661	14,204	14,183	13,825	13,562	13,837	13,400	12,585	11,711	11,352	11,038	10,843	11,032	11,383	11,085	10,894	10,709	11,004	10,668	10,199	364,207	11,749	
JULY 1894	DATE	-	2	ea	4	NO.	9	7	80	cn ·	9 :		12	13	7	13	16	17	20	9	8	27	7 2	2 2	77	Q	8	27	R	R :	8	10	TOTAL	AVERAGE	

	0.00 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	RECOVERY RELEASE RE
	WEIGHT (GRAMS)
	AFTER RECOVERY (MM) 111 112 113 114 115 115 116 117 117 118 118 119 119 119 119
	ATER RECOVERY (AM) 121 122 123 124 125 126 127 128 128 128 129 129 129 129 129 129 129 129 129 129
	RECOVERY 11ME
	RECOVERY DATE DA
	LOWER LADGER LOWER LOWER LADGER LOWER LADGER LOWER LADGER LOWER LADGER LOWER LADGER
NOI	RELEASE LOCATION 250 FT US DAM (RM 38.7) 25
HINOOM SALM	
JUVENILE CI	DATE PELEASE PELEASE PASE P
UTILITY DIST	TAGGING DATE DATE DATE DATE TABAR (U)
APPENDIX 8. EAST BAY MUNICIPAL UTILITY DISTRICT PASSIVE-INTEGRATED TRANSPONDER DATA FOR JUVENILE CHINOON SALMON	TRANSPONDER TAG ID NUMBER TAG ID NUMBER TOG
APPENDIX 8. EAS PASSIVE-INTEGRA	TRANSPONDER LOT NUMBER LOT NUMBER 2047 270635 270645 270655 270646 270647 270646 270647 270648 27064

	ELAPSED																																		1																							
	RECOVERY	RELEASE 3	RELEASE 4	AELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	NELENARE A	DELEASES	REI FASE A	DEI FASCA	PEI FASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASE 4	RELEASES	RELEASE 5	RELEASES	RELEASES	RELEASE 5	RELEASE 5	RELEASE 5	RELEASE 5	RELEASE 5	RELEASE 5	KE EASE 0	DESCRIPTION OF	REI FASE 6	RELEASE 5	RELEASE 5	RELEASE 5	RELEASE 5	RELEASE 6	RELEASES	ACTURAGE B	PELEASE B	RELEASE &	RELEASE 6	RELEASE 8	RELEASE 6	RELEASE 6	RELEASE 6	RELEASES	RELEASE 8	RELEASE 8	RELEASE 6		RELEASE 6	RELEASE 6	
	WEIGHT (GRAMS)	11.3	12.6	0.41	0.5	13.9	6.7	2 :	48.7	121	11.6	0	11.9	12.1	12.7	15.1	8	12.3	13.2	-	10.4	15.8	12.5	13.6	14	12.1	12.8	14.2	12.8	14.2	12	16.7	13.2	14.5	0 8	151	8.1	11.7	8.4	7.7	119	200	20.0	10.7	9.5	10.6	10.7	12.1	12.7	6 2 9	15.3	9.6	9.9	12.2	11.6	15	12.1	
	RECOVERY (MM)	100	110	100	24	100	-04	200	116	100	107	84	103	106	107	107	96	105	105	86	8	100	103	108	108	102	106	112	107	113	104	117	108	711	NA.	114	93	103	96	06	104	100	406	100	8	100	103	107	113	919	113	96	96	106	101	112	105	
	RECOVERY (MM)	110	110	117	101	117	111	146	25.	110	115	101	110	116	115	119	103	113	114	106	107	117	110	117	117	111	115	122	115	121	112	122	2	777	65	524	100	110	105	26	21:	443	7.1	100	106	109	111	114	118	120	123	103	107	114	112	120	113	
	TIME	10:30	08:50	16:00		06:50	0000	08-16	15.50	10.25	10.25	15:50	08:15	08:15	16.10	08:15	08:15	08:15	15:50	15:50	16:10		08:15		06:50	15:40	06:30	15.40	06:30	08.50	08:30		00.00	04.48	06:15	16:00	06:30	08:15	06:15	06:50	0000	20,00	14.14	06:15	08.15	08:15	16:10	16,08	08.15	08:15	06:50	08:15	55.15	08.18	16.30	08,15	08:15	
	DATE	07/20/94	07/24/04	07/28/94	07/25/94	07/24/94	07/2/04	070164	07/20/94	07/20/94	07/20/94	P602/20	07/21/94	07/21/84	07/21/84	07/21/94	07/21/94	07/21/94	07/20/94	07/20/04	07/21/94	07/20/94	07/21/94	07/29/94	07/24/94	07/30/94	07/25/94	07/30/94	07/2394	07/24/94	07/23/54	07/24/54	07/24/34	48CO70	07/22/94	95/00/94	07/24/64	07/21/94	07/22/94	1652770	07/24/34	07/7/04	67774/54	07/22/94	07/21/94	07/21/94	07/21/94	0777764	07/21/94	07/21/94	07/23/94	07/21/94	07/21/84	07/21/64	07/23/54	07/21/94	07/21/94	- Contract and the particular par
	LOCATION	UPPER LADDER	UPPER LADDER	UPPER LADDER	UPPER LADDER	UPPER LADOER	UPPER LADOER	CWERTADORR	LOWER LADDER	LOWER LADOER		LOWER LADOER	LOWER LADDER			LOWER LADDER	UPPER LADOER	UPPER LADDER	UPPER LADDER	UPPER LADOER	UPPER LADOER	UPPER LADOER	UPPER LADOER	UPPER LADDER	LINGER LADOER	LOWER LANGER	LOWER LADOER	LOWER LADOER	LOWER LADOER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	(IDDED LANGED	UPPER LADDER	UPPER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	COMER LADOER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER	LOWER LADDER								
П	LOCATION PARK GAZEBO (RM 16.7)	CONCRETE PAD (RM 40.75)	CONCRETE PAD (RM 40 75)	CONCRETE PAD (RM 40 75)	CONCRETE PAD (RM 40.75)	CONCRETE PADISM 40.75)	CONCRETE PAD IRM 40,75)	CONCRETE PAD IRM 40.751	CONCRETE PAD (RM 40.75)	CONCRETE PAD (RM 40.75)	CONCRETE PAD (RM 40,75)	CONCRETE PAD (RM 40.75)	IE PAD	CONCRETE PAD (RM 40.75)	De PAD	쁴	7.0	CONCRETE PAD (FIM 40.75)	RAIL ROAD BRIDGE (RM 42.1)	RAIL ROAD BRITAGE (RM 42.1)	DAIL BOAD BRIDGE (RM 42.1)	RAIL ROAD BRIDGE /RM 42 1)	RAIL ROAD BRIDGE (RM 42.1)	DAN DOAD BRIDGE HIM 42 1)	DADK GANERO JOHN TO THE	PARK GAZEBO IRM 39 71	PARK GAZEBO (RM 39.7)	PARK GAZEBO (RM 39.7)	PARK GAZEBO (RM 39.7)	PARK GAZEBO (RM 38.7)	PARK GAZEBO (RM 39.7)	PARK GAZEBO (RM 39.7)	DARK GAZEBO (RM 39.7)	PARK GAZERO (PM 29.7)	PARK GAZEBO (RM 39.7)		PARK GAZEBO (RM 39.7)	PARK GAZEBO DRM 39.7)	PARK GAZEBO (RM 397)		3																	
	DATE TIME O7/19/84 21:15	H	9/94 21:00	П	3/04 21:00	+	-	9/94 21:00		9/94 21:00	07/19/94 21:00		1	+	+	+		21:00		*	2100	7	21.00		-	1		1	1	-	25.50	13.50	12.30	12:30	12:30	1230	12.30	1230	10.00	12:14	1215	12.15	12:15	12:15	12:15	12.15	12.15	21.65	1215	12.15	Н	+	+	0.094 12:15	Н	0.094 12.15	37	
	DATE DATE DATE DATE DATE				770054 (U) 07713/04		1	t	7594 (U) 67719/94	,				1	771084 (U) 0771984	+	+	1	7/2/4 (U) 07/19/4	+	1		H	78/84 (U) 07/20/94	1	7894 (5) 07/2094	1		1		THESE CO. OF COURSE	TOUGH OIL OLD ON		18	2	J		1	7554 (U) 07/2	1	7/10/84 (U) 07/2	10	88	77/054 (U) 07/2094	3	7/10/94 (U) 07/2		74054 (U) 077054	7,694 (L) 07/29	-31	18	7694 (3) 07/2		78/94 (U) 07/20/94	7/10/04 (U) 07/29			
	or or	007347786	0000027054	007783512	007030883	007105265	007588001	629698900	007121893	007585109	007127845	008621256	007025595	006/84053	006864501	006276572	PGCC25900	00/331818	0002084000	00000/040	000591083	000001007	007031011	007839318	006572503	00000000	006111804	006564592	000770091	907572316	Westware anotherna	000018008	799055900	008359124	008122370	006365062	000559942	000000014	t	t	t		008383302	006526336	006884298	007601811	006381303	006600781	008576109	007330570	007100622	006297088	002026315			007358110		
	DER	П	27658	27650	16773	27667	18750	27663	27654	15757	27658	27650	18774	16//0	10011	16//6	27000	2/044	2/561	70077	10013	10/63	16/61	27647	27643	27544	10700	2/641	2/043	16/61	20000	18785	18782	27656	27646	16775	16779	27040	3764K	14773	18785	27643	27666	18785	27844	18781	18778	48780	27659	18812	16787	27654	18812	27651	16811	16783	6/1830	

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp	pH	SpCond	DO	DO	Redox
River Mile/	THE RESERVE OF THE PERSON NAMED IN	THE RESERVE AND ADDRESS OF THE PARTY OF THE	degF	units	uS/cm	%Sat	mg/l	mV
	Date	Time	Temp	рН	SpCond	DO	DO	Redox
Depth	MMDDYY	HHMMSS	degF	units	uS/cm	%Sat	mg/l	mV
	Part I							1
RM38.5	52694	134108	67.7	8.58	43.1	102.5	9.38	316
RM38.6-S	52694	135136	71.1	8,59	43.3	109.4	9.63	365
-3	52694	135233	69.5	8.52	43	108.9	9.76	371
-6	52694	135314	65.9	8.49	43.3	105.6	9.86	376
-9	52694	135351	65.5	8.46	43	105.1	9.85	379
-12	52694	135437	65.3	8.48	42.8	104.5	9.81	379
-15	52694	135520	65.1	8.45	42.3	103.5	9.74	382
RM39.0L-S	52694	135946	71.3	8.68	43.8	108	9.49	367
-3	52694	140052	67.2	8.58	43.1	108	9.93	376
-6	52694	140146	66.3	8.63	42.5	111.9	10.39	377
-9	52694	140227	66.3	8.6	42.7	109.5	10.17	379
RM39.0R-S	52694	140705	70.1	8.53	43.8	105	9.35	375
-3	52694	140737	66.6	8.49	43.3	104.8	9.7	380
-6	52694	140832	65.2	8.44	43.8	104	9.77	385
-9	52694	140903	65	8.43	43.6	103.1	9.71	387
-12	52694	140948	64.9	8.43	43.6	103.1	9.73	388
-15	52694	141019	64.8	8.44	43.5	103	9.72	389
RM39.9-S	52694	142124	71.2	8.54	43.5	108.7	9.56	381
-3	52694	142215	65.7	8.43	42.9	102.4	9.57	390
-6	52694	142248	64.4	8.41	42.8	102.8	9.75	392
-9	52694	142323	64	8.43	42.7	102.4	9.76	392
-12	52694	142358	64	8.43	42.6	102.3	9.75	393
RM40.75-S	52694	142951	66.5	8.31		107.8	9.99	394
-3	52694	143029	65	8.52	42.7	105.2	9.91	388
-6	52694	143116	64.4	8.5	42.6	104.6	9.92	391
-9	52694	143204	64.2	8.49	42.5	104.6	9.95	393
RM41.3-S	52694	143717	64.3	8.44	43.3	102.2	9.7	402
-3	52694	143753	64	8.41	43.3	102.2	9.74	403
-6	52694	143822	63.5	8.4	43.2	101.4	9.72	404
-9	52694	143913	63.1	8.42	43.2	101.5	9.77	404
RM42.3-S	52694	144503	61.9	8.48	41.9	98.4	9.6	395
-3	52694	144551	61.6	8.39	42.1	98	9.6	401
-6	52694	144656	61.6	8.34	41.9	98.3	9.63	404
-9	52694	144758	61.5	8.36	42.2	98.1	9.62	404
RM43.25-S	52694	145311	62,7	8.77		97.1	9.39	382
-3	52694	145405	61.4	8.49	41.3	99.4	9.76	396
-6	52694	145518	61.4	8.42	41.3	99.1	9.73	400

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/	Date	Time	Temp	pН	SpCond	DO	DO	Redox
Depth	MMDDYY	HHMMSS	degF	units	uS/cm	%Sat	mg/l	mV
RM38.5	53194	145231	67.7	8.49	43.1	100.0	0.05	
	00.00	1,0201	07.7	0.48	43.1	102.2	9.35	337
RM38.6-S	53194	150243	64.1	8.15		119.1	11.34	372
-3	53194	150351	67.2	8.34	43	102.3	9.4	365
-6	53194	150437	65.4	8.3	42.9	100.9	9.46	371
-9	53194	150515	64.8	8.27	42.8	99.7	9.41	374
-12	53194	150606	64.6	8.27	42.9	99.6	9.42	377
-15	53194	150643	64.5	8.27	42.7	99.8	9.45	378
RM39.0R-S	53194	151347	70.6	8.84		4047	0.00	
-3	53194	151422	66.9	8.39	43.1	104.7	9.28	
-6	00104	101422	00.5	0.39	43.1	101.7	9.38	386
-9	53194	151530	64.2	8.27	12.6	00.4	0.40	
-12	53194	151557	64	8.27	42.6	99.1	9.43	394
-15	53194	151647	64	8.26	42.8	98.8	9.41	395
	00104	101047	04	0.20	42.6	99.1	9.44	395
RM39.0L-S	53194	152107	71.1	8.54	43.8	109.9	9.68	375
-3	53194	152137	68.6	8.47	42.9	109.7	9.93	
-6	53194	152205	66.6	8.46	42.5	108.9		379
-9	53194	152237	65.9	8.51	42.8	108.6	10.08 10.12	382
(F)		,ozzo.	00.0	0.01	42.0	100.0	10.12	381
RM39.9-S	53194	152947	65.8	8.84		102.4	9.55	326
	53194	152959	66.3	8.5		103.5	9.61	368
-3	53194	153029	65	8.35	42.3	101.5	9.57	387
-6	53194	153057	64.2	8.3	42.3	100.2	9.53	391
-9	53194	153115	63,7	8.28	42.1	100.1	9.58	392
RM40.75-S	53194	153924	65.5	8.39	42.9	104.4	0.70	200
-3	53194	153946	64.7	8.36	42.8	104.1	9.76	382
	53194	153956	64.7	8.36	42.0	103.3	9.76	385
-6	53194	154016	63	8.34	42.9	102.6	9.7	385
-0	00194	154010	05	0.34	42.9	102.2	9.85	387
RM41.3-S	53194	162532	63.3	8.64	39.6	101.2	9.71	410
-3	53194	162602	62.3	8.42	42.5	100	9.72	419
120	53194	162620	62.3	8.38	42.6	100.3	9.75	421
-6	53194	162649	61.2	8.34	42.5	98.3	9.68	422
-9	53194	162733	61.2	8.31	42.4	99.2	9.77	423
RM42.3-S	53194	163919	61.1	8.38		99.4	9.79	396
-3	53194	163952	60.8	8.37	41.8	99.3	9.82	398
-6	53194	164029	60.8	8.32	41.8	98.3	9.73	
-9	53194	164109	60.8	8.3	41.6	96.1	9.73	401
-0	00194	104108	00.0	0.0	41.0	90.1	9.5	402
RM43.25-S	53194	165547	61.5	8.52	39.7	102.9	10.1	421
-3	53194	165612	61.5	8.46	41.8	104.3	10.23	424
-6	53194	165641	61.4	8.42	41.8	105.8	10.38	426
-9	53194	165716	61.4	8.42	41.7	103.9	10.2	425

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date	Time	Temp	pН	SpCond	DO	DO	Redox
Depth	MMDDYY	HHMMSS	degF	units	uS/cm	%Sat	mg/l	mV
RM38.5	60794	135327	64.4	8.62	40.4	400.0		2700
,,,,,,,,,	00104	100027	04.4	0.02	43.4	102,8	9.75	346
RM38.6-S	60794	140430	67.7	9.28	43.3	118.6	10.83	250
-3	60794	140546	63.8	8.62	43.1	103	9.84	353
-6	60794	140632	63	8.49	43	102.1	9.85	382
-9	60794	140718	62.8	8.46	43.2	102.1	V255.000000	389
-12	60794	140801	62.7	8.44	42.9	101.9	9.86	392
-15	60794	140914	62.6	8.44	42.8		9.85	394
	00,01	140014	02.0	0.44	42.0	102.3	9.91	396
RM39.0L-S	60794	141406	68.8	8.75	41.2	113.1	10.21	379
-3	60794	141500	66.6	8.61	43.7	107.1	9.91	388
-6	60794	141538	63.8	8.51	42.9	105.9	10.11	
		111000	00.0	0.01	42.5	105.9	10.11	394
RM39.0R-S	60794	142024	67.7	8.58	43.5	108.1	9.89	388
-3	60794	142101	65.8	8.47	43.2	104.8	9.78	395
-6	60794	142156	63	8.42	42.8	102.7	9.9	399
-9	60794	142240	62.5	8.39	42.4	101.6	9.85	402
-12	60794	142314	62.4	8.39	42.7	101.7	9.87	402
-15	60794	142359	62.3	8.38	43	101.7	9.87	403
			02.0	0.00	45	101.0	9.07	404
RM39.9-S	60794	142851	64.3	8.54	43.1	103.1	9.79	392
-3	60794	142928	63.5	8.45	42.9	102.7	9.84	397
-6	60794	143019	62.7	8.42	42.7	101.9	9.86	400
-9	60794	143051	62.3	8.41	42.7	101.7	9.89	402
-12	60794	143123	62.3	8.4	42.5	101.9	9.9	403
	337.57	(V)(3/2-77.8)	1000100	8760	12.0	101.0	5.5	400
RM40.75-S	60794	143701	64.8	8.69	43.5	106.9	10.1	388
-3	60794	143729	64.4	8.58	43.5	105.7	10.02	394
-6	60794	143802	63.1	8.53	43.4	105.3	10.14	397
-9	60794	143839	62.3	8.51	43.1	105.3	10.24	400
						100.0	10.24	400
RM41.3-S	60794	144541	62.8	8.66	42.8	103.4	9.99	389
-3	60794	144628	62.1	8.51	42.8	102.8	10.02	397
-6	60794	144706	61.4	8.42	42.8	101.9	10.01	402
-9	60794	144737	61.3	8.43	42.5	102.2	10.05	403
RM42.3-S	60794	145640	60.9	8,51	42.2	99.5	9.83	397
-3	60794	145710	60.9	8.42	42.1	99.7	9.85	402
-6	60794	145741	60.8	8.37	42.2	99.7	9.86	404
-9	60794	145816	60.8	8.36	41.8	99.6	9.85	405
	0.0000000000000000000000000000000000000		122121	18/28	1023	165 T C C	1.000	07240
RM43.25-S	60794	150310	60,9	8.56	42	101.8	10.05	397
-3	60794	150340	60.9	8.48	42.1	101.9	10.06	400
-6	60794	150416	60.8	8.43	42	102	10.08	403

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp	pН	SpCond	DO	DO	Redox
Deptil	WINDDIT	ппммоо	degF	units	uS/cm	%Sat	mg/l	mV
RM38.5	61494	134031	64.7	8.53	10.0		00000000	
NAME OF THE PARTY	01101	104001	04.7	0.53	42.9	101.4	9.59	336
RM38.6-S	61494	135207	67.8	8.72	43.2	440.0		
-3	61494	135255	64.1	8.47		112.6	10.28	359
-6	61494	135341	63.6		42.8	101.2	9.63	374
-9	61494	135424	63.4	8.38	42.7	100.6	9.62	380
-12	61494	135505		8.35	42.6	100.4	9.63	384
-15	TO SEE STATE OF THE SECOND SEC		63.3	8.34	42.6	100.3	9.64	386
-10	61494	135550	63.2	8.32	42.5	100.6	9.67	389
RM39.0L-S	61494	140237	70.7	9.13	44.9	447.0	101	
-3	61494	140322	66.9	7.75		117.3	10.38	350
-6	61494	140408	64.1	8.68	43.5	107.3	9.89	373
-9	100000000000000000000000000000000000000	1102/67/7		8.48	42.6	103.3	9.83	384
-5	61494	140449	64.1	8.43	42.6	103.7	9.87	387
RM39.0R-S	61494	141205	64.7	8.47	42.8	400	0.04	
-3	61494	141249	64.4	8.38		102	9.64	379
-6	61494	141322	63.6		42.8	101	9.59	386
-9	61494	141405		8.34	42.7	100.7	9.64	390
-12	25000000000000000000000000000000000000		63.4	8.33	42.7	100.2	9.61	392
-12	61494	141504	63.5	8.33	42.9	100.2	9.61	394
-10	61494	141725	63.4	8.34	42.9	100.2	9.61	395
RM39.9-S	61494	142537	64.1	8.42	43.2	103.6	9.86	385
-3	61494	142653	63.5	8.35	43.1	103	9.87	392
-6	61494	142812	62.9	8.36	43.2	102.8	9.92	395
-9	61494	142903	62.8	8.37	42.8	103	9.95	395
	20020	1.2000	02.0	0.07	72.0	103	9.95	393
RM40.75-S	61494	143839	62.9	8.45	43	103.1	9.95	385
-3	61494	143906	62.1	8.4	42.9	102.9	10.02	389
-6	61494	144025	61.7	8.37	42.8	102.3	10.01	394
-9	61494	144057	61.7	8.37	42.8	102.9	10.07	395
100	0.101		0.1.7	0.07	72.0	102.5	10.07	393
RM41.3-S	61494	144902	62.1	8.54		100.6	9.8	382
-3	61494	144937	61.6	8.41	42.5	100.4	9.84	390
-6	61494	145011	61.6	8.39	42.5	100.3	9.83	393
-9	61494	145042	61.6	8.35	42.5	100.3	9.83	395
	23/2/00/200		100.00			(Marcon)	- Section	
RM42.3-S	61494	150043	61.6	8.55	42.3	98.8	9.67	383
-3	61494	150136	61.6	8.38	42.2	98.7	9.67	394
-6	61494	150224	61.6	8.36	42.3	98.7	9.67	395
-9	61494	150304	61.5	8.34	42.1	98.5	9.66	397
21442 05 0	04404	454704		0.40	40.0	400.0	0.00	
RM43.25-S	61494	151731	61.4	8.49	42.6	100.6	9.89	388
-3	61494	151817	61.3	8.41	42.6	100.8	9.91	392
-6	61494	151852	61,3	8.39	42.4	100.8	9.9	395

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp	pH	SpCond	DO	DO	Redox
Deptii	MINIDUTT	HHIVIVISS	degF	units	uS/cm	%Sat	mg/l	mV
RM-38.5	62194	142602	67.8	8.7	44	100 6	0.20	057
		1.2002	07.0	0.7	777	102.6	9.36	357
RM-38.6-S	62194	143448	72.7	8.62	44.5	111.8	9.68	383
-3	62194	143532	66.4	8.53	43.5	105.7	9.8	100000004666
-6	62194	143616	65.7	8.46	43.4	104.5	9.77	391
-9	62194	143656	65.5	8.45	43.6	104.5	9.75	396
-12	62194	143741	65.3	8.43	43.8	103.2		398
-15	62194	143833	64.9	8.37	43.4	99.7	9.69 9.4	401 405
RM-39.0L-S	62194	144420	71.9	8.69	44.5	440.4	40.40	
-3	62194	144501	67.3	8.6	43.4	116.1	10.13	382
-6	62194	144558	66.8			113.9	10.45	389
~	02154	144000	8.00	8.77	43.3	115.2	10.63	383
RM-39.0R-S	62194	145037	70.4	8.47	44.1	108.4	9.62	389
-3	62194	145117	68.4	8.41	44	105.8	9.6	394
-6	62194	145217	65.7	8.39	43.7	104.7	9.79	398
-9	62194	145257	65.1	8.38	43.6	104	9.78	401
-12	62194	145357	65	8.4	43.5	103.5	9.75	401
-15	62194	145444	65	8.4	43.5	103.3	9.73	402
RM39.9S	62194	150320	67.4	8.37	43.5	104.6	9.59	397
-3	62194	150446	66.3	8.38	43.1	103.9	9.65	399
-6	62194	150542	64.5	8.39	42.8	103.2	9.78	401
-9	62194	150630	64.4	8.41	43.3	103.3	9.8	402
RM40.75-S	62194	151544	67.4	8.43	43.7	107	0.04	205
-3	62194	151644	66.3	8.44	43.6	106.7	9.81	395
-6	62194	151811	65.6	8.47	43.3		9.9	396
-9	62194	151938	64.6	8.47	43.3	106,3 106	9.95 10.04	397 401
N 44 0 0	20404	450000	00.0		100 1000 100	2000000000	1,000	
RM-41.3-S	62194	152838	65.8	8.43	43.9	106.2	9.92	391
-3	62194	152942	64.6	8.44	43.6	105	9.94	393
-6	62194	153029	63.5	8.43	43.7	104.1	9.97	396
-9	62194	153118	63,4	8.43	43.6	103.9	9.97	397
RM-42.3-S	62194	153945	63.3	8.37	43.3	100.6	9.66	395
-3	62194	154025	62.8	8.34	43.2	100.6	9.72	399
-6	62194	154100	62.6	8.33	43.2	100.4	9.72	400
-9	62194	154139	62.4	8.33	43.2	100.4	9.75	402
RM-43.25-S	62194	155011	62.8	8.39	42.6	102.1	9.87	396
-3	62194	155051	62.7	8.37	42.6	101.9	9.86	398
-6	62194	155230	62.6	8.38	42.6	102	9.87	401
	62194	155548	62.6	8.4	42.6	101.8	9.85	403
-9	62194	155617	62.7	8.4	42.6	101.7	9.84	404

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp	pH	SpCond	DO	DO	Redox
D OP III	MINIODIT	THE INVIEWO	degF	units	uS/cm	%Sat	mg/l	mV
RM-38.5	62894	132208	72.1	8.53	45.8	101.7	0.00	0.54
				0.00	45.6	101.7	8.86	351
RM-38.6-S	62894	133545	75.8	8.55	45.7	110.8	0.20	070
	62894	133641	70	8.5	44.8	106.2	9.28	370
-3	62894	133706	70.2	8.47	44.8	105.4	9.46	377
-6	62894	133802	69.2	8.43	44.6	105.4	9.37	379
-9	62894	133853	68.9	8.39	44.6		9.45	384
-12	62894	133938	68.4	8.36	44.6	103.2	9.31	388
-15	62894	134102	68	8.27	44.7	100.2	9.09	391
		101102	00	0.21	44.7	92.8	8.45	397
RM-39.0L-S	62894	134654	76.2	8.66	46.3	114.6	0.57	
-3	62894	134819	71	8.57	45		9.57	375
-6	62894	134932	70.2	9.52	43.8	108.4	9.56	383
		101002	10.2	9.52	45,6	124.5	11.07	353
RM-39.0R-S	62894	135352	76	8.49	46	107.2	0.00	200
-3	62894	135448	71.2	8.43	44.7	107.2	8.96	382
-6	62894	135555	69.4	8.39	44.5	103.6	9.11	389
-9	62894	135738	68.6	8.39	44.4		9.24	394
-12	62894	135858	68.5	8.39	44.3	102.1	9.23	398
	2000	100000	0.00	0.55	44.3	101.8	9.22	398
RM-39.9-S	62894	140401	71.6	8.47	44.7	106.3	0.20	007
-3	62894	140452	70.3	8.42	44.6	100.5	9.32	387
-6	62894	140541	68.8	8.43	44.3	103.8	9.29	392
-9	62894	140644	68.4	8.4	44.3		9.38	394
	62894	141324	73	8.45	45	103.4	9.38	397
	62894	141328	73	8.4	44.9	106	9.15	389
	02004	141020	,,,	0.4	44.9	105.9	9.14	392
RM-40.75-S								
-3	62894	141456	68.9	8.41	44.3	102.9	0.00	2005
-6	62894	141552	67.5	8.39	44.3	102.9	9.28	395
-9	62894	141631	67.1	8.41	44.3		9.37	398
_ 3	02004	141001	07.1	0.41	44.2	101.9	9.38	398
RM-41.3-S	62894	142155	70.6	8.48	44.6	108	9.56	200
-3	62894	142250	67.9	8.46	44.2	105.6	9.64	390
-6	62894	142340	67.4	8.47	44.2	105.0		393
-9	62894	142430	67.2	8.47	43.9		9.65	395
-	02034	172700	01.2	0.47	40.8	105.2	9.67	396
RM-42.3-S	62894	143059	68.5	8.39	44.6	103	9.33	204
-3	62894	143059	67.3	8.4	44.5		2.22	394
-6	62894	143245	66.6	2000/00/00	DH239099A	101.8	9,35	395
-9	7.446.007.007.000			8.39	44.4	101.5	9.39	397
-9	62894	143340	66.5	8.41	44.3	101.6	9.41	397
RM-43.25-S	62804	144456	85.6	0.4	42.0	00.0	0.22	205
	62894	144456	65.6	8.4	43.8	99.6	9.32	395
-3	62894	144553	65.3	8.37	43.6	99.4	9.33	398
-6	62894	144700	65.2	8.38	44.1	99.3	9.33	399

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp degF	pH units	SpCond uS/cm	DO %Sat	DO mg/l	Redox
RM38.5	70594	132536	74.7	181815			177.0917	1117
111100.0	70594		71.7	8.51	45.2	101	8.83	355
	70594	133444	74.1	8.43	45	105	8.96	376
RN38.6-S	70594	133604	74.3	8.41	45	405.4	2	
-3	70594	133651	69.8	8.36	44.4	105.1	8.95	380
-6	70594	133736	69.2	8.3		100	8.93	386
-9	70594	133822	69.1	8.34	44.3	99.2	8.91	391
-12	70594	133909	69	8.32	44.2	99.9	8.99	390
-15	70594	134007	68.9	8.33	44.2 44.2	99.5 99.2	8.97	392
	Mariana and American			0.00	17.2	33,2	8.95	393
RM39.0L-S	70594	134530	77	8.67	47.6	113.5	9.4	374
-3	70594	134614	70.8	8.55	44.8	106.3	9.39	383
-6	70594	134654	69.9	8.51	44.2	108.4	9.67	387
-9	70594	134740	69.7	8.44	44	106.1	9.49	392
RM39.0R-S	70594	135152	74.4	8.4	45.5	404.77		
-3	70594	135246	70.9	8.32	45.5	104.7	8.9	390
-6	70594	135339	69.2		44.8	101.8	8.98	395
-9	70594	135428	68.9	8.31	44.2	101.8	9.16	397
-12	70594	135507	68.7	8.32	44.3	101.1	9.12	398
-15	70594	135550	68.7	8.32	44.2	100.9	9.12	398
-10	70034	133330	00.7	8.32	43.9	100.6	9.09	399
RM39.9-S	70594	140018	71.4	8.34	44.9	104.3	9.16	390
-3	70594	140058	69.5	8.33	44.7	101.6	9.1	392
-6	70594	140138	68	8.33	44.5	101.5	9.25	394
-9	70594	140215	67.7	8.33	44,4	101.3	9.26	395
-12	70594	140310	67.7	8.34	44.4	101.3	9.26	395
RM40.75-S	70594	140803	70.3	8.5	440	407.0		
-3	70594	140853	68.8	8.5	44.6 44.6	107.3	9.52	385
-6	70594	140942	67.4	8.5	44.4	106.8	9.64	388
-9	70594	141023	66.7	8.5		105.3	9.66	390
	70004	141023	00,7	0.0	44	105.2	9.72	391
RM41.3-S	70594	141445	68.4	8.51	44.8	106.6	9.66	388
-3	70594	141528	67.3	8.5	44.6	106.3	9.76	390
-6	70594	141612	66.9	8.51	44.6	105.7	9.75	392
-9	70594	141643	66.6	8.52	44.3	106	9.81	392
RM42.3-S	70594	142144	65	8.39	44.3	100.7	9.49	305
-3	70594	142217	64.5	8.41	44.1	100.7	9.53	395 395
-6	70594	142251	64.3	8.41	44.2	100.7	9.57	396
-9	70594	142328	64.1	8.42	44.1	100.7	9.6	397
21110 05 0	70551	440000	20.5		40.0	400.0	in retrease	
RM43.25-S	70594	142836	63.8	8.44	43.8	100.2	9,57	393
-3	70594	142914	63.8	8.41	43.7	100.5	9.6	395
-6	70594	142954	63.7	8.42	43.7	100.3	9.59	396

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp	pН	SpCond	DO	DO	Redox
Беріп	MINIODIT	HHIVIIVISS	degF	units	uS/cm	%Sat	mg/l	mV
RM38.5	71294	133921	73	8.68	45.6	101.0	0.70	
				0.00	45.0	101.9	8.79	363
RM38.6-S	71294	134907	76.5	8.64	45.4	108.9	9.06	363
-3	71294	135015	71.6	8.65	45.1	107.4	9.41	370
-6	71294	135055	70.8	8.61	45	105.7	9.34	374
-9	71294	135135	70.5	8,59	45.3	103.7	9.19	
-12	71294	135213	70.2	8.53	44.7	100.5	8.93	377
-15	71294	135245	70	8.49	44.7	97.8	8.72	382 381
RM39.0R-S	71294	135902	74.8	8.6	45.6	405.0		100
-3	71294	135938	73.2	8.59		105.3	8.92	377
-6	71294	140019	70.7	8.56	45.6	105.6	9.1	380
-9	71294	140051	70.1		45.3	103.6	9.16	384
-12	71294	140137	70.1	8.56	45.1	102.7	9.14	386
-15	71294	140230	70	8.56	45.1	102.6	9.15	387
-10	/ 1204	140230	70	8.55	45.3	102.6	9.15	389
RM39.0L-S	71294	140950	77.1	8.98		117	9.68	368
-3	71294	141044	73.1	8.7	45.7	109.4	9.43	383
-6	71294	141130	71.4	8.7	45.1	108.3	9.51	385
-9	71294	141227	71.4	8.72	45.1	110.3	9.68	385
RM39.9-S	71294	141959	72.4	8.58	45.6	106.7	9.27	386
-3	71294	142025	72.1	8.59	45.9	106.4	9.27	387
-6	71294	142100	70.1	8.58	45,4	105.1	9.35	390
-9	71294	142205	69.7	8.6	45.1	104.9	9.38	391
-12	71294	142310	69.6	8.62	45.3	105.3	9.42	391
RM40.75-S	71294	143023	71.9	8.58	45.4	107.3	0.00	
-3	71294	143105	69.6	8.58	45.1	107.3	9.36	386
-6	71294	143135	68.2	8.58	44.9	104.6	9.37 9.46	389
-9	71294	143203	67.7	8.57	44.8	104	9.40	390 392
RM41.3-S	71294	143740	70.7	8.68	45.0	100.0		
-3	71294	143825	69.3	8.68	45.2 45	109.3	9.66	384
-6	71294	143855	68.5	8.69		108	9.7	386
-9	71294	143947	68.4	8.71	44.8	108.4	9.83	387
-0	11234	140047	00.4	0.71	44.9	108.5	9.84	388
RM42.3-S	71294	144711	68.3	8.52	45	103.1	9.36	389
-3	71294	144747	66.8	8.52	45	101.7	9.39	391
-6	71294	144822	66.3	8.52	44.7	102	9.48	392
-9	71294	144853	66.2	8.52	44.9	101.9	9.47	393
RM43.25-S	71294	145438	65.3	8.58	44.3	101.1	9.5	389
-3	71294	145511	65.3	8.53	44.3	100.9	9.47	392
-6	71294	145537	65.2	8.52	44.5	100.7	9.47	393

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp	pH	SpCond	DO	DO	Redox
	THIND IT	FILIMINIOS	degF	units	uS/cm	%Sat	mg/l	mV
RM38.5	71994	134924	71.4	8.63	45.7	200	120200100	1,379,57
	1.1.00.1	101021	1.1.4	0,03	45.7	102.1	8.96	382
RM38.6-S	71994	135806	73.2	8.51	45.0	400.0		
-3	71994	135848	73.1	8.51	45.8	103.8	8.94	382
-6	71994	135921	69.4	8.44	45.9	103.5	8.92	385
-9	71994	140003	69.2	8.45	44.7	98.9	8.88	391
-12	71994	140033	69.1	8.45	44.9	101.1	9.09	394
-15	71994	140105	69.1	8.48	44.8	100.8	9.07	395
13.50		150100	00.1	0,40	44.8	100.9	9.08	395
RM39.0L-S	71994	140529	74.8	8.61	440			
	71994	140532	74.6	8.57	44.6	108.5	9.19	386
-3	71994	140609	70.7	8.61	46.9	109.3	9.27	389
-6	71994	140639	69.7		45.2	105.6	9.35	390
-9	71994	140710	69.6	8,6	44.8	105	9.38	392
	71004	140710	09.0	8.58	44.5	105.1	9.4	394
RM39.0R-S	71994	141110	73.1	8.57	45.0			50778074078
-3	71994	141146	70.2	8.59	45.8	104.5	9.01	392
-6	71994	141218	69.4		45.2	103.3	9,19	393
-9	71994	141249	68.7	8.54	44.9	102.4	9.18	398
-12	71994	141318	68.6	8.52	44.7	102.1	9.23	400
-15	71994	141352	68.6	8.52	44.8	101.7	9.2	401
10	71004	141002	00.0	8.54	45	101.6	9.2	401
RM39.9-S	71994	141907	70.9	8.57	44.0	1011		
-3	71994	141952	69.1	8.55	44.9	104.1	9.19	393
-6	71994	142019	68.6	8.55	45.1	103.5	9.32	397
-9	71994	142054	68.3	8.56	45	103.3	9.35	398
-12	71994	142126	68.3	8.59	45	102.8	9.34	399
1	7 1004	142120	00.3	0.09	44.8	103.1	9.36	398
RM40.75-S	71994	142754	70.5	8.58	45.3	104.4	0.00	
-3	71994	142825	69.4	8.6	45.1	104.4	9.26	395
-6	71994	142853	67.3	8.59	44.8	103.8	9.32	395
-9	71994	142927	66.8	8.58	44.5	102.5	9.41	397
	,,,,,,	112021	00.0	0.50	44.5	102.6	9.48	399
RM41.3-S	71994	143505	69	8.65	44.8	107.0	0.00	
-3	71994	143540	67.4	8.68	45	107.6	9.69	395
-6	71994	143622	67	8.66	44.9	106,5 106,3	9.76	394
-9	71994	143651	66.8	8.68	44.9	106.3	9.8	396
-175	, 1004	140001	00.0	0.00	44.5	100.4	9.82	396
RM42.3-S	71994	144256	65.5	8.59	44.6	102.2	0.50	205
-3	71994	144328	65.2	8.57	44.4	102.2	9.58	395
-6	71994	144420	65.2	8.54	44.4	102 101.7	9.59	397
-9	71994	144449	65	8.54	44.4	101.7	9.56	400
	1.1004	1274440	00	0.04	44.4	101.0	9.58	401
RM43.25-S	71994	145007	64.5	8.63		100	9.47	200
-3	71994	145045	64.3	8.6	44.2	99.8	27.0 (2.5)	388
-6	71994	145115	64.3	8.56	44.2	3.14(9)(F)(102.5-0	9.48	392
3,70	11004	140110	04.0	0.00	44.2	99.9	9.49	396

Appendix 9. Water quality parameters measured in Mokelumne River and Lake Lodi, May 26, 1994 through July 25, 1994.

River Mile/ Depth	Date MMDDYY	Time HHMMSS	Temp degF	pH	SpCond	DO	DO	Redox
		THE RELIEF CO.	degr	units	uS/cm	%Sat	mg/l	mV
RM38.5	72594	130128	69.9	8.71		100.4	8.96	386
RM38.6-S	72594	131138	72.0	0.57	202	100000000000000000000000000000000000000	1007000	000
-3	72594	131227	73.3 68.2	8.57	45.7	106.3	9.14	379
-6	72594	131310		8.65	45.2	104.5	9.51	381
-9	72594	131340	67.6	8.61	45	101.5	9.28	385
-12	72594	131419	67.4	8.58	45	100.2	9.19	389
-15	72594	131503	67.2	8.56	44.7	100.3	9.21	392
	72004	131303	66.7	8.5	44.4	95	8.78	394
RM39.0L-S	72594	131824	75.2	0.0				
-3	72594	131858	69.8	8.6	47.7	103.7	8.74	388
-6	72594	131927	68.4	8.57	45.7	101.2	9.03	394
-9	72594	132020	68	8.62	44.9	103.8	9.42	393
	12004	102020	00	8.63	44.6	104.2	9.49	395
RM39.0R-S	72594	132347	73.1	8.58	45.8	105.1	9.06	205
-3	72594	132503	69.2	8.57	45	100.9	9.07	395
-6	72594	132549	67.8	8.58	44.8	100.5	9.18	399
-9	72594	132649	67.4	8.59	44.8	100.5	9.22	401
-12	72594	132735	67.2	8.56	44.7	100.1	9.19	402
-15	72594	132752	67.2	8.57	44.7	99.9	9.18	405 404
RM39.9-S	72594	133753	69.3	0.6	45.4	222	6.00	
-3	72594	133831	69	8.6 8.6	45.1	103.9	9.33	394
-6	72594	133906	67.4	8.59	45.3	103.7	9.34	395
-9	72594	133936	67.1	8.61	44.9 45.1	102.5	9,4	398
-12	72594	134008	67.1	8.59	45.1	102.2 102.2	9.4 9.41	398 401
RM40.75-S	72594	134506	68	8.59	45.4	NAVI III	1.000	
-3	72594	134554	67.8	8.59	45.1	102.6	9.35	398
-6	72594	134629	66.7	8.62	45	103.3	9.43	400
-9	72594	134707	65.5	8.64	45	103.1	9.53	399
	12007	104707	00,0	0.04	44.9	101.6	9.51	400
RM41.3	72594	135054	67.9	8.69	45.2	106.8	9.75	394
-3	72594	135145	66.4	8.69	45	105.4	9.77	396
-6	72594	135220	66	8.68	45.1	105.3	9.81	398
-9	72594	135257	65.9	8.69	45	105.3	9.82	399
M42.3-S	72594	135759	65.9	8.62	45.3	101.2	9.44	398
-3	72594	135828	65	8.61	45	101.4	9.56	400
-6	72594	135854	64.6	8.59	44.7	101.4	9.6	402
-9	192012 200000	135925	64.5	8.59	45.1	101.5	9.61	403
M43.25-S	72594	140409	64.1	8.59	44.6	99.3	9.45	403
-3	124 CO	140444	63.9	8.56	44.4	98.6	9.4	406
-6	72594	140528	63.8	8.56	44.5	98.6	9.42	407

Location		Fish#	FL(mm)	TL(mm)	WT(g)	The second second second	Sp. Act.	Total ATPase	Total Protei
UPSHA	B 03/25/94	1 2	45 51	48	0.9	8.14E-04	2.28	2.34	1.03
UPSHAS	B 03/25/94	3	50	55	1.5	9.02E-04	1.89	2.18	1.14
UPSHAE	8 03/25/94	4	43	53 45	1.2	8.06E-04	2.19	1.42	0.65
UPSHAE	8 03/25/94	5	56	60	1.7	7.68E-04	7.98	3.76	0.47
UPSHAE		6	57	61	1.8	7.87E-04 7.93E-04	3.11	2.9	0.93
UPSHAE		7	55	59	1.7	8.28E-04	3.28	3,15	0.98
JPSHAE JPSHAE		8	60	65	2.2	8.01E-04	0.59	4.69 0.93	1.39
JPSHAE		9	55	59	1.6	7.79E-04	1.62	1.79	1,58
WIDD	04/11/94	10	53	56	1.4	7.97E-04	2.7	3.33	1.23
WIDD	04/11/94	2	78 89	82	4	7.25E-04	3.69	9.69	2.63
WIDD	04/11/94	3	82	98 91	7.2	7.65E-04	3.97	19.68	4.98
MIDD	04/11/94	4	84	93	5.6	7.43E-04	4.2	10,43	2.48
WIDD	04/11/94	5	93	102	8.4	7.71E-04 7.92E-04	2.7	10.88	4.02
WIDD	04/11/94	0	78	83	4.6	8.04E-04	5.2 4.29	14.13	2.72
WIDD	04/11/94	7	77	84	4.2	7.09E-04	3.57	13.14 9.93	3.06
IPSHAB IPSHAB	CALL CONTRACT	1	81	89	3.5	4.96E-04	1.92	5.31	2.79
PSHA8		3	71	77	1.9	4.16E-04	1.31	1.6	1.22
PSHAB		3	83 73	75	2.5	5.93E-04	0.47	0.99	2.11
PSHAB		5	69	68	1.9	6.61E-04	3.02	4,69	1.55
PSHAB		6	68	63	1.3	5.20E-04	2.7	4.81	1.78
PSHAB	04/12/94	7	65	58	1	4.80E-04 5.13E-04	1.91	2.04	1.07
PSHAB	04/12/94	8	54	50	0.8	6.40E-04	1.57	2.04	1.3
PSHAB	04/25/94	1	67	73	3.5	9.00E-04	3.94	1.73 8.27	1.17
PSHAB	04/25/94	2	69	78	4	8.43E-04	2.69	9.07	3.38
PSHAB PSHAB	04/25/94	3	78	84	4.6	7.76E-04	4.23	12.09	2.86
PSHAB	04/25/94 04/25/94	5	80	89	5.7	8.09E-04	1.99	10.12	5.09
PSHAB	04/25/94	6	68 70	74	3.5	8.84E-04	2,68	7.16	2.67
PSHAB	04/25/94	7	70	76 79	3.8	8.66E-04	3.74	8.02	214
WIDD	04/25/94	1	101	110	4.3	8.72E-04	4.03	11.23	2.79
WIDD	04/25/94	2	93	102	8.4	7.51E-04 7.92E-04	3,43 4,03	13.7	3.99
WIDD	04/25/94	3	105	116	12.7	8.14E-04	5	16.23	4.03
WIDD	04/25/94	4	99	108	8.8	6.99E-04	4.88	14.31	4.05 2.95
WIDD	04/25/94	5	86	96	6.6	7.46E-04	4.44	13.82	3,11
WIDD	04/25/94	6	87	94	7.3	8.79E-04	3.07	11.68	3.79
PSHAB	05/10/94	1	78	82	5	9.07E-04	3,37	12.71	3.78
SHAB	05/10/94 05/10/94	3	80 75	87	6	9.11E-04	2.52	9.75	3.87
SHAB	05/10/94	4	77	82 83	5 4.5	9.07E-04	2.68	9.07	3.38
SHAB	05/10/94	5	75	81	4	7.87E-04 7.53E-04	3.93	17,95	4.57
SHAB	05/10/94	6	75	81	5	9.41E-04	3.48	10.55 9.81	3.63
VIDD	05/10/94	1	102	93	9.4	1.17E-03	7.17	19.62	2.74
VIDD	05/10/94	2	93	84	6.5	1.10E-03	5.74	22.52	3.92
VIDO	05/10/94	3	95	87	6.5	9.87E-04	6.07	21.41	3.53
VIDD	05/10/94	5	90	82 85	5.4	9.79E-04	5.23	14,99	2.87
VIDD	05/10/94	8	83	75	8.5 4.5	1.06E-03	3.3	17.77	5.38
SHAB	05/23/94	1	84	93	6.3	1.07E-03 7.83E-04	6.95 1.94	16.29 6.66	2.34
SHAB	05/23/94	2	78	85	5.4	8.79E-04	2.49	8.11	3.42
SHAB	05/23/94	3	76	83	5.2	9.09E-04	3.89	12.19	3.13
SHAB	05/23/94	4	74	82	5.5	9.98E-04	2.26	5.39	2.38
SHAB	05/23/94 05/23/94	5	72 78	80	5	9.77E-04	1.08	3.7	3.43
VIDD	05/23/94	1	101	87 110	5.9 10.3	8.96E-04	2.6	7.22	2.78
DDIV	05/23/94	2	91	100	8	7.74E-04 8.00E-04	1.8	5.06	2.81
/IDD	05/23/94	3	89	99	7.2	7.42E-04	2.73	9.38 6.47	3.05
/IDD	05/23/94	4	90	98	7.5	7.97E-04	0.89	2.34	2.63
//00	05/23/94	5	90	98	8.2	8,71E-04	0.62	2.06	3.35
/IDD	05/23/94	6	92	102	7.9	7.44E-04	4.88	9.98	2.08
/IDO /IDO	06/10/94	1 2	95	105	9.8	8.47E-04	3.37	9	2.87
ODI	06/10/94	3	102 89	112 96	9.5 7.1	6.76E-04 8.02E-04	2.06	5.63	2.73
100	06/10/94	4	87	95	7.3	8.51E-04	1.97	3.66	1.85
IDD	06/10/94	5	95	104	8.6	7.85E-04	2.98	1.69 5.53	2.35 1.88
IDD	06/10/94	6	95	100	8.2	8.20E-04	3.63	7.92	2.18
IDD	06/10/94	7	100	107	10	8.16E-04	1.75	4.59	2.62
SHAB	06/24/94	1	87	95	7.9	9.21E-04	0.48	2.2	4.55
'IDD	06/24/94	1	98	110	10.8	8.11E-04	2.44	9.75	4
OOI	06/24/94	2	100	110	11	8.26E-04	3.27	13.36	4.09
100	08/24/94	3	105	118	13.8	8.84E-04	2.57	10,88	4.22
100	08/24/94	5	96 92	105	10.6	9.16E-04	1.04	5.11	4.9
	08/24/94	6	98	101	8.9 11.6	8.64E-04 9.21E-04	1,96	5.67	2.9
	06/24/94	7	105	114	13.3	8.21E-04 8.98E-04	1.92	6.47	3.37
	07/10/94	1	118	127	14.1	6.88E-04	1.21	16.27 6.42	3.86 5.33
	07/10/94	2	117	127	12.4	6.05E-04	1.75	8.9	5.09
	07/10/94	3	100	110	10.4	7.81E-04	5.36	14.37	2.68
	07/10/94	4	100	112	11.1	7.90E-04	1.99	10.72	5.38
	07/10/94	5	95	104	8.9	7.91E-04	2.25	7.94	3.53
	07/10/94	6	94	104	8.7	7.73E-04	1.91	12.5	6.53
	07/10/94 07/23/94	7	87	95		9.21E-04	3.15	7.9	2.5
	07/23/94	2	88 98	109		8.00E-04	1,51	3.21	2.13
	07/23/94	3	101	111	10.2 8.4	7.88E-04 6.14E-04	0.53	1.82	3.47
	07/23/94	4	101	111		8.26E-04	1.73	3.04 6.86	4.2 3.97
TACTO IN						A-9-2-2-2		-16 WW.	40.00
100	0/123/94	5	102	112	10.9	7.78F-04	2.63	9.2	3.5
	07/23/94 07/23/94	5	102	112		7.76E-04 8.90E-04	2.63 5.22	9.2	3.5 2.45